MILITARY SPECIFICATION SHEET

WIRE, ELECTRICAL, POLYTETRAFLUOROETHYLENE (PTFE) INSULATED, 200°C, 600 VOLTS, EXTRUDED INSULATION

This amendment forms a part of Military Specification Sheet MIL-W-16878/4B(NAVY), dated 10 August 1981, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

TABLE I, under "Conductor diameter (nominal) (inch)" across from wire size 32:

Delete	and substitute
0.0089	0.0080
.0089	.0080
.0089	.0080

PAGE 2

TABLE I, under "Wire size" across from "16" delete: "4/".

PAGE 3

TABLE I, under footnotes, Delete: "4/ Under MPD-1506, type E, 16 AWG size was heavier."

Under "REQUIREMENTS"; Add: "Heat resistance: Condition at 290°C."

PAGE 4

Under "REQUIREMENTS", "Fungus resistance:" Delete "Applicable" and substitute "Not applicable."

Review activities:
Navy - AS, EC

User activities:
Navy - OS, MC

Preparing activity:
Navy - SH
(Project 6145-N307-1)

FSC 6145

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:26Z
Check the source to verify that this is the current version before use.