INCH-POUND

MIL-C-70770 (AR)
4 November 1992

MILITARY SPECIFICATION

CONTAINERS, SHIPPING AND STORAGE: PA 137, PA 138 AND PA 141, FOR THE M139 MINE DISPENSER SYSTEM

This Specification is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document contains requirements not normally covered by drawings and provides Quality Assurance provisions for the fabrication of parts, assembly and packing of the Container: Air Mounting Hardware, used in the M139 Mine Dispenser System.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation. (See 6.5)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document, should be addressed to: Commander U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1095
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:59Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, standard Quality Assurance Provisions, General Specification for.

STANDARDS

MILITARY

MIL-STD-1190- Minimum Guidelines for level C Preservation, Packing and Marking.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Ave, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

8837375	ARRADCOM Environmental Testing Criteria for OCONUS shipping container
12553085	Mounting Kit, Mine Dispenser: Air System M139
12564879	Fabrication, Fiberglass, Reinforced, Plastic, Shipping and Storage Containers

PUBLICATIONS

ITOP 1-2-601	US Army TECOM International Test Operation Procedure "LABORATORY VIBRATION SCHEDULES"

(Copies of drawings, publications, and other Government documents required by the contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the Contracting Activity.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-D-2563 - Classifying Visual Defects in Glass Reinforced Laminate Parts.

(Application for copies shall be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

2.3 Order of precedence. In the event of a conflict between text of this document and the references cited herein, the text of this document shall take precedence. Nothing in the document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.1.1 Cushion certification. All cushion material associated with the shipping containers must have a material certification.

3.2 Components and assemblies. The containers, shipping and storage: Support Panel, Mine Dsipenser left (12553072) and Mounting Kit, Mine Dispenser, Air System Accessories (12564839) shall comply with all requirements specified on applicable and associated drawings and with all requirements of the applicable specification.

3.3 Container tests. (At ambient termperature 65 $\pm$ 5°F).

3.3.1 Environmental tests. When the Air System Mounting Hardware (PA137, PA138 or PA141) or equivalent is placed inside the container the container shall enable the hardware to withstand the environmental conditions specified below. After each test, the content shall be examined and shall not be damaged, deformed, punctured or malfunction.

3.3.1.1 Pressure retention. The container shall be subjected to the pressure retention test as specified in 4.5.1.

3.3.1.2 Secured cargo vibration. All three types of shipping containers shall be subjected to the Vibration test as specified in 4.5.2, followed by pressure retention test as specified in 3.3.1.1.

3.3.1.3 Drop tests. The PA138 and PA141 containers shall be subjected to the edgewise drop test and the PA137 container shall be subjected to the free fall drop test as specified in 4.5.3.

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:59Z
Check the source to verify that this is the currenversion before use.

3.3.1.4 Cornerwise and 7 foot drop. The PA138 and PA141 containers shall be subjected to the cornerwise drop test and the PA137 shall be subjected to the seven(7) foot drop test as specified in 4.5.4.

3.3.1.5 Loose cargo vibration. All three containers shall be subjected to the loose cargo test as specified in 4.5.5.

3.3.2 Latch mechanism. The container latch assemblies shall require no more than 25 pounds force to open/close when tested as specified in 4.5.6

3.4 Fabrication process. The container shall be fabricated in accordance with good commercial practice in a clean, dry, safe environment. Departures from the fabrication sequence presented in drawing #12564879, shall obtain prior approval from the contracting officer.

3.5 Workmanship.

3.5.1 Workmanship (general). The container shall be fabricated and finished in a manner that does not diminish the durability, serviceability, safety and general appearance as intended by the requirements. All hardware, gaskets, padding and internal supports shall be free of damage properly cut and fit, and securely attached to the container.

3.5.2 Workmanship (structural). Minor surface irregularities such as scuffs, and scratches are allowed providing the exterior coating (gel coat) is not removed. Workmanship shall be in accordance with good commercial practices as listed on dwg 12564879 (Reference ASTM-D-2563, Level IV) and dwg. 12927377 and dwg. 12927348, except where detail drawing indicate a need for special criteria.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:59Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection (4.3)

b. Quality Conformance Inspection (4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample, as designated by the Contracting Officer, for evaluation in accordance with the provisions Table I.

4.3.2 Rejection. Rejection for poor workmanship shall be as stated in ASTM-D-2563 for acceptance with level IV per dwg. 12564879 unless otherwise indicated. In addition, the presence of any 7 or more of the 28 different defects listed shall be cause for rejection.

4.3.3 Requalification. The contractor shall be subjected to another First Article for the component or assembly affected as stipulated in the contract, if any of the following occur:

a. Manufacturing techniques or process controls which affect the form, fit, or function of the assembly are revised by either the contractor or one of his subcontractors supplying parts or assemblies or materials.

b. The contractor relocates his production facilities or portions thereof.

c. The contractor desires to use a new subcontractor (unqualified) for materials, parts or assemblies.

d. A change occurs in the design, material, performance or assembly of the shipping container.

e. A lapse in production for a period of 90 days or as stipulated in the contract.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:59Z
Check the source to verify that this is the currentversion before use.

TABLE I. First article inspection.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE Shipping and Storage Container: Air System	SHEET 1 OF 1	DRAWING NUMBER See Below
			NEXT HIGHER ASSEMBLY ---

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Shipping and Storage Container: PA 138 and PA 141 (12553072)			
	Examination for defects	2-0-1	3.5	4.4.2.1 and 4.4.2.2
	Environmental tests	2-0-1	3.3.1	4.5.1 thru 4.5.5
	Latch mechanism	2-0-1	3.3.2	4.5.6
	Lamination/fabrication (Destructive test)	1-0-1	3.4	4.5.7
	Shipping and Storage Container: PA 137 (12564839)			
	Examination for defects	2-0-1	3.5	4.4.2.14
	Environmental tests	2-0-1	3.3.1	4.5.1 thru 4.5.5
	Latch mechanism	2-0-1	3.3.2	4.5.6
	Lamination/fabrication (Destructive test)	1-0-1	3.4	4.5.7

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:59Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lot shall comply with the lot formation provision of MIL-A-48078.

4.4.2 Examination and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteriestics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified . When cited herein, attributes sampling inspection shall be conducted in accordance with Table II below using the levels stated in the Classification of Characteristics paragraphs.

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:59Z
Check the source to verify that this is the currentversion before use.

TABLE II Attributes sampling inspection

Lot size	Inspection Level	
	I Major	II Minor
2 to 8	*	3
9 to 15	*	3
16 to 25	*	3
26 to 50	*	3
51 to 90	*	4
91 to 150	125	5
151 to 280	125	6
281 to 500	125	7
501 to 1200	125	9
1201 to 3200	125	10
3201 to 10000	125	10
10001 to 35000	296	10
35001 to 150000	296	10
150001 to 500000	346	10
500001 and over	431	10

Numbers under inspection levels indicate sample size; asterisks (*) indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

b. Alternative quality conformance provisions. Unless otherwise specified herein or provided for in the contract, alternative quality conformance procedures, methods or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation and approval (see 6.6). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality assurance provisions herein. In cases of dispute as to whether the contractor's proposed alternative provides equal assurance, the provisions of this specification shall apply. All approved alternative inspection provisions shall be specifically incorporated into the contractor's quality program plan or detailed inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:59Z
Check the source to verify that this is the currentversion before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70770 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Shipping and Storage Container: PA 141	1 OF 1	12553072 (-1)
			NEXT HIGHER ASSEMBLY 12553085

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Location of bulkheads, cushions and straps	Level I	3.2	Scale
102	Latch nut torque	Level I	3.2	Torque wrench
103	Latch mechanism	Level I	3.3.2	4.5.6
104	Poor workmanship (structural)	Level I	3.5.2	4.4.3.1
Minor				
201	Poor workmanship (general)	Level II	3.5.1	Visual/Gage
202	Marking incorrect	Level II	3.2	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Shipping and Storage Container: PA 138	1 OF 1	12553072(-2)
			NEXT HIGHER ASSEMBLY 12553085

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Location of bulkheads, cushions and straps	Level I	3.3	Scale or equiv.
102	Latch nut torque	Level I	3.3	Torque wrench
103	Latch mechanism	Level I	3.3.2	4.5.6
104	Poor workmanship (structural)	Level I	3.5.2	4.4.3.1
Minor				
201	Marking incorrect	Level II	3.2	Visual/Gage
202	Poor workmanship (general)	Level II	3.5.1	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Breather Valve	1 OF 1	12564757
			NEXT HIGHER ASSEMBLY 12564800/12564812

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Air flow in direction 'P'	10-0-1	3.2	Tester
102	Air flow in direction 'V'	10-0-1	3.2	Tester
103	Valve not crack at 3.0 + 0.5 psig	10-0-1	3.2	Tester
104	Valve not reseal after flow by 2.0 psig	10-0-1	3.2	Tester
Minor				
201	Finish	Level II	3.2	Visual
202	Poor workmanship	Level II	3.5	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70770 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Base Shell, Container: PA137 and PA139	1 OF 1	12564761
			NEXT HIGHER ASSEMBLY 12564812

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Lamination/fabrication	Level I	3.4	4.5.7 or Process Certification
102	Barcol hardness	Level I	3.2	Barcol Hardness Tester
103	Overall shell dimension	Level I	3.2	Tape
104	Poor workmanship (structural)	Level I	3.5.2	4.4.3.1
Minor				
201	Poor workmanship (general)	Level II	3.5.1	Visual/Gage

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Cover Shell, Container: PA137 and PA139	1 OF 1	12564763
			NEXT HIGHER ASSEMBLY 12564770

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Lamination/fabrication	Level I	3.4	4.5.7 or Process Certification
102	Barcol hardness	Level I	3.2	Barcol Hardness Tester
103	Overall shell dimension	Level I	3.2	Tape
104	Poor workmanship (structural)	Level I	3.5.2	4.4.3.1
Minor				
201	Poor workmanship (general)	Level II	3.5.1	Visual/Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Container Cover Assembly: PA137	1 OF 1	12564770
			NEXT HIGHER ASSEMBLY 12564839

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Gasket not secured and not trimmed flush to seat in flange groove	Level I	3.2	Gage
Minor 201	Poor workmanship (general)	Level II	3.5.1	Visual/Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70770 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Glass, Fabric, Triaxial	1 OF 1	12564772
			NEXT HIGHER ASSEMBLY 12564879

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Material	Each lot	3.1	Certification
Minor	None defined			

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70770 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Resin	1 OF 1	12564773
			NEXT HIGHER ASSEMBLY 12564879

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Material	Each lot	3.1	Certification
Minor	None defined			

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70770 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Gelcoat	1 OF 1	12564796
			NEXT HIGHER ASSEMBLY 12564879

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Material	Each lot	3.1	Certification
Minor	None defined			

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:59Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Cover Shell, Container: PA 138 and PA141	1 OF	12564797
			NEXT HIGHER ASSEMBLY 12564799

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Lamination/fabrication	Level I	3.4	4.5.7 or Process Certification
102	Barcol Hardness	Level I	3.2	Barcol Hardness Tester
103	Overall Shell Dimension	Level I	3.2	Steel Tape
104	Poor workmanship (structural)	Level I	3.5.2	4.4.3.1
Minor				
201	Poor workmanship (general)	Level II	3.5.1	Visual/Gage

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70770 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Base Shell, Container: PA 138 and PA141	1 OF 1	12564798
			NEXT HIGHER ASSEMBLY 12564800

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Lamination/fabrication	Level I	3.4	4.5.7 or Process Certification
102	Barcol Hardness	Level I	3.2	Barcol Hardness Tester
103	Overall Shell Dimension	Level I	3.2	Steel Tape
104	Poor workmanship (structural)	Level I	3.5.2	4.4.3.1
Minor				
201	Poor workmanship (general)	Level II	3.5.1	Visual/Gage

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70770 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.12	Container Cover Assembly: PA 141	1 OF 1	12564799(-1)
			NEXT HIGHER ASSEMBLY 12553072(-1)

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Slot location	Level I	3.2	Steel tape & caliper
102	Slot dimension	Level I	3.2	caliper
Minor				
201	Marking	Level II	3.2	Visual
202	Poor workmanship (general)	Level II	3.5.1	Visual/Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.13	Container Cover Assembly: PA 138	1 OF 1	12564799(-2)
			NEXT HIGHER ASSEMBLY 12553072(-2)

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Slot location	Level I	3.2	Steel tape & caliper
102	Slot dimension	Level I	3.2	caliper
Minor				
201	Marking	Level II	3.2	Visual
202	Poor workmanship (general)	Level II	3.5.1	Visual/Gage

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH 4.4.2.14	TITLE Container Base Assembly: PA 141	SHEET 1 OF	DRAWING NUMBER 12564800(-1)
			NEXT HIGHER ASSEMBLY 12553072(-1)

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Slot location and dimension	Level I	3.2	Steel tape & calipers
102	Location of handles	Level I	3.2	Steel tape
103	Location of latches	Level I	3.2	Steel tape
104	Lamination of parts to base	Level I	3.2	Visual
105	Sealing compound applied	Level I	3.2	Visual
Minor				
201	Location of pressure fitting incorrect	Level II	3.2	Visual
202	Poor workmanship (general)	Level II	3.5.1	Visual/Gage

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:59Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70770 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.15	Container Base Assembly: PA 138	1 OF 1	12564800(-2)
			NEXT HIGHER ASSEMBLY 12553072(-2)

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Slot location and dimension	Level I	3.2	Steel tape & calipers
102	Location of handles	Level I	3.2	Steel tape
103	Location of latches	Level I	3.2	Steel tape
104	Lamination of parts to base	Level I	3.2	Visual
105	Sealing compound applied	Level I	3.2	Visual
Minor				
201	Location of pressure fitting	Level II	3.2	Steel tape
202	Poor workmanship (general)	Level II	3.5.1	Visual/Gage

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH 4.4.2.16	TITLE Container Base Assembly: PA 137	SHEET 1 OF	DRAWING NUMBER 12564812
			NEXT HIGHER ASSEMBLY 12564839

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Slot location and dimension	Level I	3.2	Steel tape & calipers
102	Location of handles	Level I	3.2	Steel tape
103	Location of latches	Level I	3.2	Steel tape
104	Lamination of parts to base	Level I	3.2	Visual
105	Sealing compound applied	Level I	3.2	Visual
Minor				
201	Location of pressure fitting	Level II	3.2	Steel tape
202	Poor workmanship (general)	Level II	3.5.1	Visual/Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70770 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.17	Shipping and Storage Container: PA 137	1 OF	12564839
			NEXT HIGHER ASSEMBLY 12553085

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Location of bulkheads and cushions	Level I	3.2	Scale
102	Latch nut torque	Level I	3.2	Torque wrench
103	Latch mechanism	Level I	3.3.2	4.5.6
104	Poor workmanship (structural)	Level I	3.5.2	4.4.3.1
Minor				
201	Marking	Level II	3.2	Visual
202	Poor workmanship (general)	Level II	3.5.1	Gage/Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85; which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.18	Adhesive	1 OF 1	12564855
			NEXT HIGHER ASSEMBLY
			12564770/12564799
			12564800/12564812

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Material	Each lot	3.1	Certification
Minor	None defined			

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.19	Core, Balsa	1 OF 1	12564857
			NEXT HIGHER ASSEMBLY: 12564798/12564797

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Material	Each lot	3.1	Certification
Minor	None defined			

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.20	Gasket, Extruded	1 OF 1	12564756
			NEXT HIGHER ASSEMBLY 12564770/12564799

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Material per drawing	Each lot	3.1	Certification
Minor 201	Poor workmanship (general)	Level II	3.5.1	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70770 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.21	Handle, Assembly	1 OF 1	12564861
			NEXT HIGHER ASSEMBLY 12564812/12564800

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Handle position bent	Level I	3.2	Clamp/Angle
102	90 degree stop	Level I	3.2	Visual/Angle
103	Parts assembled	Level I	3.2	Visual
Minor				
201	Poor workmanship	Level II	3.5.1	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is decribed in the First Article and Quality Conformance Inspection tables beginning with 4.4.2.

4.4.3.1 Structural workmanship testing. The container's structure shall be checked for workmanship in accordance with ASTM-D-2563, level II. Failure of 9 or more defects in each test sample shall result in rejection of the lot.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections specified hereis is identified in the "Inspection Method Reference" column of the Classification of Characteristics listings starting with 4.4.2.1. Contractor inspection equipment designs shall be submitted for Government approval as specified in the contract. Designs which provide variable measurements instead of attributers data are preferred in order to facilitate the use of statistical process control See MIL-A-48078 and 6.3.

4.5 Methods of inspection.

4.5.1. Pressure retention. Remove breather valve in container base and install an air test (schrader) valve. Torque air test valve to 30 in-lbs. The containers shall be subjected to the pressure retention test No. 15 of ARDEC Drawing 8837375 except the criteria for acceptance shall be that there exists no loss of pressure greater than .05 psi in 10 minutes for PA137, PA138 and PA141. In addition, PA138 and PA141 shall be pressurized to an internal air pressure of 2.25 ± .25 psi only. Each container opening shall be opened and closed three times before conducting the pressure retention test. The latch nuts shall be torqued to 65 ± 5 inch pounds prior to testing. The container shall be tested at ambient temperature. After successful completion of pressure test, reinstall breather valve and torque to 30 in-lbs.

4.5.2 Secured cargo vibration. The container shall be subjected to the Secured Cargo Vibration per ITOP 1-2-601 wheeled vehicle and pressure retention test. Following the tests the container cushions and bulkheads shall be intact.

4.5.3 Edgewise drop. The PA132, PA138, PA141 containers shall be subjected to the Edgewise drop Test No. 3 of ARDEC Drawing 8837375 followed by pressure retention test.

4.5.4 Cornerwise drop. The PA137, PA138, PA141 containers shall be subjected to the Cornerwise Drop Test No. 4 of ARDEC Drawing 8837375 followed by Pressure Retention Test.

4.5.5 Loose cargo vibration. All containers shall be subjected to the Loose Cargo Vibration Test No. 14 of ARDEC Drawing No. 8837375, followed by pressure retention test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

4.5.6 Latch mechanism. The container shall be subjected to a latch force test as specified in Table I. The latch assemblies on the container shall require no more than 25 pounds force to open and close. The force shall be applied and measured within one inch of each latch lever end in a direction perpendicular to the latch lever. The latch nuts shall be torqued to 65 ± 5 inch pounds in the closed position prior to testing. The container shall be tested at ambient temperature and pressure.

4.5.7 Lamination fabrication process test. The lamination/fabrication process of the container shall be determined in accordance with the test procedures listed in drawing 12564879. Unless otherwise indicated in the test procedures, three specimens shall be taken from each container to do each test. The measured values shall be compared to the lowest determined value listed in drawing 12564879. If any of the specimens fails to meet the requirement, the container lot shall be rejected.

5. PACKAGING.

5.1 Packaging.

5.1.1 Level A. Level A packaging not applicable.

5.1.2 Level B. Level B packaging not applicable.

5.1.3 Level C. Level C packaging shall be in accordance with MIL-STD-1190.

5.2 Packing.

5.2.1 Level A. Level A packing not applicable.

5.2.2 Level B. Level B packing not applicable.

5.2.3 Level C. Level C packing shall be in accordance with MIL-STD-1190.

5.3 Marking.

5.3.1 Level A. Level A marking not applicable.

5.3.2 Level B. Level B marking not applicable.

5.3.3 Level C. Level C marking shall be in accordance with MIL-STD-1190.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:59Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The Shipping and Storage Container: Air Mounting Hardware Kit is to be used to store the supporting structure of the M139 VOLCANO Mine Dispenser Air System.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of the specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (See 2.1).

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to: Commander, US Army Armament Research, Development and Engineering Center (ARDEC), ATTN: SMCAR-QAT-M, Picatinny Arsenal, New Jersey 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.4 Distribution of ammunition data cards and test data. Distribution of data cards and functioning test data shall include the following: Commander, US Army Armament Research, Development and Engineering Center, ATTN: SMCAR-QAT-M, Picatinny Arsenal, New Jersey 07806-5000.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as US Army Armament Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal or Picatinny Arsenal drawings. Technical data originally prepare by these activities is now under the cognizance of ARDEC.

6.6 Submission of alternative quality conformance provisions. Unless otherwise specified in the contract, proposed alternative quality conformance provisions will be submitted by the contractor for evaluation by the technical activity responsible for the preparation of this specification.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:59Z
Check the source to verify that this is the currentversion before use.

6.7 Subject term (key word) listing.
Latching Mechanism
Mounting Hardware Kit: Air
Pressure Retention

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1095-A780)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
3. DOCUMENT TITLE		

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON
c. ADDRESS (Include Zip Code)	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:59Z
Check the source to verify that this is the current version before use.