MIL-P-80072B
5 March 1985
SUPERSEDING
MIL-P-80072A
10 February 1969

MILITARY SPECIFICATION

PUNCHING MACHINE, METAL, POWER DRIVEN, SINGLE END TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers power driven metal punching machines of the single end type with equipment and accessories specified herein.

1.2 Classification. This specification covers machines of the sizes listed in table I. The size to be furnished shall be as specified (see 6.2.1 and table I).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-M-18058 - Machinery, Metal and Woodworking, Packaging of.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSG, Memphis, Tennessee 38114-5297, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-H28 - Screw Thread Standards for Federal Services.

FED-STD-376 - Preferred Metric Units for General Use by the Federal Government.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

U. S. DEPARTMENT OF LABOR

OSHA 2206 - General Industry, OSHA Safety and Health Standards (29 CFR 1910).

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issue of the documents which are indicated as DoD adopted shall be the issue listed in the current DODISS and the supplement thereto, if applicable.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI/NFPA 79 - Metalworking Machine Tools and Plastics Machinery, Electrical Standard for.

(Application for copies should be addressed to the American National Standards Institute, ATTN: Sales dept., 1430 Broadway, New York, NY 10018.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D 3951 - Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103).

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2.1), a sample shall be subjected to first article inspection (see 4.3 and 6.3).

3.2 Design. The machine shall be new and one of the manufacturer's current models capable of metal punching operations in accordance with the requirements herein. The machine shall include all components, parts, and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement, and repair.

3.2.1 Measurement systems. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) shall be used in the design and construction of the machine. When only one system of measurements is acceptable, the particular system required shall be as specified (see 6.2.1). In this specification, all measurements, dimensions, sizes, and capacities are given in US units. These measurements may be converted to SI units through the use of the conversion factors and methods specified in FED-STD-376.

3.2.1.1 Measuring and indicating device calibrations. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) shall be used to graduate measuring and indicating devices such as scales, depth stops, carriage stops, dial indicators, pressure gauges, temperature indicators, and other similar devices. When only one system of graduation is acceptable, the particular graduation required shall be as specified (see 6.2.1). Regardless of the measurement system used, all measuring and indicating devices on the machine shall be graduated in the same system.

3.2.1.1.1 Dual calibrations. When specified (see 6.2.1), measuring and indicating devices shall be graduated in both the US and the SI System of Measurements. When a dual US and SI system is furnished, both dials shall have independent zero adjustments and both dials shall be calibrated in such a manner that the last dial graduation progresses into and is continuous with the first dial graduation as the dial is rotated through the zero position.

3.2.2 Reclaimed materials. The machine may contain reclaimed materials provided such materials will not jeopardize the machine's intended use and performance. The reclaimed materials shall have been reprocessed, remanufactured, or recycled in a manner which will restore them to the same chemical composition and physical properties as the materials originally selected for use on the machine.

3.2.3 Energy efficiency. The machine and all its applicable components that directly consume energy in normal operation shall be designed and constructed for the highest degree of energy efficiency as governed by the latest developments available within the industry.

3.2.4 Controls. All operating controls shall be located convenient to the operator at his normal work station.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

3.2.5 Safety and health requirements. Covers, guards, or other safety devices shall be provided for all parts of the machine that present safety hazards. The safety devices shall not interfere with the operation of the machine. The safety devices shall prevent unintentional contact with the guarded part, and shall be removable to facilitate inspection, maintenance, and repair of the parts. All machine parts, components, mechanisms, and assemblies furnished on the machine, whether or not specifically required herein, shall comply with all of the requirements of OSHA 2206 that are applicable to the machine itself. Additional safety and health requirements shall be as specified (see 6.2.1 and 6.4).

3.2.6 Mercury restriction. The machine shall not contain mercury or mercury compounds nor be exposed to free mercury during manufacture.

3.2.7 Asbestos restriction. Asbestos and materials containing asbestos shall not be used on or in the machine.

3.2.8 Environmental protection. The machine shall be so designed and constructed that, under the operating, service, transportation, and storage conditions described herein, the machine shall not emit materials hazardous to the ecological system as prescribed by federal, state, or local statutes in effect at point of installation (see 6.4).

3.2.9 Lubrication. Means shall be provided to insure adequate lubrication for all moving parts. Recirculating lubrication systems shall include a filter which is cleanable or replaceable. Each lubricant reservoir shall have means for determining fluid level. All oil holes, grease fittings, and filler caps shall be accessible.

3.2.10 Interchangeability. To provide for replacement of worn or damaged parts, all parts shall be manufactured to definite dimensions and tolerances that will permit installation of replacement parts without modification of the part or machine.

3.3 Construction. The machine shall be constructed of parts which are new, without defects, and free of repairs. The structure shall be capable of withstanding all forces encountered during operation of the machine to its maximum rating and capacity without permanent distortion.

3.3.1 Castings and forgings. All castings and forgings shall be free from defects such as scale and mismatching. Processes such as welding, peening, plugging, or filling with solders or pastes shall not be used on castings or forgings to reclaim any defective components for use on the machine. Such processes may be used only for enhancing surface finish and appearance.

3.3.2 Welding, brazing, or soldering. Welding, brazing, or soldering shall be employed only where specified in the original design. None of these processes shall be employed as a repair measure for any defective part.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

3.3.3 Fastening devices. All screws, pins, bolts, and other fasteners shall be installed in a manner to prevent change of tightness. Fastening devices subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently installed.

3.3.4 Surfaces. All surfaces shall be clean and free of sand, dirt, fins, sprues, flash, scale, flux, and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be in accordance with the manufacturer's commercial practice.

3.3.5 Painting. Unless otherwise specified (see 6.2.1), the machine shall be painted in accordance with the manufacturer's commercial practice, provided that all surfaces to be painted shall be cleaned of all foreign matter and at least one coat of primer and one coat of finish color is applied.

3.3.6 Threads. All threaded parts used on the machine and its related attachments and accessories shall conform to FED-STD-H28.

3.3.7 Gears. All gears shall be constructed from a material suitable for the intended purpose. All gears shall be machined and heat treated by a process that will impart the hardness, surface finish, and toughness that will enable the gear train to transmit full rated torque of the drive motor without gear damage, failure, or premature deterioration and wear.

3.4 Components.

3.4.1 Frame. The machine shall be provided with either an iron or steel frame of the "C" style, having a base, column, and overhang to form a workpiece opening or throat. The frame shall be sufficiently rigid to withstand stresses imposed during the punching operations specified in 3.6. The base shall have provisions for securing the machine to a mounting surface. When specified (see 6.2.1), the top of the frame shall be provided with a rigging eye or other means to facilitate lifting the machine.

3.4.2 Table. The machine shall be provided with a table for supporting the workpiece. The table top shall be of iron or steel construction, and of sufficient size and strength to support workpiece sizes up to the size specified in table I, while performing punching operations at any point on the workpiece. When required, the table top dimensions shall be the size specified (see 6.2.1).

3.4.3 Machine drive. Unless otherwise specified, the punching action of the machine shall be accomplished by either a mechanical type drive or a

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

hydraulic type drive. When only one type drive is acceptable, the particular drive shall be as specified (see 6.2.1). The drive shall be designed to assure that sufficient energy is developed for accomplishing the performance requirements specified herein. Unless otherwise specified (see 6.2.1), the drive shall be controlled by a foot pedal type control.

3.4.3.1 Mechanical type drive. The mechanical type drive when furnished shall be provided with an electric motor driven flywheel for transmitting the required punching force to a machine ram through a drive shaft. The drive shall include clutch and brake mechanisms for controlling the punching action. The clutch mechanism shall be arranged to provide both single and continuous stroke operation. The punching motion of the ram shall be guided by a machine way arrangement.

3.4.3.2 Hydraulic type drive. The hydraulic type drives when furnished shall be provided with a hydraulic power unit to include at least an electric motor, hydraulic pump, fluid reservoir, ram cylinder unit, and connecting hose or tubing. The fluid reservoir shall be provided with a fluid level gauge, and a hydraulic fluid filter with replaceable type element. The hydraulic ram cylinder shall be the double acting type. The drive shall be provided with hydraulic fluid control devices including a high pressure relief valve. The connecting hose or tubing shall be capable of withstanding fluid pressure up to 150 percent of the maximum allowable working pressure of the hydraulic system. The hydraulic type drive shall be designed to provide both single and continuous stroke operation.

3.4.4 Punch holder. The machine shall be provided with a punch holder for holding the punches in punching position under the ram or ram cylinder unit. The punch holder shall maintain punch alignment with the die without tool distortion while utilizing die clearances of not more than .006 inch. Means shall be provided for radially locating the punches in the punch holder. The punch holder shall accommodate round, square, and rectangular punches.

3.4.5 Die base. The machine shall be provided with a die base for holding the dies in position for receiving the punches. The die base shall hold the dies in such a manner to assure punch alignment as specified in 3.4.4. The die base shall be directly supported by the machine frame. Means shall be provided for radially locating the dies in the die base. The die base shall accommodate round, square, and rectangular dies.

3.4.6 Stripper. The machine shall be provided with a workpiece stripper or other means necessary for automatically releasing the workpiece from the punch when the punch is withdrawn from the die.

3.4.7 Punches and dies. When required, punches and dies of sizes and shapes specified (see 6.2.1) shall be furnished. The punches and dies shall be tool steel, hardened, and ground for accuracy. Each punch and die shall be permanently marked for size and identification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

3.4.8 Tool storage. Each machine shall be provided with a tool storage cabinet, located either on the machine or furnished as a separate unit. The cabinet shall be constructed to enclose and accommodate at least 8 cubic feet of tooling.

3.4.9 Front to back and side gauge. Unless otherwise specified (see 6.2.1), the machine shall be furnished with a front to back gauge and side gauge for aligning the workpiece under the ram and punch. The gauge shall be provided with a guide bar for controlling workpiece alignment across the table from front to back along the Y axis. The guide bar shall move across the table in machine ways or by other means to maintain a constant plane, parallel with the X axis throughout the adjustment range. The guide bar shall be provided with not less than 9 workpiece stops for aligning the workpiece from the center of the ram and punch to either side along the X axis. The workpiece stops shall be arranged to slide along and be locked to the guide bar at intervals for programming required hole locations. The guide bar and workpiece stops shall be provided with micrometer dials or micrometer gauges for measuring workpiece settings of 0.001 inch or less in both the X and Y axes. Each axis of the gauge shall be provided with scales, permanently marked in graduated increments, for measuring the distance from the center of the ram and punch through the adjustment range for the X and Y axes as specified in table I. A device shall be provided for locking the gauge in position at any point within the adjustment ranges.

3.4.10 Stylus type workpiece positioning gauge. When specified (see 6.2.1), the size 2, 3, 4, 5, 6, 7, 8, 9, and 10 machines shall be furnished with a stylus type workpiece positioning gauge for aligning the workpiece under the ram and punch. The gauge shall be a duplicator style device with a template table, workpiece holding carriage, and hand controlled stylus for locating the punching points on the templates and actuating the machine drive for punching. The table shall have provisions for securely holding template sizes up to the size specified in table I. The carriage shall be provided with at least two clamps for holding the workpieces for punching operations.

3.4.11 Electrical system. Unless otherwise specified (see 6.2.1), the electrical system shall conform to ANSI/NFPA 79. Each machine shall draw all of its electrical power from a single 230/460 volt, 3 phase, 60 Hz circuit. Each machine shall have a fused safety disconnect switch or circuit breaker. The machine shall be initially wired for operation on 460 volts. An identified terminal for grounding the machine when it is installed shall be mounted in or near the disconnect switch. The terminal shall be suitable for connecting the size grounding conductor specified in ANSI/NFPA 79 for the disconnect fuse rating.

3.4.11.1 Motors. Motors shall be rated for continuous duty and shall have ball or roller bearings of the sealed and permanently lubricated type. Unless otherwise specified (see 6.2.1), each motor enclosure shall meet the requirements for a dripproof enclosure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

3.4.11.2 Solid state components. Solid state design shall be used throughout for electronic components.

3.4.11.3 Control circuit voltage. Auxiliary control circuits shall be isolated from the input electric power supply by a low-voltage transformer having a secondary voltage no greater than 115 volts.

3.5 Size and capacity. Unless otherwise specified (see 6.2.1), the size and capacity of the machine shall be not less than those specified in table I for the machine size specified.

3.6 Performance. The machine shall be capable of punching and notching in not less than 50,000 psi mild steel to meet the capacity requirements of table I. The hole punching operations shall be performed with standard style tooling with no shear on punches or dies. There shall be no deformation of the workpiece.

3.6.1 Additional performance requirements. Performance features required in addition to, or in lieu of, the requirements herein shall be as specified and fully described (see 6.2.1).

3.7 Standard equipment. Unless otherwise specified all standard equipment normally furnished by the manufacturer, shall be furnished. Additional equipment required shall be furnished as specified and fully described (see 6.2.1).

3.8 Optional equipment. Optional equipment shall be furnished as specified and shall be fully described (see 6.2.1).

3.9 Repair parts. Such repair parts as are specified (see 6.2.1), shall be furnished.

3.10 Marking on plates, charts, and decals. All words on plates, charts, and decals shall be in the English language. Characters shall be engraved, etched, embossed, or stamped in boldface on a contrasting background.

3.10.1 Lubrication chart or plate. Unless otherwise specified (see 6.2.1), a lubrication chart or plate shall be permanently and securely attached to each machine. If a chart is furnished, it shall be placed in a transparent plastic folder, or permanently sealed between clear plastic sheets, with suitable means of mounting. The chart or plate shall contain the following information:

Points of lubricant application
Servicing interval
Type of lubricant
Viscosity

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

TABLE I. Sizes and characteristics.

Characteristics	Machine sizes									
	1	2	3	4	5	6	7	8	9	10
Throat depth, inches	12	18	30	30	30	30	30	48	30	36
Workpiece size, inches	12x24	18x30	30x30	30x60	30x30	30x54	30x60	48x60	30x48	36x48
Stroke length, inches	1/2	1/2	1/2	1/2	1/2	1/2	1/2	5/8	5/8	5/8
Shut height, inches	4-3/4	5-1/4	5-1/4	5-1/4	5-1/4	5-1/4	5-1/4	5-1/4	5-1/4	5-1/4
Max. diameter, inches in	2.000	3.500	3.500	3.500	5.000	5.000	5.000	5.000	5.000	5.000
Material thickness, inches	.036	.089	.089	.105	.105	.105	.105	.135	.187	.187
Diameter, inches in	.372	1.000	1.000	1.000	2.000	2.500	2.500	2.250	1.125	1.125
Max. material thickness inches	.250	.250	.250	.250	.250	.250	.250	.250	.500	.500
Front to back and side gauge adjustment range, inches										
In "X" axis	24	30	30	60	30	54	60	60	48	48
In "Y" axis	12	15	30	30	30	30	30	48	30	36
Stylus type workpiece positioning gauge template size, inches	N/A	18x30	30x30	30x50	30x30	30x50	30x50	48x50	30x48	36x48

NOTE: Requirements are not less than the figures shown.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

3.10.2 Nameplate. Unless otherwise specified (see 6.2.1), a nameplate shall be securely attached to each machine. The nameplate shall contain the information listed below. If the machine is a special model, the model designation shall include the model of the basic standard machine and a suffix identified in the manufacturer's permanent records. The captions listed may be shortened or abbreviated, provided the entry for each caption is clear as to its identity.

Nomenclature
Manufacturer's name
Manufacturer's model designation
Manufacturer's serial number
Net weight of machine
Power input (volts, total amps, phase, frequency)
Contract Number or Order Number
National Stock Number or Plant Equipment Code
Date of manufacture

3.11 Hour meter. Unless otherwise specified (see 6.2.1), the machine shall be equipped with an hour meter. The hour meter shall be installed to display accumulated operating time of the main drive motor. The meter shall be of the nonresetting type and shall have a range of 0 to 99,999 hours in increments of one hour. The meter shall be sealed to prevent the entrance of dust and moisture and shall be mounted to withstand shock and vibration generated by the machine. Upon reaching 99,999 hours, the meter readout shall automatically return to zero and continue to accumulate time.

3.12 Digital readout system. Unless otherwise specified (see 6.2.1), a digital readout system shall be installed on the X and Y axes of travel. The digital readout system shall consist of a position feedback device, an electronic display for each axis specified with all related components, mounting hardware, and electrical equipment necessary to assure complete operation of the system. The system shall be capable of providing a readily visible digital display over the full working range of each machine axis on which installed. The system resolution shall be 0.0005 inch. The system accuracy shall be $\pm$0.002 inch per 6 inches and repeatability shall be 0.002 inch.

3.12.1 Position feedback device. A position feedback device including all related components, hardware, and electrical equipment shall be provided for each axis having a readout system. The feedback device shall be of the independent type. The length of the feedback device for each axis specified shall be at least 1-3/4 inches longer than the full axis travel to prevent damage to the feedback device in the event of overtravel. Each feedback device shall be installed with a cover or guard to prevent physical damage to any portion of the feedback device. The device shall provide axis travel feedback over the entire range of axis travel for each specified axis. The feedback device shall be either of the rack and pinion or glass scale type. The feedback devices shall be guarded to prevent damage to them during operation of the machine.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

3.12.2 Electronic display console. The electronic display console shall contain a universal digital display with individual digits not less than .70 inch high. The console shall be capable of displaying at least six digits simultaneously. The display console shall also provide keyboard entry, memory, absolute-incremental counting, data preset, power failure indicator, inch/metric conversion, absolute zero recall, and calculator add and subtract. The electronic display console shall be installed so as to be readily accessible and easily read from the operator's work position. The console shall be mounted to withstand any shock and vibration generated by the machine. The connecting cable shall be armored and shall be installed so as not to interfere with the normal operation of the machine. The cable shall be securely fastened to the structure of the machine.

3.13 Technical data. When technical data is required it shall be furnished in accordance with the requirements of the contract. All technical data furnished shall be written in the English language.

3.14 Workmanship. Workmanship of the machine and accessories shall be of a quality equal to that of the manufacturer's commercial equipment of the type specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When first article inspection is required, it shall be applied to the first article submitted in accordance with 3.1. Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examination in 4.5 and all tests in 4.6. Failure of the item to pass the first article examination and all tests shall be cause for rejection.

4.4 Quality conformance inspection. Quality conformance inspection shall be applied to each item prior to being offered for acceptance under

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

the contract. Unless otherwise specified (see 6.2.1) quality conformance inspection shall consist of at least the examination in 4.5, the test in 4.6.1, and the inspection in 4.7. Failure of the item to pass the examination, test and inspection shall be cause for rejection.

4.5 Examination. The machine and equipment shall be visually examined to determine compliance with all requirements of this specification.

4.6 Tests.

4.6.1 Operational test. The machine shall be operated at no load for not less than 30 minutes. Proper operation of all controls, motors, adjusting mechanisms, and accessories shall be verified during the trial period.

4.6.2 Performance test. The machine shall be tested for conformance with 3.6 by punching holes using standard style tooling in metal test pieces of not less than 50,000 psi mild steel. The machine shall punch at least 12 holes each of the diameters specified for each of the material thicknesses specified in table I for the size machine being tested. The holes shall be punched without deforming the test pieces.

4.7 Packaging inspection. Packaging of each item shall be inspected to determine compliance with the requirements of Section 5.

5. PACKAGING

5.1 Packaging, packing, and marking. Unless otherwise specified, packaging, packing, and marking shall be in accordance with ASTM D 3951. When specified (see 6.2.1), level A preservation, level A or level B packing, and special marking shall be accomplished in accordance with MIL-M-18058.

6. NOTES

6.1 Intended use. The machines covered by this specification are intended for use in short run metal punching operations where close tolerances are required.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Size required (see 1.2 and table I).

c. When first article is required for inspection and approval (see 3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

d. If machine is required to be configured in a specific measurement system (US or SI), state required system (see 3.2.1).

e. If measuring and indicating devices are required to be graduated in a specific measurement system (US or SI), state required system (see 3.2.1.1).

f. Dual calibrations (US and SI), if required (see 3.2.1.1.1).

g. Additional safety and health requirements, if required (see 3.2.5 and 6.4).

h. Painting, if different (see 3.3.5).

i. Rigging eye, if required (see 3.4.1).

j. Table top dimensions, if different (see 3.4.2).

k. If machine drive is to be a specific type, state required type (see 3.4.3).

l. Foot petal type control, if different (see 3.4.3).

m. Punches and dies, specify sizes and shapes required (see 3.4.7).

n. Front to back and side gauge, if different (see 3.4.9).

o. Stylus type workpiece positioning gauge, if required (see 3.4.10).

p. Electrical system and input power, if different (see 3.4.11).

q. Motor enclosure, if different (see 3.4.11.1).

r. Size and capacity, if different (see 3.5).

s. Additional performance features, if required (see 3.6.1).

t. Standard equipment, if different (see 3.7).

u. Specify and fully describe optional equipment, if required (see 3.8).

v. Specify applicable repair parts, if required (see 3.9).

w. Lubrication chart or plate, if different (see 3.10.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

x. Nameplate, if different (see 3.10.2).

y. Hour meter, if different (see 3.11).

z. Digital readout system, if different (see 3.12).

aa. First article inspection, if different (see 4.3).

bb. Quality conformance inspection, if different (see 4.4).

cc. If packaging, packing, and marking in accordance with MIL-M-18058 is required, specify level required and specification number (see 5.1).

6.2.2 Contract data requirements. Required technical data such as operators manuals, parts lists, wiring diagrams, foundation and anchor bolt plans, and acceptance test reports should be specified on a DD Form 1423, Contract Data Requirements List, incorporated into the contract.

6.3 First article. When first article inspection is required, the item to be tested should be the first item offered for acceptance under the contract. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.4 Safety, health, and environmental protection requirements. Paragraph 3.2.5 requires compliance only with those OSHA requirements that concern the machine itself. It does not require compliance with those OSHA requirements that concern "the machine in its operating environment" such as noise levels, radiation levels, electromagnetic emissions, noxious vapors, air contaminants, and heat. Since OSHA limits the total hazard level of these hazards in the environment (and does not limit the hazard level of individual machines in the environment) the procuring activity is advised to analyze the existing hazard levels in the proposed operating environment, and specify additional machine requirements that will integrate the new machine into its future operating environment. The machine shall be equipped with all point-of-operation guarding normally furnished as standard on the manufacturer's commercial machines supplied to the commercial market. If specific point-of-operation guarding is required, the procuring activity should specify the exact configuration of the guard required, as in most cases, the guard configuration is dependent on the size and configuration of the workpieces. The above, and any other additional safety, health, and environmental protection requirements should be specified in detail under 6.2.1 (g).

6.5 Cross-reference of classification changes. Machine classification changes from previous issues of this specification are as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

MIL-P-80072	MIL-P-80072A	MIL-P-80072B
	Size 1 (new size)	Size 1 (no change)
Type I, size 1	Size 2	Size 2 (no change)
Type I, size 2	Size 3	Size 3 (no change)
	Size 4 (new size)	Deleted
		Size 4 (new size)
Type II, size 1 and 2	Size 5	Size 5 (no change)
		Size 6 (new size)
		Size 7 (new size)
	Size 6 (new size)	Size 8
		Size 9 (new size)
	Size 7 (new size)	Size 10

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - AL
Navy - SH
Air Force - 99

Review Activities:
DLA - GS
Air Force - 84

User Activities:
Navy - YD, MC

Preparing Activity:
DLA - IP

(Project 3445-0094)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEFENSE LOGISTICS AGENCY
Commander
Defense Industrial Plant Equipment Center
ATTN: DIPEC-SSG
Memphis, TN 38114-5297

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Commander
Defense Industrial Plant Equipment Center
ATTN: DIPEC-SSG
Memphis, TN 38114-5297

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-80072B	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.