MILITARY STANDARD

AUTOMATED ENGINEERING

DOCUMENT PREPARATION SYSTEM

RELAYS, SOLID-STATE

TO ALL HOLDERS OF MIL-STD-35-101(MI):

1. THE FOLLOWING PAGES OF MIL-STD-35-101(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
5-37	10 May 1976	(REPRINTED WITHOUT CHANGE)	
5-38	19 October 1976	5-38	10 May 1976
5-43	19 October 1976	5-43	10 May 1976
5-44	10 May 1976	(REPRINTED WITHOUT CHANGE)	
5-47	10 May 1976	(REPRINTED WITHOUT CHANGE)	
5-48	19 October 1976	5-48	10 May 1976
5-49	19 October 1976	5-49	10 May 1976
5-50	19 October 1976	5-50	10 May 1976
5-51	10 May 1976	(REPRINTED WITHOUT CHANGE)	
5-52	19 October 1976	5-52	10 May 1976
5-59	19 October 1976	5-59	10 May 1976
5-60	10 May 1976	(REPRINTED WITHOUT CHANGE)	
5-61	19 October 1976	5-61	10 May 1976
5-62	10 May 1976	(REPRINTED WITHOUT CHANGE)	
5-63	10 May 1976	(REPRINTED WITHOUT CHANGE)	
5-64	19 October 1976	5-64	10 May 1976
5-75	19 October 1976	5-75	10 May 1976
5-76	10 May 1976	(REPRINTED WITHOUT CHANGE)	
5-101	19 October 1976	5-101	10 May 1976
5-102	10 May 1976	(REPRINTED WITHOUT CHANGE)	
5-105	19 October 1976	5-105	10 May 1976
5-106	10 May 1976	(REPRINTED WITHOUT CHANGE)	
5-109	10 May 1976	(REPRINTED WITHOUT CHANGE)	
5-110	19 October 1976	5-110	10 May 1976
5-111	10 May 1976	(REPRINTED WITHOUT CHANGE)	
5-112	19 October 1976	5-112	10 May 1976
5-115	19 October 1976	5-115	10 May 1976
5-116	19 October 1976	5-116	10 May 1976
5-123	19 October 1976	5-123	10 May 1976
5-124	10 May 1976	(REPRINTED WITHOUT CHANGE)	
5-125	19 October 1976	5-125	10 May 1976
5-126	10 May 1976	(REPRINTED WITHOUT CHANGE)	
5-127	10 May 1976	(REPRINTED WITHOUT CHANGE)	
5-128	19 October 1976	5-128	10 May 1976

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

2. RETAIN THIS NOTICE AND INSERT BEFORE TABLE OF CONTENTS.

3. Holders of MIL-STD-35-101(MI) will verify that page changes and additions indicated above have been entered. This notice page will be retained as a check sheet. This issuance, together with appended pages, is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army - MI

Review activities:
Army - AT
Army - AV
Army - EL
Army - ME
Army - MR
Army - SG
Army - WC

User activity:
Army - MU

Preparing activity:
Army - MI

(PROJECT EDS-A204)

☆U.S. GOVERNMENT PRINTING OFFICE: 1976/703-020/910

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

5.39 Resistance to Solvents

Code 4828 is the 1006 test code (5.4).

Code 4829 is the 1006 except test code (5.4).

To detail a resistance to solvents test, Code 4839 is mandatory. Other codes are optional.

Code 4839 and an "X", entered on the SRS, will specify to test in accordance with Method 215 of MIL-STD-202.

Code 4838 and a chemical name(s), entered on the SRS, will specify additional solvent(s) to which the parts shall be subjected.

Code 4835 and a letter(s), entered on the SRS, will specify which solvent solutions shown with the subparagraph letter(s) in Method 215 of MIL-STD-202 shall be not used.

Code 4831 and an "X", entered on the SRS, will specify the marking area shall be brushed.

Code 6279 and an "X", entered on the SRS, will specify all surfaces of the device shall be brushed.

Code 4833 is the 1006 requirement code (5.4).

Code 4834 is the 1006 except requirement code (5.4).

Code 4830 and an "X", entered on the SRS, will specify there shall be no evidence of physical damage or degradation of performance. To detail requirements, this code is mandatory.

Code 4836 and an "X", entered on the SRS, will specify that marking shall remain legible after subjection to the solvents specified.

5.40 Salt Spray

Code 4769 is the 1006 test code (5.4).

Code 4770 is the 1006 except test code (5.4).

To detail a salt spray test, Codes 4771 and 4772 are mandatory.

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

Code 4771 and an "X", entered on the SRS, will specify to test in accordance with Method 101 of MIL-STD-202.

Code 4772 and a test condition letter, entered on the SRS, will specify the test condition letter entered shall apply.

Code 4773 and a document designation, entered on the SRS, will specify that special mounting shall be in accordance with the document. The applicable test name from the referenced document shall be entered on the SRS in addition to the document designation (5.7).

Code 4765 and an "X", entered on the SRS, will specify that mounting shall be by normal mounting means.

Code 4766 and an "X", entered on the SRS, will specify that any suitable means of mounting may be used.

Code 4877 is the 1006 requirement code (5.4).

Code 4878 is the 1006 except requirement code (5.4).

Code 4782 and an "X", entered on the SRS, will specify no evidence of corrosion, physical damage or degradation of performance.

Code 2074 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the insulation resistance test.

Code 2075 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the dielectric withstanding voltage at sea level test.

Code 2078 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the turn-on and turn-off time tests.

Code 2079 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the turn-on and turn-off voltage tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

Code 1471 and an "X", entered on the SRS, will specify there shall be no discontinuity during the test.

Code 4703 and an "X", entered on the SRS, will specify the device shall remain within specified tolerance.

Code 2085 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the insulation resistance test.

Code 2086 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the dielectric withstanding voltage at sea level test.

Code 2089 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the turn-on and turn-off time tests.

Code 2090 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the turn-on and turn-off voltage tests.

Code 2091 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the input current sensitivity test.

Code 2092 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the leakage current test.

Code 2093 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the transient voltage test.

Code 2094 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the waveform distortion test.

Code 2095 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the power dissipation test.

5.43 Solderability

Code 4661 is the 1006 test code (5.4).

Code 4662 is the 1006 except test code (5.4).

Supersedes page 5-43 of 10 May 1976.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

To detail a solderability test, it is mandatory to use Code 4683. Other codes are optional.

Code 4683 and an "X", entered on the SRS, will specify to test in accordance with Method 208 of MIL-STD-202.

Code 4666 and a value (quantity), entered on the SRS, will specify the quantity of terminations on each device to be tested. This code is only used when all terminations are not tested.

Code 4667 and a value, entered on the SRS, will specify the depth in inches of immersion in flux and solder. This code and value are entered when the required depth of immersion is to be other than to within 0.05 inch of the body.

Code 4663 and a value, entered on the SRS, will specify the depth in millimetres of immersion in flux and solder.

Code 4664 and a value, entered on the SRS, will specify the standard wrap wire, as defined in Method 208 of MIL-STD-202, is to be wrapped this number of inches from the body of the device.

Code 4665 and a value, entered on the SRS, will specify the standard wrap wire, as defined in Method 208 of MIL-STD-202, is to be wrapped this number of millimetres from the body of the device.

Code 6205 and an "X", entered on the SRS, will specify that special preparations are permitted, such as lead straightening or orientation.

Code 4673 is the 1006 requirement code (5.4).

Code 4674 is the 1006 except requirement code (5.4).

Code 4675 and an "X", entered on the SRS, will specify no evidence of physical damage. This code is mandatory when requirements are detailed. Other codes are optional.

Code 4672 and an "X", entered on the SRS, will specify the device shall meet the evaluation criteria specified in Method 208 of MIL-STD-202.

Code 4677 and an "X", entered on the SRS, will specify the device shall remain within specified tolerance.

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

Code 6219 and a Roman numeral, entered on the SRS, will specify the applicable procedure number.

Code 6220 and a value, entered on the SRS, will specify the storage temperature in degrees Celsius. This code is only used when a temperature other than 71 degrees Celsius is required.

Code 6221 and a value, entered on the SRS, will specify the duration in hours of the high temperature storage. This code is only used when a storage other than 48 hours is required.

Code 6222 and a value, entered on the SRS, will specify the highest operating temperature in degrees Celsius at which the device under test is designed to operate.

Code 6224 and a value, entered on the SRS, will specify the operating time in minutes at the temperature specified with Code 6222. Do not use Code 6224 with Code 6225.

Code 6225 and a value, entered on the SRS, will specify the operating time in hours at the temperature specified with Code 6222. Do not use Code 6225 with Code 6224.

Code 6227 is the 1006 requirement code (5.4).

Code 6228 is the 1006 except requirement code (5.4).

To detail high temperature requirements, it is mandatory to use Code 6229.

Code 6229 and an "X", entered on the SRS, will specify there shall be no evidence of physical damage after exposure to high temperature.

Code 2096 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the insulation resistance test.

Code 2097 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the dielectric withstanding voltage at sea level test.

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

Code 2100 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the turn-on and turn-off time tests.

Code 2101 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the turn-on and turn-off voltage tests.

Code 2102 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the input current sensitivity test.

Code 2103 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the leakage current test.

Code 2104 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the transient voltage test.

Code 2105 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the waveform distortion test.

Code 2106 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the power dissipation test.

5.46 Temperature, Low

Code 6230 is the 1006 test code (5.4).

Code 6231 is the 1006 except test code (5.4).

To detail a low temperature test, it is mandatory to use Code 6232. Other codes are optional.

Code 6232 and an "X", entered on the SRS, will specify to test in accordance with Method 502 of MIL-STD-810.

Code 6234 and a value, entered on the SRS, will specify the storage temperature in degrees Celsius. This code is only used when a temperature other than minus 57 degrees Celsius is required.

Supersedes page 5-48 of 10 May 1976.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

Code 6235 and a value, entered on the SRS, will specify the duration in hours of the low temperature storage. This code is only used when a storage other than 24 hours is required.

Code 6236 and a value, entered on the SRS, will specify the lowest operating temperature in degrees Celsius at which the device under test is designed to operate.

Code 6237 and a value, entered on the SRS, will specify the chamber air velocity in feet per second where the heat transfer rate from the surface of the test item is important.

Code 6238 and a value, entered on the SRS, will specify the chamber air velocity in metres per second where the heat transfer rate from the surface of the test item is important.

Code 6315 or 6316 and a value, entered on the SRS, will specify the operation time at low temperature in minutes and hours, respectively. Do not use these codes together.

Code 6317 is the 1006 requirement code (5.4).

Code 6318 is the 1006 except requirement code (5.4).

To detail low temperature requirements, it is mandatory to use Code 6319.

Code 6319 and an "X", entered on the SRS, will specify there shall be no evidence of physical damage.

Code 2107 and an "X", entered on the SRS, will specify the relays shall conform to the requirments of the insulation resistance test.

Code 2108 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the dielectric withstanding voltage at sea level test.

Supersedes page 5-49 of 10 May 1976.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

Code 2111 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the turn-on and turn-off time tests.

Code 2112 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the turn-on and turn-off voltage tests.

Code 2113 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the input current sensitivity test.

Code 2114 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the leakage current test.

Code 2115 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the transient voltage test.

Code 2116 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the waveform distortion test.

Code 2117 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the power dissipation test.

5.47 Terminal Strength

Code 1409 is the 1006 test code (5.4).

Code 1410 is the 1006 except test code (5.4).

Code 1375 and an "X", entered on the SRS, will specify to test in accordance with Method 211 of MIL-STD-202. This code is mandatory if the test method is to be detailed.

There are eight additional codes to detail the test method. One or more may be entered with a value to specify the test condition letter(s) and applicable value(s). Information concerning them is as follows:

Code 1411 or Code 1419, or both and a value(s), entered on the SRS, will specify test condition letter A and the fore in pounds or newtons, respectively.

Code 1412 and a value, entered on the SRS, will specify test condition letter B and the number (quantity) of bends.

Code 1413 or Code 1420, or both and a value(s), entered on the SRS, will specify test condition letter C and the weight in pounds or kilograms, respectively.

Supersedes page 5-50 of 10 May 1976.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

Code 1414 and an "X", entered on the SRS, will specify test condition letter D applies.

Code 1416 or Code 1421, or both and a value(s), entered on the SRS, will specify test condition letter E and the torque in pound-inches or newton-metres, respectively, to be applied.

Code 1417 is the 1006 requirement code (5.4).

Code 1418 is the 1006 except requirement code (5.4).

To detail requirements, Code 1433 and an "X", entered on the SRS, will specify no evidence of physical damage. This code is mandatory when requirements are to be detailed after the terminal strength test.

Code 6296 and an "X", entered on the SRS, will specify the device shall remain within specified tolerance.

5.48 Thermal Shock

Code 4712 is the 1006 test code (5.4).

Code 4713 is the 1006 except test code (5.4).

To detail a thermal shock test, it is mandatory to use Codes 4714 and 4715.

Code 4714 and an "X", entered on the SRS, will specify to test in accordance with Method 107 of MIL-STD-202.

Code 4715 and a letter, entered on the SRS, will specify the applicable test condition letter.

Code 4719 and a document designation, entered on the SRS, will specify mounting shall be in accordance with the document (5.7).

Code 4720 is the 1006 requirement code (5.4).

Code 4722 is the 1006 except requirement code (5.4).

To detail requirements, Code 4723 and an "X", entered on the SRS, will specify no evidence of physical damage. This code is mandatory when requirements are to be detailed after the thermal shock test.

Codes 4726 and an "X", entered on the SRS, will specify the device shall remain within specified tolerance.

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

Code 2118 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the insulation resistance test.

Code 2119 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the dielectric withstanding voltage at sea level test.

Code 2122 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the turn-on and turn-off time tests.

Code 2123 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the turn-on and turn-off voltage tests.

Code 2124 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the input current sensitivity test.

Code 2125 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the leakage current test.

Code 2126 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the transient voltage test.

Code 2127 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the waveform distortion test.

Code 2128 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the power dissipation test.

5.49 Transient Voltage

Code 1900 is the 1006 test code (5.4).

Code 1901 is the 1006 except test code (5.4).

To detail a transient voltage test, it is mandatory to use Code 1902 or 1914. Other codes are optional.

Supersedes page 5-52 of 10 May 1976.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

Code 1469 and an "X", entered on the SRS, will specify the device shall remain within specified tolerance.

Code 2129 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the insulation resistance test.

Code 2130 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the dielectric withstanding voltage at sea level test.

Code 2133 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the turn-on and turn-off time tests.

Code 2134 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the turn-on and turn-off voltage tests.

Code 2135 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the input current sensitivity test.

Code 2136 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the leakage current test.

Code 2137 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the transient voltage test.

Code 2138 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the waveform distortion test.

Code 2139 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the power dissipation test.

Supersedes page 5-59 of 10 May 1976.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

5.55 Vibration, Low Frequency

Code 1465 is the 1006 test code (5.4).

Code 1466 is the 1006 except test code (5.4).

To detail the low frequency vibration test, Code 1467 is mandatory. Other codes are optional.

Code 1467 and an "X", entered on the SRS, will specify to test in accordance with Method 201 of MIL-STD-202.

Code 1470 and an "X", entered on the SRS, will specify the duration in hours of vibration per axis. This code should only be used when the required vibration per axis is other than 2 hours as specified in Method 201 of MIL-STD-202.

There are three codes available to specify the method of mounting. Only one may be used. Information concerning them is as follows:

Code 4731 and an "X", entered on the SRS, will specify any suitable mounting method may be used.

Code 4730 and an "X", entered on the SRS, will specify normal mounting means shall be used.

Code 4729 and a document designation, entered on the SRS, will specify to mount in accordance with the document (5.7).

There are several codes available to specify the direction of motion. These may be used as required.

Code 1535 and an "X", entered on the SRS, will specify motion shall be perpendicular to the longitudinal axis.

Code 1536 and an "X", entered on the SRS, will specify motion shall be perpendicular to the longitudinal axis.

Code 4979 and an "X", entered on the SRS, will specify motion shall be on the centerline of the most sensitive axis.

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

Code 4978 and an "X", entered on the SRS, will specify motion shall be 90 degrees from the centerline of the most sensitive axis.

Code 1537 and an "X", entered on the SRS, will specify motion shall be in each of three mutually perpendicular axes.

Code 6201 and a value, entered on the SRS, will specify the percent of rated load to be applied during test.

Code 1474 is the 1006 requirement code (5.4).

Code 1475 is the 1006 except requirement code (5.4).

To detail requirements, Code 1476 and an "X", entered on the SRS, will specify no evidence of physical damage. This code is mandatory when requirements are to be detailed after the low frequency vibration test.

Code 1480 and an "X", entered on the SRS, will specify the device shall remain within specified tolerance.

Code 2140 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the insulation resistance test.

Code 2141 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the dielectric withstanding voltage at sea level test.

Code 2144 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the turn-on and turn-off time tests.

Code 2145 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the turn-on and turn-off voltage tests.

Code 2146 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the input current sensitivity test.

Supersedes page 5-61 of 10 May 1976.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

Code 2147 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the leakage current test.

Code 2148 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the transient voltage test.

Code 2149 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the waveform distortion test.

Code 2150 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the power dissipation test.

5.56 Vibration, Random

Code 1425 is the 1006 test code (5.4).

Code 1426 is the 1006 except test code (5.4).

To detail a random vibration test, in accordance with Method 214 of MIL-STD-202, Codes 1427, 1428, and 1438 or 1431 are mandatory. Other codes are optional.

Code 1427 and an "X", entered on the SRS, will specify the random vibration test shall be performed in accordance with Method 214 of MIL-STD-202. When Code 1427 is used, Codes 1428 and 1438 or 1431 are mandatory.

Code 1428 and a Roman numeral and letter, entered on the SRS, will specify the applicable test condition Roman numeral and letter as selected from Method 214 of MIL-STD-202. Enter the Roman numeral (I or II) and follow with the letter, for example, IB or IIK.

It is mandatory that one duration of application per axis be specified. Information concerning codes is as follows:

Code 1438 and a value, entered on the SRS, will specify the duration in minutes of the random excitation per axis. The options are 3 or 15 minutes. Do not use Code 1438 with Code 1431.

Code 1431 and a value, entered on the SRS, will specify the duration in hours of the random excitation per axis. The options are 1.5 and 8 hours. Do not use Code 1431 with Code 1438.

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

There are three codes to specify the monitoring instrumentation of the excitation. Only one may be selected.

Code 1452 and an "X", entered on the SRS, will specify any suitable system may be used to monitor excitation.

Code 1453 and an "X", entered on the SRS, will specify the use of a calibrated ac to dc converter and a strip chart recorder to monitor excitation.

Code 1459 and an "X", entered on the SRS, will specify the use of a calibrated oscilloscope to monitor excitation.

Code 1430 and a value, entered on the SRS, will specify the quantity of vibration monitoring test points.

Code 1439 or 1462 may be used to specify the location of the test point(s).

Code 1439 and an "X", entered on the SRS, will specify any suitable location(s) is permitted to mount the monitoring test points.

Code 1462 and an "X", entered on the SRS, will specify the monitoring test points shall be mounted as close as practical to the test specimen.

Code 4678 and a value, entered on the SRS, will specify the percent of rated load to be applied during test.

There are three codes available to specify the method of mounting. Only one may be used. Information concerning them is as follows:

Code 4977 and an "X", entered on the SRS, will specify any suitable mounting method may be used.

Code 4976 and an "X", entered on the SRS, will specify normal mounting means shall be used.

Code 4975 and a document designation, entered on the SRS, will specify to mount in accordance with the document. The applicable test name from the referenced document shall be entered in addition to the document designation (5.7).

Code 1434 is the 1006 requirement code (5.4).

Code 1435 is the 1006 except requirement code (5.4).

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

To detail requirements, Code 1436 and an "X", entered on the SRS, will specify no evidence of physical damage. This code is mandatory when requirements are to be detailed after the random vibration test.

Code 1538 and an "X", entered on the SRS, will specify the device shall remain within specified tolerance.

Code 2151 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the insulation resistance test.

Code 2152 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the dielectric withstanding voltage at sea level test.

Code 2155 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the turn-on and turn-off time tests.

Code 2156 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the turn-on and turn-off voltage tests.

Code 2157 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the input current sensitivity test.

Code 2158 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the leakage current test.

Code 2159 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the transient voltage test.

Code 2160 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the waveform distortion test.

Code 2161 and an "X", entered on the SRS, will specify the relays shall conform to the requirements of the power dissipation test.

Supersedes page 5-64 of 10 May 1976.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.21 (Cont)	Closed-Contact Voltage Drop and Stability (Cont)	
	*Requirements (Select one)	
	Per 1006 document (see 5.4).	1670
	Per 1006 document except (see 5.4) ____	1671
	As follows:	
	Maximum contact voltage drop (V)	1672
	Contact current shall remain constant.	1673
	Contacts shall remain closed when constant current is applied to the input control terminal(s).	1674
5.22	Crosstalk	
	*Test methods (Select one)	
	Per 1006 document (see 5.4).	1680
	Per 1006 document except (see 5.4) ___	1681
	Per MIL-R-28750.	1682
	Paralleled capacitance (pF)	1683
	Minimum input signal voltage (p to p)	1684
	Maximum input signal voltage (p to p)	1685
	Maximum input signal frequency (MHz)	1686
	Measurement terminals (des)	1687

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.22 (Cont)	Crosstalk (Cont)	
	*Requirements (Select one)	
	Per 1006 document (see 5.4).	1690
	Per 1006 document except (see 5.4) ____	1691
	As follows:	
	Minimum attenuation (dB)	1692
5.23	Current Rating	
	*Test methods (Select one)	
	Per 1006 document (see 5.4).	1700
	Per 1006 document except (see 5.4) ____	1701
	Per MIL-R-28750.	1702
	Control voltage (V)	1703
	Bias voltage (V)	1704
	Bias current (mA)	1705
	Contact voltage (V)	1706
	Contact current varied between:	
	*Minimum (mA)	1707
	*Maximum (mA)	1708

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC	
	NAME	CODE
5.40 (Cont)	Requirements (Select one) (Cont)	
	As follows:	
	*No evidence of corrosion, physical damage, or degradation of performance.	4782
	The relays shall conform to the requirements of the following tests:	
	Insulation resistance.	2074
	Dielectric withstanding voltage at sea level.	2075
	Turn-on/turn-off time.	2078
	Turn-on/turn-off voltage.	2079
	Input current sensitivity.	2080
	Leakage current.	2081
	Transient voltage.	2082
	Waveform distortion.	2083
	Power dissipation.	2084

Supersedes page 5-101 of 10 May 1976.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.41	Seal	
	*Test methods (Select one)	
	Per 1006 document (see 5.4).	4733
	Per 1006 document except (see 5.4) ___	4734
	Per MIL-STD-202, Method 112.	4732
	*Test condition letter (Select one)	
	Letter A (A)	4737
	Media for test (name)	4738
	Minimum media path temperature (deg C)	4739
	Letter B (B)	6320
	Media for test (name)	6321
	Minimum media bath temperature (deg C)	6322
	Letter C (C)	6323
	*Leak rate sensitivity (atm cm^3/s)	4741
	*Test procedure (Select one)	
	Test procedure I (I)	4740
	Backfill pressure	
	(psi)	4742
	(kPa)	4736

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC	
	NAME	CODE
5.42 (Cont)	Per MIL-STD-202, Method 213. (Cont)	
	Percent rated load applied (pct)	6204
	*Requirements (Select one)	
	Per 1006 document (see 5.4).	1507
	Per 1006 document except (see 5.4) ____	1508
	As follows:	
	*No evidence of physical damage.	1509
	No discontinuity during test.	1471
	Remain within specified tolerance.	4703
	The relays shall conform to the requirements of the following tests:	
	Insulation resistance.	2085
	Dielectric withstanding voltage at sea level.	2086
	Turn-on/turn-off time.	2089
	Turn-on/turn-off voltage.	2090

Supersedes page 5-105 of 10 May 1976.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.42 (Cont)	The relays shall conform to the requirements of the following tests: (Cont)	
	Input current sensitivity.	2091
	Leakage current.	2092
	Transient voltage.	2093
	Waveform distortion.	2094
	Power dissipation.	2095
5.43	Solderability	
	*Test methods (Select one)	
	Per 1006 document (see 5.4).	4661
	Per 1006 document except (see 5.4) ____	4662
	Per MIL-STD-202, Method 208.	4683
	Number of terminals to be tested (quantity)	4666
	Depth of immersion	
	(in.)	4667
	(mm)	4663
	Distance wrap wire applied from body	
	(in.)	4664
	(mm)	4665

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.44 (Cont)	Requirements (Select one) (Cont)	
	As follows:	
	Relay shall operate correctly at maximum specified bauds.	1896
	Maximum percent distortion at any speed (pct)	1897
5.45	Temperature, High	
	*Test methods (Select one)	
	Per 1006 document (see 5.4).	6216
	Per 1006 document except (see 5.4) ____	6217
	Per MIL-STD-810, Method 501.	6218
	*Procedure (Roman numeral)	6219
	Storage temperature if other than 71 (deg C)	6220
	Storage duration if other than 48 (hr)	6221
	Highest operating temperature (deg C)	6222
	Operation time (Select one)	
	(min)	6224
	(hr)	6225

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC	
	NAME	CODE
5.45 (Cont)	Temperature, High (Cont)	
	*Requirements (Select one)	
	Per 1006 document (see 5.4).	6227
	Per 1006 document except (see 5.4) ____	6228
	As follows:	
	*No evidence of physical damage.	6229
	The relays shall conform to the requirements of the following tests:	
	Insulation resistance.	2096
	Dielectric withstanding voltage at sea level.	2097
	Turn-on/turn-off time.	2100
	Turn-on/turn-off voltage.	2101
	Input current sensitivity.	2102
	Leakage current.	2103
	Transient voltage.	2104
	Waveform distortion.	2105
	Power dissipation.	2106

Supersedes page 5-110 of 10 May 1976.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.46	Temperature, Low	
	*Test methods (Select one)	
	Per 1006 document (see 5.4).	6230
	Per 1006 document except (see 5.4) ____	6231
	Per MIL-STD-810, Method 502.	6232
	Storage temperature if other than -57 (deg C)	6234
	Storage duration if other than 24 (hr)	6235
	Lowest operating temperature (deg C)	6236
	Chamber air velocity	
	(ft/s)	6237
	(m/s)	6238
	Operation time (Select one)	
	(min)	6315
	(hr)	6316

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.46 (Cont)	Temperature, Low (Cont)	
	*Requirements (Select one)	
	Per 1006 document (see 5.4).	6317
	Per 1006 document except (see 5.4) ____	6318
	As follows:	
	*No evidence of physical damage.	6319
	The relays shall conform to the requirements of the following tests:	
	Insulation resistance.	2107
	Dielectric withstanding voltage at sea level.	2108
	Turn-on/turn-off time.	2111
	Turn-on/turn-off voltage.	2112
	Input current sensitivity.	2113
	Leakage current.	2114
	Transient voltage.	2115
	Waveform distortion.	2116
	Power dissipation.	2117

Supersedes page 5-112 of 10 May 1976.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC	
	NAME	CODE
5.48 (Cont)	Requirements (Select one) (Cont)	
	As follows:	
	*No evidence of physical damage.	4723
	Remain within specified tolerance.	4726
	The relays shall conform to the requirements of the following tests:	
	Insulation resistance.	2118
	Dielectric withstanding voltage at sea level.	2119
	Turn-on/turn-off time.	2122
	Turn-on/turn-off voltage.	2123
	Input current sensitivity.	2124
	Leakage current.	2125
	Transient voltage.	2126
	Waveform distortion.	2127
	Power dissipation.	2128

Supersedes page 5-115 of 10 May 1976.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.49	Transient Voltage	
	*Test methods (Select one)	
	Per 1006 document (see 5.4).	1900
	Per 1006 document except (see 5.4) ____	1901
	Per MIL-R-28750.	1902
	Input voltage (V)	1903
	Bias voltage (V)	1905
	Output voltage (V)	1907
	Output current (mA)	1909
	Turn-off voltage (V)	1911
	Per MIL-STD-704.	
	Transient surge voltage	1914
	Transient surge duration (min)	1912
	Interval (s)	1913
	*Equipment (Category)	1915
	*Curve figure (No.)	1916

Supersedes page 5-116 of 10 May 1976.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC	
	NAME	CODE
5.54 (Cont)	Requirements (Select one) (Cont)	
	As follows:	
	*No evidence of physical damage.	1456
	Remain within specified tolerance.	1469
	The relays shall conform to the requirements of the following tests:	
	Insulation resistance.	2129
	Dielectric withstanding voltage at sea level.	2130
	Turn-on/turn-off time.	2133
	Turn-on/turn-off voltage.	2134
	Input current sensitivity.	2135
	Leakage current.	2136
	Transient voltage.	2137
	Waveform distortion.	2138
	Power dissipation.	2139

Supersedes page 5-123 of 10 May 1976.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.55	Vibration, Low Frequency	
	*Test methods (Select one)	
	Per 1006 document (see 5.4).	1465
	Per 1006 document except (see 5.4) ____	1466
	Per MIL-STD-202, Method 201.	1467
	Duration of vibration per axis if other than 2 hours (hr)	1470
	Method of mounting (Select one)	
	Any suitable mounting method.	4731
	Normal mounting means.	4730
	Mount per document from 5.7 (doc des)	4729
	Direction of motion	
	Parallel to longitudinal axis.	1535
	Perpendicular to longitudinal axis.	1536
	On the centerline of most sensitive axis.	4979
	90 degrees from the centerline of the most sensitive axis.	4978
	Three mutually perpendicular axes.	1537
	Percent rated load applied (pct)	6201

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.55 (Cont)	Vibration, Low Frequency (Cont)	
	*Requirements (Select one)	
	Per 1006 document (see 5.4).	1474
	Per 1006 document except (see 5.4) ____	1475
	As follows:	
	*No evidence of physical damage.	1476
	Remain within specified tolerance.	1480
	The relays shall conform to the requirements of the following tests:	
	Insulation resistance.	2140
	Dielectric withstanding voltage at sea level.	2141
	Turn-on/turn-off time.	2144
	Turn-on/turn-off voltage.	2145
	Input current sensitivity.	2146
	Leakage current.	2147
	Transient voltage.	2148
	Waveform distortion.	2149
	Power dissipation.	2150

Supersedes page 5-125 of 10 May 1976.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC	
	NAME	CODE
5.56	Vibration, Random	
	*Test methods (Select one)	
	Per 1006 document (see 5.4).	1425
	Per 1006 document except (see 5.4) ____	1426
	Per MIL-STD-202, Method 214.	1427
	*Test condition (Roman numeral and letter)	1428
	*Duration of application (Select one)	
	(min)	1438
	(hr)	1431
	Monitoring instrumentation of excitation (Select one)	
	Any suitable system.	1452
	Calibrated ac to dc converter and strip chart recorder.	1453
	Calibrated oscilloscope.	1459
	Number of vibration monitoring test points (quantity)	1430

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.56 (Cont)	Per MIL-STD-202, Method 214. (Cont)	
	Location of monitoring points (Select one)	
	Any suitable location.	1439
	As close as practical to test specimen.	1462
	Percent of rated load applied (pct)	4678
	Method of mounting (Select one)	
	Any suitable mounting method.	4977
	Normal mounting method.	4976
	Mount per document from 5.7 (doc des)	4975
	*Requirements (Select one)	
	Per 1006 document (see 5.4).	1434
	Per 1006 document except (see 5.4) ____	1435
	As follows:	
	*No evidence of physical damage.	1436
	Remain within specified tolerance.	1538

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC	
	NAME	CODE
5.56 (Cont)	As follows: (Cont)	
	The relays shall conform to the requirements of the following tests:	
	Insulation resistance.	2151
	Dielectric withstanding voltage at sea level.	2152
	Turn-on/turn-off time.	2155
	Turn-on/turn-off voltage.	2156
	Input current sensitivity.	2157
	Leakage current.	2158
	Transient voltage.	2159
	Waveform distortion.	2160
	Power dissipation.	2161

Supersedes page 5-128 of 10 May 1976.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Missile Command
ATTN: DRSMI-RCS
Redstone Arsenal, Alabama 35809

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.