MILITARY SPECIFICATION

CASES, SHIPPING, REUSABLE: 10559875, 11730881 AND 11730882

1. SCOPE

1.1 Scope.- This specification covers reusable plastic shipping cases for major assemblies of the Radar Set AN/VPS-2 (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-F-13926	Fire Control Materiel, General Specification Governing the Manufacture and Inspection of
MIL-I-45607	Inspection Equipment, Acquisition, Maintenance and Disposition of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-108	Definitions of and Basic Requirements for Enclosures for Electric and Electronic Equipment
MIL-STD-109	Quality Assurance Terms and Definitions
MIL-STD-129	Marking for Shipment and Storage

DRAWINGS

U.S. Army, Frankford Arsenal

F10559875	*Case,* Shipping, Reusable: 10559875
F11730881	Case, Shipping, Reusable: 11730881
F11730882	Case, Shipping, Reusable: 11730882

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from procuring activity or as indicated by contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS "

3.1 Materials .- The materials shall be in accordance with drawings, material specifications and general specifications forming a part Of this specification.

3.2 Fabrication.- Case assemblies shall be manufactured in accordance with the applicable drawings listed in Section 2.

3.2.1 Shell forming process.- The upper and lower case shells shall be thermo-formed by any proven method normally associated with the plastic industry. Finished formed parts shall be entirely free of blisters, blemishes, or thermo shock stress marks.

3.3 General specification.- The contractor shall be responsible for adherence to the following requirements Of MIL-F-13926:

a. . Dimensions and tolerances
b. Inorganic protective surface finishes
c. Part identification and marking
d. Workmanship

3.4 Environmental.

3.4.1 Storage.- The case assembly shall be capable of maintaining dimensional and structural integrity when subjected to temperature extremes of 150°F to -65°F. The case shall show no evidence of distortion, cracks, or delamination and shall remain watertight.

3.4.2 Standard ambient temperature.- Subsequent to the requirements of 3.4.1, the *case* shall meet all performance requirements of this specification at a standard ambient temperature between +60°F and +90°F.

3.4.3 impact resistance (ambient temperatures).- The latched Case assemblies fitted with a dummy load (see 4.5.2.2.1) shall sustain two drops, once on the top and once on the bottom, from a height Of 30 inches. Subsequent to the two drops, the case shall show no evidence of damage which will affect its intended function. The impacts" shall not unlatch the cover from the body, and the case shall then meet the requirements of 3.4.5 and 3.5.

3.4.4 Impact resistance (low temperature).- The latched case assembly, fitted with dummy load, specified in 3.4.3, shall sustain two drops, once on the top and once on the bottom, from a height of 24 inches after being subjected to low temperature conditioning at -40°F. Subsequent to the two drops, the case shall show no evidence of damage which will affect its intended function. The impact shall not unlatch the cover from the body, and there shall be no evidence of cracks or fractures. The case assembly shall then meet the requirements of 3.4.5 and 3.5, after the case has returned to ambient temperature.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

3.4.5 Watertightness.- The interior of the case shall show no evidence of leakage or moisture after the locked case is submerged in 3 feet of water in accordance with the watertight test specified in Table III of MIL-STD-108

3.4.6 Extreme operating temperatures.- The case shall meet the performance requirements of this specification while exposed to, and thermally stabilized at ambient temperatures of -65°F and 150°F.

3.5 Performance.

3.5.1 Fasteners and handles.- Fasteners and handles shall function without interference. The fasteners when engaged, shall secure the cover to the body and shall displace a uniform compression on gasketed seal.

3.5.2 Cover and body.- The cover and body shall mate freely, without restriction or interference.

3.5.3 Cushion inserts.- Cushion inserts shall be securely fastened to the cover and body. Cases with protective shrouds shall permit positioning of shroud within cushion inserts without restriction.

3.6 Workmanship.- Cases fabricated to the requirements of this specification, shall be in accordance with proven forming techniques and shall be free of defects that might affect strength, serviceability and protection of contents.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisions.- The component and subassembly inspection requirements of MIL-F-13926 form a part of the Quality Assurance Provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of two (2) case assemblies manufactured in the same manner using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials shall be obtained from the same source of supply as used in regular production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.2.2 contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection.

4.3 Inspection provisions.

4.3.1 Submission of product.- Unless otherwise specified by the contracting officer, inspection lot size, lot information and presentation of lots shall be in accordance with "Submission of Product" provisions of MIL-STD-105.

4.3.2 Examination and tests.- Components and subassemblies shall be inspected in accordance with the inspection provisions contained in MIL-F-13926. Examinations and tests related to Section 3 herein shall be performed on a single defect (individual characteristic) basis in accordance with MIL-STD-105, and the sampling plan specified in Table I. The tabulated classification of defects shall constitute the minimum inspection to be performed by the supplier prior to Government acceptance or rejection by lot.

TABLE I - CLASSIFICATION OF DEFECTS

CLASS CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
CRITICAL: NONE		
MAJOR: AQL 1.0% Defective		
.01. Fasteners and handles	3.5.1	4.6.2.1
,02. **Cover** and body	3.5.2	4.6.2.2
.03. Cushion inserts and protective shroud	3.5.3	4.6.2.3, 4.6.2.4
MINOR: NONE		

4.3.3 Acceptance and rejections.- Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.4 Special sampling.

4.4.1 General.- Two sample cases shall be selected at random as a special sampling each lot produced. The samples shall have successfully met all other acceptance tests specified herein, and shall then meet the following requirements and tests.

	TEST	REQUIREMENTS	TEST PROCEDURE
301.	Fabrication	3.2	F10559875, F11730881 or F11730882
302.	General specification	3.3	MIL-F-13926, Visual

4.4.2 Environmental and functional.- Two sample cases shall be selected at random as samples from each lot produced. The samples shall have successfully met all other acceptance tests specified herein, and shall then meet the following requirements and tests.

	TEST	REQUIREMENTS	TEST PROCEDURE
303.	Storage	3.4.1	4.6.1.1
304.	Impact resistance (ambient temperatures)	3*4.3	4.6.1.2
305.	Impact resistance (low temperature)	3.4.4	4.6.1.3
306.	Watertightness	3.4.5	4.6.1.4
307.	Extreme operating temperatures	3.4.6	4.6.1.5

4.4.3 Failure of sample.- Should any one item of a special sampling fail to meet the specified test requirements, acceptance of the product will be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted samples have been approved.

4.5 Inspection equipment.- Except as otherwise provided for by the contract, the contractor shall supply and maintain inspection equipment in accordance with the applicable requirements of MIL-I-45607.

4.5.1 Government furnished inspection equipment.- Where the contract provides for Government furnished test equipment, supply and maintenance of test equipment shall be in accordance with the applicable requirements specified in MIL-I-45607.

4.5.2 Contractor furnished inspection equipment.

4.5.2.1 Government design.- Unless otherwise specified in the contract, all inspection equipment specified by drawing number in specifications or SQAP forming a part of the contract shall be supplied by the contractor in accordance with technical data listed in the List of Inspection Documents (IEL), when provided with the Technical Data Package (TDP).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.5.2.2 Contractor design.- The contractor shall make available inspection equipment compatible with the "Test Methods and Procedures" specified in 4.6 of this specification and with the component inspection procedures specified in "Examination" and "Test Facilities" requirements of **MIL-F-13926. Since tolerance of test equipment is normally considered to be within 10% of the product tolerance for which it is intended, this** inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions and tolerances used in the design of test equipment shall be so selected and controlled as to insure that the test equipment **will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit, and permit positive rejection when** non-conforming. Construction shall be such as to facilitate routine calibration of test equipment.

4.5.2.2.1 Preparation for tests.- The case assembly shall be fitted with a dummy load as follows:

Case - 10559875: 18 3/4 x 10 x 10 .3/8 with a weight of 40 pounds.
Case - 11730881: 13 7/8 x 12 7/8 x 8 3/4 with a weight of 40 pounds.
Case - 11730882: 18 7/8 x 12 1/8 x 10 1/4 with a weight of 60 pounds.

The pressure relief valve shall be removed and the aperture sealed with a gasketed fitting when performing the watertightness test.

4.6 Test methods and procedures.

4.6.1 Environmental.

4.6.1.1 Storage.- The case assembly with dummy load shall be tested as follows:

a. Elevated temperature.- The case assembly shall be placed in test chamber and the temperature elevated gradually to 150°F and allowed to remain at this temperature until thermo-stabilization is reached within the case. The test sample shall remain at the thermo-stabilized temperature of 150°F for a period of 4 hours, after which the temperature shall be gradually reduced to ambient. There shall be no evidence of cracks, delamination or distortion as a result of the test. There shall be no leakage when the case is tested in accordance with 4.6.1.4.

b. Low temperature.- The case assembly shall be placed in test chamber and the temperature lowered gradually to -65°F and allowed to remain at this temperature until thermo-stabilization is reached within the case. The test sample shall remain at the thermo-stabilized temperature of -65°F for a period of 4 hours, after which the temperature shall be gradually raised to ambient. There shall be no evidence of cracks, delamination or 'distortion as a result of the test. There shall be no leakage when the case is tested in accordance with 4.6.1.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.6.1.2 Impact resistance (ambient temperature).- The sample case fitted with dummy load shall be subjected to a 30 inch free fall, flat drop, once on the top and once on the bottom onto a steel or concrete surface. Following the test, the ***case*** shall be subjected to a watertightness test specified in 4.6.1.4.

4.6.1.2.1 Results of test.- The case assembly shall be examined and there shall be no evidence of chipping, cracking, delamination or water penetration.

4.6.1.3 Impact resistance (low temperature).- The sample case shall be placed in a test chamber and the temperature lowered gradually to -40°F and allowed to remain at this temperature until thermo-stabilization is reached within the container. The test sample shall remain at the thermo-stabilized temperature of -40°F for a period of 4 hours. The sample shall be immediately subjected to impact test described in 4.6.1.2, except the drop height shall be 24 inches. The case shall be subjected to watertightness test specified in 4.6.1.4 after container has been stabilized at ambient temperatures.

4.6.1.3.1 Results of test.- The case assembly shall be examined and there shall be no evidence of chipping, cracking, delamination or water penetration.

4.6.1.4 Watertightness.- The watertightness test shall be performed in accordance with Table III of MIL-STD-108.

4.6.1.5 Extreme operating temperatures.- The operating temperature test consists of exposing the case to the temperatures indicated in 3.4.6 by means of equipment complying with the requirements of 4.5.2.2. The test shall be conducted in accordance with Procedure II of MIL-F-13926, and the temperature conditions of 3.4.6 shall apply. While exposed to these temperatures, the case shall meet the requirements specified in 3.5.1, 3.5.2 and 3.5.3.

4.6.2 Performance.

4.6.2.1 Fasteners and handles.- Operability of these devices shall be checked by a functional and visual examination. The fasteners shall be operated five times to determine compliance with the requirements specified in 3.5.1.

4.6.2.2 Cover and body.- The cover shall mate with body as specified in 3.5.2 when subjected to a functional examination by opening and closing the case at least five times and subsequently visually examining the components for defects or poor workmanship.

4.6.2.3 Cushion inserts.- A visual and tactile examination shall be performed to determine that the cushions are securely bonded in position. Visual examination shall reveal no evidence of damage or shifting of **cushions.**

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.6.2.4 Protective shrouds.- The shroud shall be positioned within cushion inserts of applicable case to assure fit without restriction.

5. PREPARATION FOR DELIVERY

5.1 Packaging and packing.- Unless otherwise specified, the cases shall be prepared for shipment using normal commercial methods, or materials to assure acceptance by common or other carrier for safe transportation at the lowest rate to point of destination.

5.2 Marking.- Marking for shipment shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.- The case assemblies defined herein are intended to accommodate the following items:

Case Assembly - Part No. 10559875 ,
Unit 2A1 - Microwave Chassis - 10549047

Case Assembly - Part No. 11730881
Unit 3 - Receiver Radar - 10548338
Unit 4 - Computer Range - 10548339
Unit 5 - Power Supply - 10548440

Case Assembly - Part No. 11730882
Unit 2 - Receiver Transmitter - 10548089

6.2 Ordering data.- Procurement documents should specify the following:

a. Title, number, and date of this specification
b. Case Assembly part number
c. Applicable stock number
d. Requirements for First Article tests

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1285-A219

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

YES NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
Department of the Army

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.