MILITARY SPECIFICATION SHEET

CIRCUIT CARD ASSEMBLY, 9290227

This Amendment forms a part of Military Specification Sheet MIL-C-63371/1B(AR) dated 31 July 1984, and is approved for use within the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Electrical Requirements; delete para 2 in its entirety and substitute:

"2. "All input and output levels shall be consistent with IC operating levels and power supply regulation, and shall not exceed plus or minus one percent (± 1.0%) of the indicated values, unless otherwise specified. Output voltages shall read as indicated in the table below:

Test Number	Voltage	Allowable Voltage Range
1-3	0	0 to 1.2 v
	14v	12.8v to 14.2v
pin 49	0	0 to 2v
4a	13.461v	13.25 to 13.60*
	1.85v	1.85v to 2.22v*
4b	13.462v	13.25 to 13.60*
		1.85v to 2.22v*
4c	13.457v	13.25 to 13.60*
	1.85	1.85v to 2.22*

*Add +/-5% variation for temperature tests."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

NOTE: the margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1095-A256-1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.