METRIC
MIL-PRF-55365/8J
5 September 2014
SUPERSEDING
MIL-PRF-55365/8H
26 January 2011

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, CHIP, FIXED, TANTALUM, POLARIZED ESTABLISHED RELIABILITY, NON-ESTABLISHED RELIABILITY AND HIGH RELIABILITY, STYLE CWR11 (METRIC)

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-55365.




FIGURE 1. Style CWR11 (molded) capacitors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

Dimensions						
Case code	H	H_2 (min)	L	P ±0.3 (.012)	W	W_2 ±0.1 (.004) (see note 4)
A	1.6 ±.2 (.063 ±.008)	0.7 (.028)	3.2 ±.2 (.126 ±.008)	0.8 (.031)	1.6 ±.2 (0.063 ±.008)	1.2 (.047)
B	1.9 ±.2 (.075 ±.008)	0.7 (.028)	3.5 ±.2 (.138 ±.008)	0.8 (.031)	2.8 ±.2 (.110 ±.008)	2.2 (.087)
C	2.5 ±.3 (.098 ±.012)	1.0 (.039)	6.0 ±.3 (.236 ±.012)	1.3 (.051)	3.2 ±.3 (.126 ±.012)	2.2 (.087)
D	2.8 ±.3 (.110 ±.012)	1.0 (.039)	7.3 ±.3 (.287 ±.012)	1.3 (.051)	4.3 ±.3 (.169 ±.012)	2.4 (.094)

NOTES:
1. Dimensions are in millimeters. Inch equivalents are given in parenthesis for general information only.
2. These capacitors are designed for mounting by dip or wave soldering, reflow soldering, thermo-compression bonding, or other conventional means.
3. The anode (+) terminal shall be indicated by a marking on the case or by bevel on anode end.
4. Applicable to solderable surfaces only. The configuration of the nonsolderable area is optional.
5. Solderable surfaces are only those surfaces designated as such. Termination edges are not considered solderable.
6. For solder coated terminations, add an additional 0.38 mm (.015 inch) to the tolerances for “L”, “H”, “P”, and “W_2” for each case size.

FIGURE 1. Style CWR11 (molded) capacitors - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Termination finish: In accordance with MIL-PRF-55365.

DC rated voltage: See table I. Above +85°C, voltage derating is required (see MIL-PRF-55365).

Operating temperature range: -55°C to +125°C.

Product level designator: In accordance with MIL-PRF-55365.

DC leakage (DCL): See table I.

Capacitance: See table I.

Capacitance tolerance: ±5 percent (J), ±10 percent (K), or ±20 percent (M).

Dissipation factor (DF): See table I.

Equivalent series resistance (ESR) at 100 kHz: In accordance with MIL-PRF-55365. See table I.

Resistance to soldering heat: In accordance with MIL-PRF-55365.

Stability at low and high temperatures: In accordance with MIL-PRF-55365.

Life:

2,000 hours: In accordance with MIL-PRF-55365.

10,000 hours: In accordance with MIL-PRF-55365.

Solderability: In accordance with MIL-PRF-55365, except that following steam aging; test samples may have a 30 minute bake out at +150°C prior to solder dipping.

Marking: In accordance with MIL-PRF-55365, to be marked on top of case as follows: Print orientation is optional.

Case code A

J	(+)	polarity stripe, J = JAN
105X	-	capacitance in picofarad code manufacturer's identifier

Case codes B, C, and D

J	(+)	polarity stripe, J = JAN
105	-	capacitance in picofarad code
35X	-	rated voltage; manufacturer's identifier

Alternate case code A marking

X	(+)	polarity stripe, X = manufacturer's identifier
105J	-	capacitance in picofarad code; J = JAN

At the option of the manufacturer, the lot date code may be marked on the top of the case for any case code.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

TABLE I. Style CWR11 characteristics.

Part or identifying number (PIN) 1/	DC rated voltage (+85°C)	Cap. (nom)	DC Leakage (max)			Dissipation factor (max)			Max ESR 100 kHz +25°C	Case size
			+25°C	+85°C	+125°C	+25°C	+85°C +125°C	-55°C		
	Volts	µF	µA	µA	µA	%	%	%	Ohms	
CWR11C-225 - - -	4	2.2	0.5	5.0	6.0	6	9	9	8.0	A
CWR11C-475 - - -	4	4.7	0.5	5.0	6.0	6	9	9	8.0	A
CWR11C-685 - - -	4	6.8	0.5	5.0	6.0	6	9	9	5.5	B
CWR11C-106 - - -	4	10.0	0.5	5.0	6.0	6	9	9	4.0	B
CWR11C-156 - - -	4	15.0	0.6	6.0	7.2	6	9	9	3.5	B
CWR11C-336 - - -	4	33.0	1.3	13.0	15.6	6	9	9	2.2	C
CWR11C-686 - - -	4	68.0	2.7	27.0	32.4	6	9	9	1.1	D
CWR11C-107 - - -	4	100.0	4.0	40.0	48.0	8	12	12	0.9	D
CWR11D-155 - - -	6	1.5	0.5	5.0	6	6	9	9	8.0	A
CWR11D-225 - - -	6	2.2	0.5	5.0	6	6	6	9	8.0	A
CWR11D-335 - - -	6	3.3	0.5	5.0	6	6	9	9	8.0	A
CWR11D-475 - - -	6	4.7	0.5	5.0	6	6	9	9	5.5	B
CWR11D-685 - - -	6	6.8	0.5	5.0	6	6	6	9	4.5	B
CWR11D-106 - - -	6	10.0	0.6	6.0	7.2	6	9	9	3.5	B
CWR11D-156 - - -	6	15.0	0.9	9.0	10.8	6	6	9	3.0	C
CWR11D-226 - - -	6	22.0	1.4	14.0	16.8	6	9	9	2.2	C
CWR11D-476 - - -	6	47.0	2.8	28.0	33.6	6	6	9	1.1	D
CWR11D-686 - - -	6	68.0	4.3	43.0	51.6	6	9	9	0.9	D
CWR11F-105 - - -	10	1.0	0.5	5.0	6.0	4	6	6	10.0	A
CWR11F-155 - - -	10	1.5	0.5	5.0	6.0	6	6	9	8.0	A
CWR11F-225 - - -	10	2.2	0.5	5.0	6.0	6	9	9	8.0	A
CWR11F-335 - - -	10	3.3	0.5	5.0	6.0	6	9	9	5.5	B
CWR11F-475 - - -	10	4.7	0.5	5.0	6.0	6	9	9	4.5	B
CWR11F-685 - - -	10	6.8	0.7	7.0	8.4	6	9	9	3.5	B
CWR11F-156 - - -	10	15.0	1.5	15.0	18.0	6	6	9	2.5	C
CWR11F-336 - - -	10	33.0	3.3	33.0	39.6	6	9	9	1.1	D
CWR11F-476 - - -	10	47.0	4.7	47.0	56.4	6	9	9	0.9	D
CWR11H-684 - - -	15	0.68	0.5	5.0	6.0	4	6	6	12.0	A
CWR11H-105 - - -	15	1.0	0.5	5.0	6.0	4	6	6	10.0	A
CWR11H-155 - - -	15	1.5	0.5	5.0	6.0	6	9	9	8.0	A
CWR11H-225 - - -	15	2.2	0.5	5.0	6.0	6	9	9	5.5	B
CWR11H-335 - - -	15	3.3	0.5	5.0	6.0	6	8	9	5.0	B
CWR11H-475 - - -	15	4.7	0.7	7.0	8.4	6	9	9	4.0	B
CWR11H-106 - - -	15	10.0	1.6	16.0	19.2	6	8	9	2.5	C
CWR11H-226 - - -	15	22.0	3.3	33.0	39.6	6	8	9	1.1	D
CWR11H-336 - - -	15	33.0	5.3	53.0	63.6	6	9	9	0.9	D
CWR11J-474 - - -	20	0.47	0.5	5.0	6.0	4	6	6	14.0	A
CWR11J-684 - - -	20	0.68	0.5	5.0	6.0	4	6	6	12.0	A
CWR11J-105 - - -	20	1.0	0.5	5.0	6.0	4	6	6	10.0	A
CWR11J-155 - - -	20	1.5	0.5	5.0	6.0	6	9	9	6.0	B
CWR11J-225 - - -	20	2.2	0.5	5.0	6.0	6	8	9	5.0	B
CWR11J-335 - - -	20	3.3	0.7	7.0	8.4	6	9	9	4.0	B
CWR11J-475 - - -	20	4.7	1.0	10.0	12.0	6	8	9	3.0	C
CWR11J-685 - - -	20	6.8	1.4	14.0	16.8	6	9	9	2.4	C
CWR11J-156 - - -	20	15.0	3.0	30.0	36.0	6	8	9	1.1	D
CWR11J-226 - - -	20	22.0	4.4	44.0	52.8	6	9	9	0.9	D

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

TABLE I. Style CWR11 characteristics - Continued.

Part or identifying number (PIN) 1/	DC rated voltage (+85°C)	Cap. (nom)	DC Leakage (max)			Dissipation factor (max)			Max ESR 100 kHz +25°C	Case size
			+25°C	+85°C	+125°C	+25°C	+85°C +125°C	-55°C		
	Volts	µF	µA	µA	µA	%	%	%	Ohms	
CWR11K-334 - - -	25	0.33	0.5	5.0	6.0	4	6	6	15.0	A
CWR11K-474 - - -	25	0.47	0.5	5.0	6.0	4	6	6	14.0	A
CWR11K-684 - - -	25	0.68	0.5	5.0	6.0	4	6	6	7.5	B
CWR11K-105 - - -	25	1.0	0.5	5.0	6.0	4	6	6	6.5	B
CWR11K-155 - - -	25	1.5	0.5	5.0	6.0	6	8	9	6.5	B
CWR11K-225 - - -	25	2.2	0.6	6.0	7.2	6	9	9	3.5	C
CWR11K-335 - - -	25	3.3	0.9	9.0	10.8	6	8	9	3.5	C
CWR11K-475 - - -	25	4.7	1.2	12.0	14.4	6	9	9	2.5	C
CWR11K-685 - - -	25	6.8	1.7	17.0	20.4	6	9	9	1.4	D
CWR11K-106 - - -	25	10.0	2.5	25.0	30.0	6	8	9	1.2	D
CWR11K-156 - - -	25	15.0	3.8	38.0	45.6	6	9	9	1.0	D
CWR11M-104 - - -	35	0.10	0.5	5.0	6.0	4	6	6	24.0	A
CWR11M-154 - - -	35	0.15	0.5	5.0	6.0	4	6	6	21.0	A
CWR11M-224 - - -	35	.22	0.5	5.0	6.0	4	6	6	18.0	A
CWR11M-334 - - -	35	.33	0.5	5.0	6.0	4	6	6	15.0	A
CWR11M-474 - - -	35	.47	0.5	5.0	6.0	4	6	6	10.0	B
CWR11M-684 - - -	35	.68	0.5	5.0	6.0	4	6	6	8.0	B
CWR11M-105 - - -	35	1.0	0.5	5.0	6.0	4	6	6	6.5	B
CWR11M-155 - - -	35	1.5	0.5	5.0	6.0	6	8	9	4.5	C
CWR11M-225 - - -	35	2.2	0.8	8.0	9.6	6	8	9	3.5	C
CWR11M-335 - - -	35	3.3	1.2	12.0	14.4	6	8	9	2.5	C
CWR11M-475 - - -	35	4.7	1.7	17.0	20.4	6	8	9	1.5	D
CWR11M-685 - - -	35	6.8	2.4	24.0	28.8	6	9	9	1.3	D
CWR11N-104 - - -	50	.10	0.5	5.0	12	6	8	8	22.0	A
CWR11N-154 - - -	50	.15	0.5	5.0	6.0	4	6	6	17.0	B
CWR11N-224 - - -	50	.22	0.5	5.0	6.0	4	6	6	14.0	B
CWR11N-334 - - -	50	.33	0.5	5.0	6.0	4	6	6	12.0	B
CWR11N-474 - - -	50	.47	0.5	5.0	6.0	4	6	6	8.0	C
CWR11N-684 - - -	50	.68	0.5	5.0	6.0	4	6	6	7.0	C
CWR11N-105 - - -	50	1.0	0.5	5.0	6.0	4	6	6	6.0	C
CWR11N-155 - - -	50	1.5	0.8	8.0	9.6	6	8	9	4.0	D
CWR11N-225 - - -	50	2.2	1.1	11.0	13.2	6	8	9	2.5	D
CWR11N-335 - - -	50	3.3	1.7	17.0	20.4	6	9	9	2.0	D
CWR11N-475 - - -	50	4.7	2.4	24.0	28.8	6	9	9	1.5	D

1/ Complete PIN shall include additional symbols to indicate termination finish, capacitance tolerance, product level, and, if applicable, surge current option letter. If optional surge current is not required, the last "-" shall be deleted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Army - AR, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99
NASA – NA

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5910-2014-022)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.