INCH-POUND

MIL-P-60679A(AR)
AMENDMENT 5
9 February 1990
SUPERSEDING
AMENDMENT 4
1 July 1983

MILITARY SPECIFICATION

PROJECTILE, 20MM, HEIT-SD, M246; METAL PARTS

This Amendment forms a part of Military Specification MIL-P-60679A(MU), dated 10 December 1969, and is approved for use by the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, Under STANDARDS: Delete "FEDERAL - Federal Test Method Standard No. 151 - Metals; Test Methods".

2.1, Under DRAWINGS, MUNITIONS COMMAND: Add "11075245 - Standard for Eddy Current Flaw Detector".

2.2, Add the following:

"2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM)
ASTM B 117-64 - Method of Test for Salt Spray (Fog) Testing

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Technical Society and Technical Association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using federal agencies.".

4.3.1.a, Add the following:

"(5) 3 Test panels (see TT-C-490)".

AMSC N/A

FSC 1305

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:55Z
Check the source to verify that this is the current version before use.

PAGE 7

4.4.3.3 Make the following changes:

Major 115: Delete in its entirety and substitute the following:

"115. Void at junction of rotating band and body, Visual".

Major 117: Delete in its entirety.

Major 118: Delete the word "datum" and substitute the word "basic".

Major 125: Delete the word "Thickness" and substitute the word "Width".

Add the following defect:

Major 130:

"130. Concentricity, boss (tracer cavity) with datum surface, Gage".

Major 131: Delete in its entirety and substitute the following:

"131. Length, boss (tracer cavity) to basic diameter (igniter cavity), Gage".

Major 132: Delete in its entirety.

PAGE 8

4.4.3.5: Make the following changes:

Add the following defect:

Major 110:

"110. Perforation or fracture of metal between cavities, Visual".

* Add the following defect:

Major 111:

"111. Paint on threads, Visual".

* Minor 204: Delete in its entirety

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:55Z
Check the source to verify that this is the current version before use.

PAGE 9

4.4.4, Table I: Add the following test:

"Test	Sample Size	Item	Req Para
Paint in Igniter Cavity	8/ 800	Assemblies, painted	3.6.2".

PAGE 10

4.4.4 Table I: Add the following note:

"8/ All of the assemblies selected shall be visually inspected for paint in the igniter cavity. Any assembly that has paint in the igniter cavity shall be segregated. Five (5) of the worst case samples from each group of 100 segregated assemblies or fraction thereof or a minimum of 5 samples when the segregated assembly entire quantity is less than 100, shall be selected and tested as specified in 4.5.9. If one or more assemblies fail to comply with the requirement, the lot shall be rejected.".

PAGE 12

4.5.7: Delete in its entirety and substitute the following:

"4.5.7 Corrosion resistance. The method of test shall be as prescribed in American Society for Testing and Materials (ASTM) ASTM B117. The paint shall not be disturbed; however, the rotating band and unpainted surfaces of the sample projectiles may be masked out by a wax coating or other suitable material. The salt spray solution and exposure time shall be as specified in 3.6.3.".

4.5.9: Add the following paragraph:

"4.5.9 Paint in igniter cavity. The sample shall be cut in half to expose the layer of paint in the igniter cavity and inspected to determine acceptability. Any paint found in igniter cavity shall be one smooth and continuous layer that follows the outline of the cavity with no puddling or other type of paint build up.".

PAGE 13

* 6.6 Delete in its entirety and substitute the following:

"6.6 Defect standard for eddy current testing. The contractor shall be responsible for the procurement, manufacture, and maintenance of eddy current equipment and the front, rear slot, phase set, and three slot standards IAW the latest drawings called out in the applicable technical data package and the contract. The production check E.C. standards (PCS No. 1) Dwg. 11075245 shall be furnished by the contractor to the Government agency having contract adminstration responsibility.".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:55Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1305-AD19)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:55Z
Check the source to verify that this is the current version before use.