SS-A-701B
July 15, 1974
SUPERSEDING
Int.Fed.Spec. SS-A-00701a
January 6, 1967

FEDERAL SPECIFICATION

ASPHALT, PETROLEUM (PRIMER, ROOFING, AND WATERPROOFING)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for use of all Federal agencies.

1. SCOPE

1.1 This specification covers a cut-back asphalt used as a masonry primer.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for approval form a part of this specification to the extent specified herein.

Federal Specifications

PPP-D-729 - Drums: Metal, 55-Gallon (For Shipment of Noncorrosive Material)
PPP-P-704 - Pails, Metal (Shipping, Steel, 1 through 12 Gallon)

Federal Standard

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies)

FSC 5610

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks, as outlined under General Information in the Index of Federal Specifications and Standards, at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Service Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks, and the Index of Federal Specifications and Standards, from established distribution points in their agencies.)

Military Standards

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-129 - Marking for Shipment and Storage

(Copies of Military Specifications and Standards, required by suppliers in connection with specific procurement functions, should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM)

D41 - Primer for use with Asphalt in Dampproofing and Waterproofing

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

National Motor Freight Traffic Association, Inc. Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 S. Riverside Plaza, Chicago, IL 60606.)

Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.

3. REQUIREMENTS

3.1 Standard product. The primer shall, as a minimum, be in accordance with the requirements of this specification, and shall be the manufacturer's standard product. Additional features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard product shall be included in the primer being furnished.

3.2 First article. When specified (see 6.2), the contractor shall furnish one five-gallon pail of asphalt primer for first article inspection and approval (see 4.2.1 and 6.3).

3.3 Material. The asphalt primer shall consist of an asphaltic base thinned to a suitable brushing consistency, with a volatile solvent, and shall conform to the requirements as set forth in ASTM D41.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

For joining (welding) joints, burrs and splices shall be requirements prior

4.1.1 Inspection of materials and components. In accordance with 4.1, the supplier is responsible for insuring that materials and components used were manufactured, examined, and tested to the extent specified, in accordance with the requirements of referenced subsidiary specifications and standards. The terms and definitions of MIL-STD-109 shall apply.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. First article inspection shall be performed on one five-gallon pail of asphalt primer, when a first article sample is required (see 3.2). This inspection shall include the examination of 4.5 and the tests of 4.6. Failure of the first article to pass the examination or any of the tests shall be cause for rejection. The first article may be a standard production item from the supplier's current inventory, provided the unit meets the requirements of the specification, and is representative of the design, construction, and manufacturing technique applicable to the remaining units to be furnished under the contract.

4.2.2 Quality conformance inspection. Quality conformance inspection shall be performed on the samples selected in accordance with 4.4. This inspection shall include the examination of 4.5 and the tests of 4.6.

4.3 Inspection lot. All asphalt primer offered to the Government at one time shall be considered a lot for purposes of inspection. The sample unit shall be one filled package.

4.4 Sampling.

4.4.1 Sampling for examination. A random sample of filled packages shall be selected from each lot offered to the Government in accordance with MIL-STD-105 at inspection level II. The acceptable quality level (AQL) shall be 4.0 percent.

4.4.2 Sampling for tests. Sampling for tests shall be done in accordance with ASTM D41.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

4.5 Examination. Each unit selected in accordance with 4.4.1 shall be examined to verify compliance with the requirements of this specification. This element of inspection shall encompass all visual examinations.

4.6 Tests. Each sample selected in accordance with 4.4.2 shall be tested in accordance with ASTM D41, and any unit failing to pass the tests, shall be rejected. A certificate of compliance from an independent laboratory, approved by the contracting officer, will be accepted as evidence that the primer has passed the required tests.

4.7 Inspection of preparation for delivery. An inspection shall be made to determine that the packaging and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with Table I. The sample unit shall be one shipping container fully prepared for delivery. Sampling shall be in accordance with MIL-STD-105. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

Table I. Classification of preparation for delivery defects

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components, such as incomplete closure of container. Distortion of container.

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B or C, as specified (see 6.2).

5.1.1 Level A. The asphalt primer shall be packed in five-gallon pails conforming to PPP-P-704, type II, Class 1, 2, or 3, or in 55-gallon drums conforming to PPP-D-729, type II as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:13Z
Check the source to verify that this is the currentversion before use.

5.1.2 Level B. The asphalt primer shall be packed in five-gallon pails with lug covers and a wire bail securely attached to each pail. The wire bail shall be fabricated from No. 9 Steel Wire Gage with a nominal thickness of 0.148 inch, and shall be zinc-coated or protected with a corrosion-resistant material. Each cover shall have a flowed-in or other suitable gasket, uniformly distributed around the circumference of the inner edges of the cover. All exterior surfaces of the pail shall be coated with a commercial coating.

5.1.3 Level C. The asphalt primer shall be packed in a manner which will insure arrival at the destination in satisfactory condition and be acceptable to the carrier at lowest rates. Containers and packing shall comply with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.2 Marking. (see 6.2)

5.2.1 Civil agencies. In addition to any special marking required by the contract or order, the interior package and exterior shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.2.2 Military activities. In addition to any special marking required by the contract or order, the interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Primer is intended for use as a priming coat for concrete (below or above ground level), brick, and other masonry surfaces, over which asphalt built-up roofing, waterproofing, or dampproofing is to be applied.

6.2 Ordering data. Purchasers should select the preferred options offered herein and include the following data in procurement documents:

6.2.1 Procurement requirements.

(a) Title, number, and date of this specification.
(b) When first article is required for inspection and approval (see 3.2).
(c) Level of packing required (see 5.1).
(d) Packing quantities (see 5.1.1).
(e) Marking required (see 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

6.2.2 Contract data requirements. When this specification is used in a procurement which incorporates a DD Form 1423 and invokes the provisions of paragraph 7-104.9(n) of the Armed Services Procurement Regulation, the data requirements identified below will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the Contract Data Requirements List (DD Form 1423) incorporated into the contract. When the provisions of ASPR 7-104.9(n) are not invoked, the data specified below shall be delivered in accordance with the contract requirements. Deliverable data required by this specification is cited in the following paragraph.

Paragraph	Data Requirement	Applicable DD 1664
4.6	Certificate of Compliance	DI-E-2121

(Copies of Data Item Descriptions required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

6.3 First article. When a first article is required it shall be tested and approved under the appropriate provisions or paragraph 7-104.55 of the Armed Services Procurement Regulation. The first article may be a standard production item from the supplier's current inventory. The first article should consist of one five-gallon pail. The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for examinations, test, and approval of the first article.

6.4 Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

MILITARY CUSTODIANS:
Army - ME
Navy - YD
Air Force - 84

User activity:
Army - CE

Preparing activity:
Navy - YD

Civil Agency Coordinating Activities:
GSA - FSS
FAA
AFS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 25 cents each.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:13Z
Check the source to verify that this is the currenversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS. The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers, vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:13Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commanding Officer
Naval Construction Battalion Center
Code 156
Port Hueneme, CA 93043

OLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.