MILITARY SPECIFICATION

RELAYS, SOLID STATE, GENERAL SPECIFICATION FOR

This supplement forms a part of Military Specification MIL-R-28750C, dated 16 February 1993

SPECIFICATION SHEETS

MIL-R-28750/5	-	Relay, Solid State, Hermetically Sealed, Class II, Isolated, ±50 mA, ± 40 V, AC or DC, Analog Signal Switching, SPST (N.O)
MIL-R-28750/6	-	Relay, Solid State, Hermetically Sealed, Class II, Isolated, 250 mA, 40 V dc, Signal Switching, SPST (N O.).
MIL-R-28750/7	-	Relay, Solid State, Hermetically Sealed, Class II, Isolated, 100 mA, 250 V dc, Signal Switching, SPST (N.O.).
MIL-R-28750/8	-	Relay, Solid State, Hermetically Sealed, Class II, Optically Isolated, 600 mA, 50 V dc, Signal Switching, SPST (N.O.).
MIL-R-28750/9	-	Relay, Solid State, Hermetically Sealed, Class II, Optically Isolated, Zero Voltage Turn on, 1 Ampere (2 Amperes with Heat Sink), 40-440 Hz, Power Switching, SPST (N.O.).
MIL-R-28750/10	-	Relay, Solid State, Sealed, Class I, Optically Isolated, Zero Voltage Turn On, 25 Amperes, 250 Volts Maximum, 45-440 Hz, Power Switching, SPST (N O).

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0849)

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:24Z
Check the source to verify that this is the current version before use.