INCH-POUND
MIL-PRF-28750D
SUPPLEMENT 1
1 February 1999

PERFORMANCE SPECIFICATION

RELAYS, SOLID-STATE, GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-28750D,
dated 1 February 1999.

SPECIFICATION SHEETS

MIL-R-28750/5	-	Relay, Solid-State, Hermetically Sealed, Class II, Isolated, ±50 mA, ±40 V, AC or DC, Analog Signal Switching, SPST (N.O.).
MIL-R-28750/6	-	Relay, Solid-State, Hermetically Sealed, Class II, Isolated, 250 mA, 40 V DC, Signal Switching, SPST (N.O.).
MIL-R-28750/7	-	Relay, Solid-State, Hermetically Sealed, Class II, Isolated, 100 mA, 250 V DC, Signal Switching, SPST (N.O.).
MIL-PRF-28750/8	-	Relay, Solid-State, Hermetically Sealed, Class II, Optically Isolated, 600 mA, 50 V DC, Signal Switching, SPST (N.O.).
MIL-PRF-28750/9	-	Relay, Solid-State, Hermetically Sealed, Class II, Optically Isolated, Zero Voltage Turn-on, 1 Ampere (2 Amperes with Heat Sink), 400 Hz, Power Switching, SPST (N.O.).
MIL-PRF-28750/10	-	Relay, Solid-State, Sealed, Class I, Optically Isolated, Zero Voltage Turn-on, 25 Amperes, 250 V maximum, 400 Hz, Power Switching, SPST (N.O.).

Custodians:
Navy - EC
Air Force - 85

Preparing activity:
DLA - CC

(Project 5945-0980-99)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:24Z
Check the source to verify that this is the current version before use.