

MILITARY SPECIFICATION SHEET

RELAY, SOLID STATE, HERMETICALLY SEALED, ISOLATED, 250 MA, 40 V DC, SIGNAL SWITCHING, SPST (N.O.)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the relay described herein shall consist of this specification and the latest issue of MIL-R-28750.





CIRCUIT
(BOTTOM VIEW)

INCHES	MM
.017	.43
.031	.79
.032	.81
.100	2.54
.200	5.08
.275	6.99
.335	8.51
.370	9.40
.500	12.70

NOTES

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.010 (.25 mm).
4. Terminal numbers shown above are for reference only.

FIGURE 1. Outline drawing and dimensions.

Ⓓ denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:25Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

INPUT DATA·

Input voltage range 4.0 to 7 V dc. 1/

Rated turn-on voltage· 5.0 V dc. 1/

Rated turn-off voltage 1.0 V dc maximum. 1/

Input current· 22 mA dc maximum at rated voltage.

Turn-on time 10 microseconds maximum at rated voltage.

Turn-off time 15 microseconds maximum from rated voltage.

Bias voltage Not applicable.

OUTPUT DATA

Rated output current See figure 2.

Rated output voltage. 40 V dc.

Output voltage drop .5 V dc maximum at rated voltage.

Output leakage current 100 microamperes maximum at rated voltage.

Crosstalk· Not applicable.

Transient voltage Not applicable.

Electric system spike· Not applicable.

Overload 1.5 x rating for 5 ms, 1 percent duty cycle.

DC offset voltage· Not applicable.

Waveform distortion. Not applicable.

ELECTRICAL DATA·

Dielectric withstanding voltage 1,000 V ac (P-P), 60 Hz.

Insulation resistance 100 megohms.

(D) Isolation 10 picofarads tested at 1 kHz.

Power dissipation 260 milliwatts maximum at rated voltage.

ENVIRONMENTAL DATA·

Temperature (operating and storage)· -55°C to +125°C.

(D) Shock (specified pulse) MIL-STD-202, method 213, test condition F (1500 G's).

(D) Vibration· MIL-STD-202, method 204, test condition H, except peak value shall be 100 G's (10 to 2,000 Hz).

Electromagnetic interference Not applicable.

Resistance to soldering heat Applicable.

Salt spray (corrosion) In accordance with MIL-STD-750, method 1041

Moisture resistance Not applicable.

1/ Input must be a step function. Rise or fall time, as applicable, not to exceed 100 microseconds

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:25Z
Check the source to verify that this is the current version before use.




FIGURE 2. Output current vs. input control voltage and ambient temperature.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:25Z
Check the source to verify that this is the current version before use.

PHYSICAL DATA

Terminal strength (MIL-STD-202, method 211)

Pull test. Test condition A, 1 pound pull.

Bend test Test condition C, 1/2 pound load.

Twist test. Test condition D.

Terminal solderability Applicable

Dimensions and configuration See figure 1

Weight 5 grams (.18 ounce) typical.

Seal Hermetic.

LIFE TEST REQUIREMENTS

Life test Applicable.

Minimum marking Military part number, functional diagram and terminal identification, date code, and manufacturer's name or source code.

(D) Part number M28750/6-001W, Y, or X to indicate the applicable screening level as specified in MIL-R-28750.

QUALIFICATION INSPECTION (reduced testing):

If the relays produced for MIL-R-28750/6 are similar in internal design, construction and material, except for the output, to the relays produced for MIL-R-28750/7, then reduced testing for qualification of MIL-R-28750/6 may be performed concurrent with or subsequent to successful qualification of MIL-R-28750/7. For reduced testing see table I.

TABLE I Qualification inspection (reduced testing).

Inspection	Sample size
Electrical characteristics Life	6 units

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Army - MI
Navy - OS
Air Force - 11, 17, 99
DLA - ES

User activities
Army - AR, AT, MF
Navy - AS, MC, SH
Air Force - 19

Agent
DLA - ES

Preparing activity.
Navy - EC

(Project 5945-0682-2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:25Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Naval Electronic Systems Command
Washington, DC 20363

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20363
ATTN: ELEX 8111

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:25Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1 DOCUMENT NUMBER	2 DOCUMENT TITLE
MIL-R-28750/60	RELAY, SOLID STATE, HS, ISOLATED

3a NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)* _____

5 PROBLEM AREAS

a Paragraph Number and Wording

b Recommended Wording

c Reason/Rationale for Recommendation

6 REMARKS

7a NAME OF SUBMITTER *(Last First MI)* – Optional	b WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c MAILING ADDRESS *(Street City State ZIP Code)* – Optional	8 DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:25Z
Check the source to verify that this is the current version before use.