INCH-POUND

MIL-PRF-28750/6H
01 December 2023
SUPERSEDING
MIL-R-28750/6G
10 December 2014


PERFORMANCE SPECIFICATION SHEET

RELAY, SOLID STATE, HERMETICALLY SEALED, ISOLATED, 250 mA, 40 V DC, SIGNAL SWITCHING, SPST (N. O.)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

MIL-PRF-28750/6 is inactive for new design and is no longer used, except for replacement purposes.

The requirements for acquiring the products described herein shall consist of this specification sheet and MIL-PRF-28750.



Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.370	---	9.40
B	---	.335	---	8.51
C	----	.020	---	0.51
D	---	.280	---	7.11
E	.500	---	12.70	---
F	.007	.027	0.18	0.68
G	.021	.041	0.53	1.04
H	.022	.042	0.56	1.07
J	.090	.110	2.29	2.79
K	.190	.210	4.83	5.33

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ± .010 in (0.25 mm).
4. Terminal numbers shown above are for reference only.

FIGURE 1. Outline drawing and dimensions.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:25Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

INPUT DATA:

Input voltage range: 4.0 to 7 V dc. 1/

Rated turn-on voltage: 5.0 V dc. 1/

Rated turn-off voltage: 1.0 V dc maximum. 1/

Input current: 22 mA dc maximum at rated voltage.

Turn-on time: 10 microseconds maximum at rated voltage.

Turn-off time: 15 microseconds maximum from rated voltage.

Bias voltage: Not applicable.

OUTPUT DATA:

Rated output current: See figure 2.

Rated output voltage: 40 V dc.

Output voltage drop: .5 V dc maximum at rated voltage.

Output leakage current: 100 microamperes maximum at rated voltage.

Crosstalk: Not applicable.

Transient voltage: Not applicable.

Electric system spike: Not applicable.

Overload: 1.5 x rating for 5 ms, 1 percent duty cycle.

DC offset voltage: Not applicable.

Waveform distortion: Not applicable.

ELECTRICAL DATA:

Dielectric withstanding voltage: 1,000 V ac (P-P), 60 Hz.

Insulation resistance: 100 megohms.

Isolation: 10 picofarads tested at 1 kHz.

1/ Input must be a step function. Rise or fall time, as applicable, not to exceed 100 microseconds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:25Z
Check the source to verify that this is the current version before use.

Power dissipation: 260 milliwatts maximum at rated voltage.

Reverse polarity (dc operated relays): Not applicable.

ENVIRONMENTAL DATA:

Temperature (operating and storage): -55°C to +125°C.

Shock (specified pulse): MIL-STD-202-213, test condition F (1,500 G's).

Vibration: MIL-STD-202-204, test condition H, except peak value shall be 100 G's (10 to 2,000 Hz).

Electromagnetic interference: Not applicable.

Resistance to soldering heat: Applicable.

Salt spray (corrosion): In accordance with MIL-STD-750, method 1041.

Moisture resistance: Not applicable.

PHYSICAL DATA:

Terminal strength (MIL-STD-202- 211):

Pull test: Test condition A, 1 pound pull.

Bend test: Test condition C, 1/2 pound load.

Twist test: Test condition D.

Terminal solderability: Applicable.

Dimensions and configuration: See figure 1.

Weight: 5 grams (.18 ounce) typical.

Seal: Hermetic.

Terminal finish: Gold plated.

LIFE TEST REQUIREMENTS:

Life test: Group B and group C testing shall not be performed.

Minimum marking: Military PIN, functional diagram and terminal identification, date code, and manufacturer's name or source code.

Part or Identifying Number (PIN): M28750/6-001Y, M28750/6-001W and M28750/6-001X have been superseded by M28750/6-001Y.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:25Z
Check the source to verify that this is the current version before use.




FIGURE 2. Output current versus input control voltage and ambient temperature.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:25Z
Check the source to verify that this is the current version before use.

QUALIFICATION INSPECTION (reduced testing):

If the relays produced for MIL-PRF-28750/6 are similar in internal design, construction and material, except for the output, to the relays produced for MIL-R-28750/7, then reduced testing for qualification of MIL-PRF-28750/6 may be performed concurrent with or subsequent to successful qualification of MIL-R-28750/7. For reduced testing, see table I.

TABLE I. Qualification inspection (reduced testing).

Inspection	Sample size
Electrical characteristics Life	6 units

Referenced documents. In addition to MIL-PRF-28750, this document references the following:

MIL-R-28750/7 MIL-STD-202-213 MIL-STD-202-204 MIL-STD-202-211 MIL-STD-750

6.9 Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-2024-001)

Review activities:
Army - AR, AT, CR4, MI
Navy - AS, MC, OS, SH
Air Force - 19
NASA – NA

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:25Z
Check the source to verify that this is the current version before use.