The requirement to comply with changes implemented in this Revision must be completed by 6 months from the date of this document.

INCH-POUND
MIL-PRF-28750/9K
29 September 2026
SUPERSEDING
MIL-PRF-28750/9J
16 March 2021

PERFORMANCE SPECIFICATION SHEET

RELAY, SOLID-STATE, HERMETICALLY SEALED, CLASS II, OPTICALLY ISOLATED, ZERO VOLTAGE TURN-ON, 1 AMPERE (2 AMPERES WITH HEAT SINK), 400 HZ, POWER SWITCHING, SPST (N.O.)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the relay described herein shall consist of this specification sheet and MIL-PRF-28750.




FIGURE 1. Outline drawing and dimensions.

AMSC N/A

FSC 5945

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:26Z
Check the source to verify that this is the current version before use.

Ltr.	Inches		mm	
	Min	Max	Min	Max
A	---	.890	---	22.61
B	---	.530	---	13.46
C	.770	.840	19.56	21.34
D	---	.190	---	4.83
E	.250	.290	6.35	7.37
F	.125	.145	3.18	3.68
G	.490	.510	12.45	12.95
H	.095	.115	2.41	2.92
J	.290	.310	7.37	7.87
K	.590	.610	14.99	15.49
L	---	.020	---	0.51
M	.016	.020	0.41	0.51

NOTES:
1. Dimensions are in inches.
2. Metric equivalents given for general information only.
3. Unless otherwise specified, tolerance is ±.010 (0.25 mm).
4. Terminal numbers shown above are for reference only.

FIGURE 1. Outline drawing and dimensions - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:26Z
Check the source to verify that this is the current version before use.




FIGURE 2. Maximum load current versus case temperature.




FIGURE 3. Maximum load current versus ambient temperature.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:26Z
Check the source to verify that this is the current version before use.




FIGURE 4. Peak surge current versus surge current duration.




FIGURE 5. Conducted emissions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:26Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

INPUT REQUIREMENTS:

Input voltage range: 3.8 V dc to 32 V dc.

Assured turn-on voltage: ≤3.8 V dc.

Assured turn-off voltage: ≥1.5 V dc.

Input current: 18 mA dc maximum.

Turn-on time: ½ cycle ac Hz.

Turn-off time: 1 cycle ac Hz.

Bias voltage: Not applicable.

OUTPUT REQUIREMENTS:

Rated output current: See figure 2 and figure 3.

Rated output voltage: 250 V ac rms maximum, 400 Hz.

Output voltage drop: 1.5 V ac maximum.

Output leakage current: 3 mA rms maximum.

Crosstalk: Not applicable.

Transient voltage: Step line voltage from 230 V ac, 400 Hz to 360 V ac, 400 Hz. For 5 seconds maximum. (Relay can be externally protected to meet the requirements of MIL-STD-704, category B).

Electrical system spike: Not applicable.

Overload: 1.5 times the rated current (no heat sink), 10 percent duty cycle (see figure 4).

DC offset voltage: ±100 millivolts maximum.

Waveform distortion: 4 V rms maximum, initial turn-on: ±10 V peak maximum.

Minimum current: Applicable (load current shall be varied between 10 percent and 100 percent of rated load).

ELECTRICAL REQUIREMENTS:

Dielectric withstanding voltage: 1,500 V ac rms, 60 Hz.

Insulation resistance: 100 megohms minimum.

Isolation: 10 picofarads maximum.

Power dissipation: 2.00 watts maximum (no heat sink).

Exponential rate of voltage rise (dv/dt): 100 V/µs.

ENVIRONMENTAL REQUIREMENTS:

Temperature:

Operating: -55°C to +110°C.

Storage: -55°C to +125°C.

Thermal shock: Applicable.

Shock (specified pulse): MIL-STD-202-213, test condition F (1,500 g's).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:26Z
Check the source to verify that this is the current version before use.

Vibration: 20 g's, 10 Hz to 2,000 Hz.

Moisture resistance: Not applicable.

Electromagnetic interference: Maximum broadband conducted emission on power lines with 115 V ac, 400 Hz, 1.0 ampere resistive load during steady state and switching conditions (see figure 5).

Resistance to soldering heat: Applicable.

Salt atmosphere (corrosion): In accordance with MIL-STD-750, method 1041.

PHYSICAL REQUIREMENTS:

Weight: 6 grams maximum.

Dimensions and configuration: See figure 1.

Terminal strength: 1 pound pull minimum.

Terminal solderability: Applicable.

Terminal finish: Corrosion resistant material. Corrosion resistant material such as gold plating are considered acceptable.

Seal: Hermetic (solder or weld).

Minimum marking: Part number, functional diagram and terminal identification, date code, and manufacturer's name or source code.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

APPLICABLE PUBLICATIONS:

Referenced documents: In addition to MIL-PRF-28750, this document references the following:

MIL-STD-202-213 MIL-STD-704 MIL-STD-750

CONCLUDING MATERIAL:

Custodians:
Navy - EC
Air Force - 85
DLA – CC

Preparing activity:
DLA - CC

(Project 5945-2026-037)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:26Z
Check the source to verify that this is the current version before use.