INCH-POUND

MIL-R-28750/7C
AMENDMENT 2
16 February 1993

MILITARY SPECIFICATION SHEET

RELAY, SOLID STATE, HERMETICALLY SEALED, CLASS II, ISOLATED
100 MA, 250 V DC, SIGNAL SWITCHING, SPST (N O)

This amendment forms a part of MIL-R-28750/7C, dated 12 April 1985, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 1

* FIGURE 1, add dimension of "0 020 MAX", in the location from the bottom surface of the can, extending down the leads to show the maximum allowable distance the material around the lead, may extend down the lead

PAGE 2

ELECTRICAL DATA, add the following

"Reverse polarity (dc operated relays) Not applicable "

PAGE 4

* PHYSICAL DATA, add the following

"Terminal finish Gold plated "

* Part number, delete and substitute the following

"Part or Identifying number (PIN) M28750/7-001Y M28750/7-001W and M28750/7-001X have been superseded by M28750/7-001Y "

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Army - MI
Navy - OS
Air Force - 17, 99
NASA - NA
DLA - ES

User activities
Army - AR, AT, ME
Navy - AS, MC, SH
Air Force - 19

Preparing activity
Navy - EC

Agent
DLA - ES

(Project 5945-0875-03)

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:26Z
Check the source to verify that this is the current version before use.