MIL-B-60107B(MU)
12 February 1974
SUPERSEDING
MIL-B-60107A(MU)
10 June 1965

MILITARY SPECIFICATION
BANDOLEER, M4

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope.-This specification covers one type of bandoleer intended to contain 7.62mm ammunition in links, in a carton.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on the date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal

PPP-B-1055	- Barrier, Material, Waterproofed, Flexible
PPP-B-636	- Boxes, Fiberboard

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-129	- Marking for Shipment and Storage

DRAWINGS

Armament Command

D10533984	- Assembly, Bandoleer, M4, Ctgs, 7.62MM
F10534012	- Packing and Marking, Bandoleer, M4

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:10Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications, required by suppliers in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.-The bandoleer shall comply with the requirements specified on Drawing F10533984, referenced specifications and the following:

3.2 First article sample.-Requirements for submission of first article sample by the contractor shall be as specified in the contract.

3.3 Strength of material.-The bandoleer loaded with a weight of 6 pounds, 8 ounces, shall not show any ripping of stitches or material when subjected to a 12 inch free drop with center of strap supporting bandoleer upon completion of drop.

3.4 Workmanship.-The bandoleer shall be free of rips, tears, irregular sewing and other defects.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the procurement of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality Assurance terms and definitions.-Reference shall be made to MIL-STD-109 for definition of quality assurance terms.

4.2 First article sample.

4.2.1 First article sample.-At the beginning of regular production, a sample shall be submitted in accordance with contract requirements. The sample shall be manufactured using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials shall be the same as used for regular production and shall be obtained from the same source of supply. The sample shall consist of:

a. 50 ea. - Bandoleers for dimensional and visual examination and drop test (see 6.2)

b. 25 ea. - Straps for dimensional and visual examination

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:10Z
Check the source to verify that this is the current version before use.

4.2.1.1 Examination and test.-After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

4.2.1.2 Initial production sample failure.-Failure of the sample to comply with the requirements of the drawings and specifications shall result in sample disapproval. Determination as to acceptability of any initial production sample shall be based upon results of initial tests only and no second tests shall be permitted on that initial production sample.

4.3 Inspection provisions.

4.3.1 Lot.

4.3.1.1 Submission of product.-The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Size of lot.-The bandoleers lot size shall be as agreed upon between the contractor and the contracting officer, provided the formation of the lot is in accordance with MIL-STD-105.

4.3.2 Examination.-Examination for major and minor defects shall be performed as specified herein. Each bandoleer found to be defective shall be rejected.

4.3.2.1 Sample and acceptance criteria.-Sampling plans and procedures shall be in accordance with MIL-STD-105. Defect characteristics for major and minor defects shall be performed on a class basis in accordance with the classification of defects, using applicable sampling plans and acceptance criteria of MIL-STD-105. The Acceptable Quality Level (AQL) for the major class shall be 1.5 percent with no individual defect characteristic associated with the class basis for major defects exceeding an AQL of 0.65 percent. The AQL for minor class shall be 4.0 percent.

4.3.3 Classification of defects.-The classification of defects shall be as follows:

Defect	Method of Inspection
MAJOR	
101. Improper stitch type	Visual
102. Skipped, broken or omitted stitching greater than 1/2 inch in length	Measure
103. Rips or tears	Visual
104. Soiled	Visual
105. Width of pocket, min.	Measure
106. Depth of pocket, min.	Measure
107. Ends of straps incorrectly located	Measure

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:10Z
Check the source to verify that this is the current version before use.

4.3.3 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Twisted strap	Visual
202. Missing or excessive back stitching	Visual
203. Insufficient or excessive stitching per inch	Measure
204. Missing identification	Visual
205. Width of pocket, max.	Measure
206. Depth of pocket, max.	Measure
207. Length of carrying strap	Measure
208. Skipped, broken or omitted stitching, 1/4 to 1/2 inch in length	Measure
209. Length of stitching run-off (Tails)	Measure

4.3.4 Tests.-The following test shall be conducted in accordance with the test methods and procedures prescribed in 4.4.

4.3.4.1 Drop test.-A sample of 50 bandoleers shall be subjected to the drop test. If three or more bandoleers fail to comply with the requirements of 3.3, the lot shall be rejected. If one or two bandoleers fail to comply with the requirements, a second sample consisting of the same number of units as specified in the first sample shall be tested. If in the accumulated sample four or more units fail to comply with the requirements, the lot shall be rejected.

4.3.5 Packing and marking inspection.-Inspection for packing and marking shall be as directed by the contracting officer.

4.3.6 Inspection equipment.-The examination and tests shall be made using equipment approved by the Government.

4.4 Test methods and procedures.

4.4.1 Drop test.-Each test bandoleer shall be filled with inert cartridges, 7.62mm, in links in a carton as shown on Drawing F10534012, or an equivalent weight approximating the size and shape of the filled carton (6 pounds, 8 ounces plus or minus 2 ounces). The filled bandoleer shall then be suspended by the strap, with the weight evenly distributed, from a rigid horizontal bar of approx. 1/2 inch diameter. The strap, at the point of suspension, shall then be raised vertically one foot and dropped upon the bar.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:10Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packing.-Level C (domestic shipment).-Bandoleers shall be packed in a fiberboard box as follows: 1000 bandoleers in 40 bundles, 25 bandoleers per bundle. Straps are to be random folded and placed inside each bandoleer. Bandoleers are to be packaged oriented in the same direction (front side up) in neat bundles of 25 pieces and secured to prevent disarrangement during shipment. The bandoleers shall be packed within a corrugated fiberboard box, 350 lb test, conforming to style RSC of PPP-B-636, containing a preformed, bag type, interior wrap conforming to barrier material, Class C-1, of PPP-B-1055.

5.2 Marking.-Each box shall be marked with the bandoleer manufacturer's name, lot number and date of manufacture and other markings in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data.-Invitations for bids and contracts or orders will specify the following:

6.1.1 Title, number and date of this specification.

6.1.2 Requirement for contractor to provide and maintain an inspection system in accordance with MIL-I-45208, Inspection System Requirements.

6.2 The 50 samples submitted for First Article evaluation should not be subjected to the drop test prior to submission to the Government.

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1305- A752

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:10Z
Check the source to verify that this is the current version before use.