MILITARY SPECIFICATION SHEET

CABLE ASSEMBLY, T4132-1

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-50288(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for Cable Assembly, T4132-1.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-50288(MU) - Cable Assemblies for War Reserve Atomic Demolition Charges, General Specification for
MIL-P-116 - Preservation, Methods of

DRAWINGS

ORDNANCE CORPS

8808362 - Packing and Marking for Storage and Shipments
8836735 - Clip
8838893 - Lug, Spade
8838897 - Cable Assembly T4132-1
8838898 - Plug, Insulated, Double
8846959 - Bag, Packing, Ammunition, for Cable Assembly, Special Purpose, Electrical: T4132-1
8858702 - Insulator
EL-8838897 - Equipment List

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

3.1 Requirements. Requirements shall be in accordance with MIL-C-50288(MU) and as specified herein.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with Table I.

Table I

Circuit resistance (see dwg 8838897)

From connector Pin	To Clip	Ohms max
In line with cable	Red	0.2
Not in line with cable	Black	0.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality assurance provisions. Quality assurance provisions shall be in accordance with MIL-C-50288(MU) and as specified herein.

4.2 Classification of characteristics.

4.2.1 Clip (see dwg 8836735); lug, spade (see dwg 8838893); plug, insulated, double (see dwg 8838898); insulator (see dwg 8858702); covering details of dwg 8838897.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see Objective evidence, section 6, MIL-C-50288(MU) available for part in accordance with applicable drawing.....	Visual
Minor: None defined.		

4.2.2 Cable assembly T4132-1 (see dwg 8838897).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Length.....	*Measure
102.	Length from clips to mold.....	*Measure
103.	Marking.....	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

104. Cable free of paint.....Visual
105. Objective evidence (see Objective evidence, section 6, MIL-C-50288(MU) for protective finish in accordance with dwg 8838897.....Visual

* Measure with suitable scale.

Minor:
201. Serialization (see Serialization, section 3, MIL-C-50288(MU).....Visual

4.2.3 Bag, packing, ammunition, for cable assembly, special purpose, electrical: TH132-1 (see dwg 8846959).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Plug and clips wrapped and secured with tape.....Visual
102. Cable coiled properly and secured with tape.....Visual
103. Length of bag before packing, min.....*Measure
104. Width of bag before packing, min.....*Measure
105. Air exhausted from bag.....Visual-Manual
106. Proper heat seal.....Visual-Manual
107. Objective evidence (see Objective evidence, section 6, MIL-C-50288(MU) available in accordance with Heat Seal Test, MIL-P-116.....Visual
108. Materials (see Materials, section 3, MIL-C-50288(MU).....Visual
109. Marking.....Visual

* Measure with suitable scale.

Minor: None defined.

4.3 Acceptance inspection equipment. Acceptance inspection equipment shall be in accordance with MIL-C-50288(MU) and EL-8838897.

4.4 Test methods.

4.4.1 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with Table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

Table II

Insulation resistance (see dwg 8838898)

Positive potential applied to connector pin	Minus potential to all other pins, shell and clips except
In line with cable	Red clip
Not in line with cable	Black clip

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-50288(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-50288(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs 8846959 and 8808362 and as specified in MIL-C-50288(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwg 8808362 and MIL-C-50288(MU).

5.2.2 Packing.

5.2.2.1 Levels A and C. The cable assembly shall be packed in accordance with dwgs 8846959 and 8808362 and MIL-C-50288(MU).

5.2.3 Marking. Marking shall be as specified in dwgs 8846959 and 8808362 and MIL-C-50288(MU).

6. NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-50288(MU).

Custodian:
Army - MU

Preparing Agency
Army - MU

Project No. - 1125-A045

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-C-50288//7(MU) Cable Assembly, T4132-1

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-NR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.