INCH-POUND

MIL-DTL-55302/145C
w/AMENDMENT 3
12 October 2022
SUPERSEDING
MIL-DTL-55302/145C
w/AMENDMENT 2
30 November 2012

DETAIL SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, RECEPTACLE WITH PIN CONTACTS, 2 FEMALE KEYING GUIDES, 2.114 INCHES LENGTH, FOR PRINTED WIRING BOARDS (.100 INCH SPACING)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-55302.




FIGURE 1. Connector, receptacle (.100 inch spacing).

AMSC N/A FSC 5935

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
.006	0.15	.142	3.61
.012	0.30	.153	3.89
.016	0.41	.189	4.80
.0229	0.582	.200	5.08
.024	0.61	.248	6.30
.0244	0.620	.252	6.40
.050	1.27	.305	7.75
.071	1.80	.317	8.05
.100	2.54	1.800	45.72
.122	3.10	2.114	53.70

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).
4. Standoffs are located between each cable hole and between each hole and contact hole set.

FIGURE 1. Connector, receptacle (.100 inch spacing) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.



Inches	mm
.004	0.10
.030	0.76
.050	1.27
.060	1.52
.070	1.78
.100	2.54
.106	2.69
.118	3.00
.200	5.08
.240	6.10
.320	8.13
1.80	45.7

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).

FIGURE 2. Recommended hole patterns.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.





FIGURE 3. Coaxial configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm
.020	0.51	.138	3.51
.03	0.8	.139	3.53
.063	1.60	.155	3.94
.071	1.80	.157	3.99
.076	1.93	.158	4.01
.079	2.01	.165	4.19
.094	2.39	.177	4.50
.095	2.41	.185	4.70
.100	2.54	.189	4.80
.110	2.79	.271	6.88
.122	3.10	.303	7.70
.126	3.20	.317	8.05
		.374	9.50

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).

FIGURE 3. Coaxial configurations – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.




FIGURE 4. Contact and keying arrangements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.




FIGURE 5. Connector terminations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm
.010	0.25	.063	1.60	.177	4.50
.014	0.36	.100	2.54	.200	5.08
.020	0.51	.118	3.00	.217	5.51
.025	0.64	.126	3.20	.236	5.99
.056	1.42	.155	3.94	.490	12.45
.062	1.57	.173	4.39		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).
4. Solder tail accepts no. 22 AWG wire.
5. Crimp contact accepts no. 22-26 AWG wire.
6. Contact with .025 inch^2 (0.64 mm^2) wrappost.

FIGURE 5. Connector terminations - Continued.





FIGURE 6. Recommended panel cutouts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
.004	0.10	.374	9.50
.008	0.20	.809	20.55
.116	2.95	.900	22.86
.187	4.75	1.618	41.10
.197	5.00	1.800	45.72

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).
4. Floating mount panel thickness .085 (2.16 mm) maximum.

FIGURE 6. Recommended panel cutouts - Continued.



(1R & 2R) RECEPTACLE - FIXED
JACKSOCKET - POLARIZED

Inches	mm
.085	2.16
.098	2.49
.282	7.16

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .015 (0.38 mm).
4. 1R has hexagonal base with 6 polarizing positions; 2R has a square base with 4 polarizing positions.

FIGURE 7. Mounting hardware.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions and configurations: See figures 1 through 6.

Contact identification: See figure 4.

Contact retention: Coaxial and power: 11.25 pounds minimum.
Signal: 4 pounds minimum.

Mating and unmating force (per contact):	Coaxial	Power	Signal
(Min)	7.2 ounces	3.6 ounces	0.7 ounce
(Max)	36 ounces	18 ounces	3.6 ounces

Values for each connector to be addition of contacts according to contact type.

Contact resistance: 12 milliohms maximum.

Dielectric withstanding voltage:

Sea level: 1,000 V rms, 60 Hz.

High altitude: 300 V rms, 60 Hz.

Current rating:

Power contacts: 25 amperes at 25°C.

Coaxial contacts: .5 ampere at 25°C.

Signal contacts: 3 amperes at 25°C.


Keying: Moldings and mounting hardware provide 16 or 36 polarizing positions according to choice of 4 or 6 way capability. Connectors are supplied with hex pins in the “1” and “A” positions, except for 1/4-turn locking styles, which are keyed in “F” and “6” positions. When required, connectors can be easily keyed to desired position by using a simple wrench.

Mating connectors: In accordance with MIL-DTL-55302/150.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

Part or Identifying Number (PIN): Consists of the letter M, the basic number of the specification sheet, and a dash number compiled as follows:

Example:



Qualification: Qualification is not required for this specification sheet.

First article testing (FAT): FAT shall be in accordance with MIL-DTL-55302, qualification inspection.

Sample size: 6 connectors shall be subjected to the FAT. All sample units shall be subjected to the inspections in subgroup I. The sample units shall be divided equally into 3 groups of 2 and subjected to the inspection for their particular subgroups. Contacts shall be tested as specified in subgroup 4A or 4B as applicable.

Amendment notations. The margins of this specification are marked with vertical lines to indicate where modifications from this amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-DTL-55302, this document references the following:

MIL-DTL-55302/150

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2022-204)

Review activities:
Army - AR, AT, AV, CR4, MI
Navy - AS, MC, OS, SH
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.