MILITARY SPECIFICATION

LIGHT, MARKER, DISTRESS, BUOYANT, DROPPABLE

This amendment forms a part of Military Specification MIL-L-81509(AS), dated 5 December 1966, and has been approved by the Naval Air Systems Command, Department of the Navy.

Page 1

1.1 SCOPE, at the end of the sentence: Add "and power supply."

2.1 SPECIFICATIONS: Under "Federal" delete "PPP-T-45" and add the following:

"PPP-B-566	Box, Folding, Paperboard
PPP-T-76	Tape, Pressure-Sensitive Adhesive Paper, Water Resistant (For Carton Sealing)"

Page 2

2.1 STANDARDS: Under "Military" delete "MS27981".

Page 3

3.1 Preproduction, title and line 3: Delete "preproduction" and substitute "first article".

3.2 Materials and components, line 2: After "herein" add: "No material or component used in the construction of the light or battery, as applicable, shall have any deleterious effect on itself or any other material or component used in the construction of the light or battery, as applicable."

3.3 Design, line 3: After "supply" add "compartment."

FSC 6230

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:32Z
Check the source to verify that this is the current version before use.

3.4.1 Power Supply:

(a) Line 8: Delete "MS27981-3N" and "MS27981-4N" and substitute "United Carr Fastener Corporation, Cambridge, Massachusetts, miniature stud Part Number BS52719-K1105, and miniature socket Part Number HS52784-K1105, or equivalent".

(b) Line 11: Change "12-3/8 by 1-3/8" to "12-11/32 ± 1/16 by 1-11/32".

(c) Line 13: Delete in its entirety and substitute the following: "Corporation, New York, New York, Part Number Y-1230-2; Mallory Battery Company, Division of P. R. Mallory and Company, Incorporated, Tarrytown, New York, Part Number 304031; or equivalent."

Page 4

Top of the page, under "Minimum Average Candlepower", line 4: Delete "150" and substitute "40".

Page 5

3.9 Workmanship: Delete in its entirety and substitute the following:

"3.9 Workmanship - The droppable buoyant distress marker light or power supply, as applicable, shall not be misaligned, deformed, nor contain any rough surface, nick, burr, sharp edge, crack, embedded foreign matter, detached component, or loose particle. The light or power supply, as applicable, shall be uniform in quality and shall be free from mechanical, electrical, or other irregularities or defects which could adversely affect performance, reliability or durability. The lights or power supplies, as applicable, shall conform to the quality and grade of product established by this specification. The occurrence of defects shall not exceed the acceptance criteria established herein."

Page 6

Top of the page, (a) Preproduction inspection, title and line 1: Delete "preproduction" and substitute "first article".

4.3 Preproduction:

(a) Title and line 1: Delete "preproduction" and substitute "first article".

(b) Line 2: After "lights" add "or power supply, as applicable".

Source: https://assist.dla.mil -- Downloaded: 202640-23T05:32Z
Check the source to verify that this is the currentversion before use.

4.3.1 Preproduction samples:

(a) Title and lines 6, 7, 8, 9, and 13: Delete "preproduction" and substitute "first article".

(b) Line 3: Delete "and five additional power supplies" and substitute "or five power supplies, as applicable".

4.3.1.1:

(a) Lines 1 and 5: Delete "preproduction" and substitute "first article".

(b) Line 4: Delete "and the additional power supplies" and substitute "or the power supplies, as applicable."

Page 7

Top of the page, lines 2 and 3: After "lights" add "or power supplies, as applicable."

4.4.1.1.2 Lights, lines 2 and 4: Delete "power supply and".

4.4.1.1.3 Preparation for delivery: Delete in its entirety and substitute the following:

"4.4.1.1.3 Preparation for delivery - An inspection lot size shall be expressed in units of one fully prepared shipping container, containing power supplies or lights with the lamps installed, as applicable, fully prepared for delivery from essentially the same materials and components. The sample unit shall be one shipping container, containing power supplies or lights with the lamps installed, as applicable, fully prepared for delivery with the exception that it need not be sealed."

4.4.1.2 Sampling for tests and examinations: Delete in its entirety and substitute the following:

"4.4.1.2 Sampling for tests and examinations of the power supplies, lights, and preparation for delivery - The sample size, acceptance criteria, tests and examinations required for the power supplies, lights, or preparation for delivery, as applicable, shall be as specified in Table I."

Page 8

TABLE I SAMPLE SIZE, ACCEPTANCE CRITERIA, TESTS, AND EXAMINATIONS OF THE LIGHTS:

(a) Delete the "title" and substitute the following: "SAMPLE SIZE, ACCEPTANCE CRITERIA, TESTS, AND EXAMINATIONS OF THE POWER SUPPLIES, LIGHTS, AND PREPARATION FOR DELIVERY."

(b) Delete the "CLASSIFICATION OF CHARACTERISTIC" column in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:32Z
Check the source to verify that this is the current version before use.

(c) In the "SAMPLE SIZE" column for "Visual Examination": After "light" add "or power supply, as applicable."

Page 9

4.6.2.1 Lights: Delete in its entirety and substitute the following:

"4.6.2.1 Lights and power supplies - Every light or power supply, as applicable, shall be examined visually for major defects to determine conformance to this specification. Each light or power supply, as applicable, selected as a sample unit from the lot, shall be thoroughly checked dimensionally and examined visually for minor defects to determine conformance to this specification. The classification and list of defects, Tables III and IV, as applicable, shall be used to classify and enumerate the defects found."

4.6.2.2 Preparation for delivery: Delete in its entirety and substitute the following:

"4.6.2.2 Preparation for delivery - Each of the fully prepared shipping containers, containing power supplies or lights with the lamps installed, as applicable, selected as a sample unit from the lot, shall be visually examined to determine that the packaging, packing and marking conform to this specification. The list of defects, Table V, shall be used to enumerate the defects found."

Page 10

TABLE III CLASSIFICATION OF DEFECTS FOR THE VISUAL EXAMINATION OF THE LIGHTS:

(a) Delete the "title" and substitute the following: "CLASSIFICATION OF DEFECTS FOR THE VISUAL EXAMINATION OF THE LIGHTS AND POWER SUPPLIES."

(b) Defect 105: Delete "power supply or".

(c) Add the following new "MAJOR" defect:

"108. Any power supply installed in any light."

TABLE IV LIST OF DEFECTS FOR FINISHED DIMENSIONS OF THE LIGHTS:

(a) Delete the "title" and substitute the following: "LIST OF DEFECTS FOR THE DIMENSIONS OF THE ASSEMBLED LIGHTS AND POWER SUPPLIES."

(b) In the "EXAMINE" column: After "light" add "or power supply, as applicable."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:32Z
Check the source to verify that this is the current version before use.

Page 11

TABLE V LIST OF DEFECTS FOR PREPARATION FOR DELIVERY, in the "DEFECT" column last line: Delete "separately" and substitute "together."

Pages 16 and 17

5. PREPARATION FOR DELIVERY: Delete in its entirety and substitute the following:

"5. PREPARATION FOR DELIVERY

5.1 Packaging - Packaging shall be Level A or C, as specified (see 6.2(d)). The power supplies shall not be installed in the lights.

5.1.1 Level A -

5.1.1.1 Lights - The lights with the lamp installed and without the power supplies shall be preserved and cushioned in accordance with MIL-P-116, Method III. No contact preservative is required. Each light shall be packaged within a snug fitting fiberboard container conforming to PPP-B-636, Type CF or SF, Domestic Class, Variety SW, Grade 125. Twelve of the boxed lights shall be packaged within a snug fitting fiberboard container conforming to PPP-B-636, Type CF or SF, Domestic Class, Variety SW, Grade 275. The individual and outer containers shall be constructed and closed in accordance with the appendix to PPP-B-636. All the seams shall be sealed with the 3 inch minimum wide tape conforming to PPP-T-76.

5.1.1.2 Power supplies - The power supplies shall be preserved and cushioned in accordance with MIL-P-116, Method III. No contact preservative is required. Twelve power supplies shall be packaged within a folding box conforming to PPP-B-566. The power supplies shall be separated by paperboard partitions and snugly cushioned to prevent movement within the container. The cushioning material shall be neutral and noncorrosive.

5.1.2 Level C - The lights or the power supplies, as applicable, shall be packaged to afford the minimum degree of protection necessary to prevent deterioration or damage during shipment and normal environmental conditions and commercial modes of transportation.

5.2 Packing - Packing shall be Level A, B, or C, as specified (see 6.2(d)).

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:32Z
Check the source to verify that this is the current version before use.

5.2.1 Level A -

5.2.1.1 Lights - Twenty-four lights (two containers), packaged as specified in 5.1.1.1, shall be packed as specified in 5.2.2.1, except that the fiberboard container shall be Weather-Resistant Class, Variety SW, Grade V3c or V3s. In addition, each container shall be reinforced with flat steel strapping or tape in accordance with the appendix to PPP-B-636.

5.2.1.2 Power Supplies - Sixty power supplies (five containers), packaged as specified in 5.1.1.2, shall be packed as specified in 5.2.2.2, except that the fiberboard container shall be Weather-Resistant Class, Variety SW, Grade V3c or V3s. In addition, each container shall be reinforced with flat steel strapping or tape in accordance with the appendix to PPP-B-636.

5.2.2 Level B -

5.2.2.1 Lights - Twenty-four lights (two containers), packaged as specified in 5.1.1.1, shall be packed within a snug fitting fiberboard container conforming to PPP-B-636, Type CF or SF, Domestic Class, Variety SW, Grade 275. All the seams shall be sealed with the 3 inch minimum wide tape conforming to PPP-T-76. The container shall be constructed and closed in accordance with the appendix to PPP-B-636.

5.2.2.2 Power supplies - Sixty power supplies (five cartons), packaged as specified in 5.1.1.2, shall be packed within a snug fitting fiberboard container conforming to PPP-B-636, Type CF or SF, Domestic Class, Variety SW, Grade 275. All the seams shall be sealed with the 3 inch minimum wide tape conforming to PPP-T-76. The container shall be constructed and closed in accordance with the appendix to PPP-B-636.

5.2.3 Level C - The packaged lights or power supplies, as applicable, which require packing for acceptance by the carrier shall be packed within exterior type shipping containers in a manner that shall assure safe transportation at the lowest rate to the point of delivery. The shipment shall conform to the minimum requirements of the rules and regulations applicable to the mode of transportation selected."

Page 17

6.2 Ordering data:

(a) Subparagraphs (b) and (c): Delete "preproduction" and substitute "first article".

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:32Z
Check the source to verify that this is the currentversion before use.

(b) Add the following new subparagraphs:

"(e) Certificate of compliance for the age of the elastomeric materials (see 3.2).

(f) Certificate of compliance for the age of the power supplies (see 3.2 and 3.7.2).

(g) Which item is required, i.e. lights or power supplies.

(h) Quantity desired."

Preparing Activity:
Navy - AS
(Project No. 6230-N198)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:32Z
Check the source to verify that this is the current version before use.