MIL-V-0050065C(EA)
30 June 1977
SUPERSEDING
MIL-V-0050065B(MU)
7 December 1970
USED IN LIEU OF
MIL-V-50065A
30 September 1964

MILITARY SPECIFICATION

VALVE, NOSECUP

This limited coordination Military specification has been prepared by US Army Armament Research and Development Command based upon currently available technical information, but it has not been approved for promulgation as a coordinated revision of Military Specification MIL-F-50065A. It is subject to modification. However, pending its promulgation as a coordinated Military specification, it may be used in procurement.

1. SCOPE

1.1 This specification covers one type of chemical-biological mask nosecup valve.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

STANDARDS

FEDERAL

FED-STD-123 - Marking for Shipment (Civil Agencies).

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

FSC 4240

: Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn: DRDAR-TSC-S, Aberdeen Proving Ground, MD 21010 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:15Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

EDGEWOOD ARSENAL

B5-2-464	-	Valve, Nosecup
A5-2-1005	-	Disk, Valve, Nonmetallic, Nosecup.
B136-14-170-1	-	Air Leakage Tester, Flow Type, Q211, Assembly

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and components. All materials and components shall conform to the specifications and drawings forming a part of this specification. Material listed as part No. B5-2-464C, listed on Drawing B5-2-464, shall be used.

3.2 Manufacture and assembly. The nosecup valve shall be manufactured and assembled as specified on Drawing B5-2-464.

3.3 Valve leakage. Leakage through the valve assembly shall not exceed 150 millilitres per minute when subjected to a pressure differential of one inch of water when tested as specified in 4.4.4.1.

3.4 Preproduction. Prior to the start of regular production, a preproduction sample of valves shall be produced in accordance with this specification for examination and test (see 4.3). Any change in methods, materials, tools, equipment or operating conditions shall require a new preproduction sample.

3.5 Workmanship. The valve shall be free from foreign matter and damage, such as distortion, surface irregularities, or dents on the seating surface which would impair its use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:15Z
Check the source to verify that this is the current version before use.

4.1.1 Contractor's responsibility. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The contractor shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3)
(b) Quality conformance inspection (see 4.4)

4.3 Preproduction inspection.

4.3.1 Sample. A preproduction sample of five valves shall be produced using the same methods, materials, tools, and equipment as will be used during regular production.

4.3.2 Inspection.

4.3.2.1 For examination. The sample valves shall be inspected for all requirements of the drawings and this specification.

4.3.2.2 For tests. The sample valves shall be tested in accordance with 4.4.4.

4.3.3 Acceptance/rejection criteria. The valves shall meet the examinations and tests specified by 4.3.2.1 and 4.3.2.2 to be acceptable. The supplier shall obtain written approval from the contracting officer before proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. A regular production lot shall consist of the valves produced by one manufacturer, at one plant, from the same materials, the same tools, and under the same manufacturing conditions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:15Z
Check the source to verify that this is the current version before use.

4.4.2 Sampling.

4.4.2.1 For examination and nondestructive tests. Sampling shall be in accordance with MIL-STD-105.

4.4.3 Inspection procedure.

4.4.3.1 For examination and nondestructive tests. Sample valves shall be examined and tested in accordance with the classification of defects amd with MIL-STD-105.

4.4.3.2 Classification of defects.

(a) Valve, nosecup (Dwg B5-2-464).

Categories	Defects	Acceptance standards
Critical:	None defined	
Major:	AQL 0.25 percent defective	
101	Valve leakage	4.4.4.1
	AQL 1.0 percent defective	
102	Rivet missing, incorrect, or incorrectly assembled	
*103	Outside diameter of flanges incorrect	
104	Inside diameter of cup incorrect	
105	Workmanship (see 3.5)	
Minor:	AQL 2.5 percent defective	
201	Protective finish missing or incorrect	
202	Burrs or sharp edges	

*This characteristic is tool controlled.

4.4.4 Tests.

4.4.4.1 Valve leakage. The nosecup valve, assembled with a disk (Dwg A5-2-1005), shall be tested for leakage with the Q'll Flow Type Air Leakage Tester Assembly (Drawing B136-14-70-1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:15Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, and marking, interplant shipment (see 6.5). The nosecup valves shall be packaged and packed to provide adequate protection from physical damage from the supply source to the first receiving activity for immediate use or further processing. Shipping containers shall be in compliance with the rules and regulations applicable to the mode of transportation. Marking shall be in conformance with FED-STD-123.

5.2 Repair part. When this item is procured for storage and issue as a repair part, preservation, packaging, packing and marking shall be as specified on the repair part packaging data sheet which is identified by the National stock number for the repair part.

6. NOTES

6.1 Intended use. This specification covers a nosecup valve for use with chemical-biological masks.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Preproduction.

(1) Time allowed for supplier submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the supplier whether or not to proceed with production.

6.3 Valve disk. The valve disks required for use in performing the valve leakage tests will be furnished by the Government and should be obtained as directed by the contracting officer.

6.4 International interest. Certain provisions of this specification are the subject of international standardization agreement (see Serial No. 21, Supplement B to Quadripartite Standardization List Sheet Report). When amendment, revision of cancellation of this specification is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:15Z
Check the source to verify that this is the current version before use.

6.5 Interplant shipments. Packaging for supplies and materials which will not enter the military supply system. Typical interplant shipments are shipments from a vendor to a subcontractor or a prime contractor, or from a subcontractor to a prime contractor, or from a vendor or contractor to a military arsenal or plant.

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 4240-A697

☆U.S. GOVERNMENT PRINTING OFFICE: 1977—703-020/4036

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:15Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commander
US Army Armament Research and Development Command
Attn: DRDAR-TSC-S
Aberdeen Proving Ground, MD 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:15Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES DD FORM 1426, 1 OCT 58, WHICH MAY BE USED.

Source: https://assist.dla.mil - Downloaded: 2026-01-22T20:15Z
Check the source to verify that this is the current version before use.