MILITARY SPECIFICATION

MICROCIRCUIT, DIGITAL, BIPOLAR, LOW-POWER SCHOTTKY TTL,
PARITY CHECKER, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/329A, dated 22 August 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Delete and substitute as printed above.

1.2.3, Outline letter: Delete "X" and substitute "2".

1.3, Thermal resistance, delete and substitute:

"Thermal resistance, junction-to-case (θ_{JC}):

Cases R and S - - - - - - - - - - - - - - - - - (See MIL-M-38510, appendix C)
Case 2- 60°C/W 2/"

1.3, Junction temperature, delete and substitute:

"Junction temperature (T_J) 3/ - - - - - - - - +175°C"

After footnote 1/, add footnotes 2/ and 3/ as follows:

"2/ When a thermal resistance value is included in MIL-M-38510, appendix C, it shall supersede the value stated herein.

3/ Maximum junction temperature shall not be exceeded except for allowable short duration burn-in screening conditions per method 5004 of MIL-STD-883."

PAGE 2

3.2.3, delete and substitute:

"3.2.3 Schematic circuits. The schematic circuits shall be submitted to the preparing activity prior to inclusion of a manufacturer's device in the specification and shall be submitted to the qualifying activity and agent activity (DESC-ECS) as a prerequisite for qualification. All qualified manufacturers' schematics will be maintained by the agent activity and will be available upon request."

3.3 Lead material and finish: Delete "(see 6.5)." and substitute "(see 6.4).".

PAGE 3

TABLE I, Low-level output, V_{OL}: Delete "I_{OL} = +4.0 V" and substitute "I_{OL} = +4.0 mA". Input clamp voltage, V_{IC}, max limits: Delete "1.5" and substitute "-1.5".

PAGE 4

TABLE II, group A test requirements, class B: After 7 add "8".

PAGE 5

FIGURE 1: Delete "Case X" and substitute "Case 2".

PAGES 10, 11, and 12

TABLE III, cases: Delete "Case X" and substitute "Case 2".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-21T14:14Z
Check the source to verify that this is the current version before use.

PAGE 13

4.2.c, delete in its entirety and substitute: "The percent defective allowable (PDA) shall be as specified in MIL-M-38510."

PAGE 14

6.1 notes, delete in its entirety and renumber the rest of the paragraphs.

6.3 Abbreviation, symbols, and definitions, GND: Delete "Electrical ground (common terminal)" and substitute "Ground zero voltage potential".

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - SH, OS, TD
Air Force - 11, 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1023)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:14Z
Check the source to verify that this is the current version before use.