MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, BIPOLAR, ADVANCED SCHOTTKY TTL,
NAND GATES, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/330B, dated 5 April 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title, delete and substitute as printed above.

1.2.3, delete case outlines X and Y and respective descriptions, and substitute:

"2 C-2 (20-terminal, .350" x .350"), square chip carrier package".

1.3, Thermal resistance, junction-to-case (θ_{JC}): Delete and substitute as follows:

"Cases A, B, C, and D - - - - - - - (See MIL-M-38510, appendix C)
Case 2 - - - - - - - - - - - - - - 60°C/W 2/".

1.3, Junction temperature (T_J), add "3/" after (T_J).

After footnote 1/ add the following footnotes:

"2/ When a thermal resistance value is included in MIL-M-38510, appendix C, it shall supersede the value stated herein.

"3/ Maximum junction temperature shall not be exceeded except for allowable short duration burn-in screening conditions per method 5004 of MIL-STD-883."

PAGE 2

1.4, after Supply voltage, add "(V_{CC})".

1.4, delete "Normalized fanout (each output) 2/:" and substitute "Normalized fanout (each output) 4/:".

3.2.3, delete and substitute:

"3.2.3 Schematic circuits. Schematic circuits shall be submitted to the preparing activity prior to inclusion of a manufacturer's device in the specification and shall be submitted to the qualifying activity and agent activity (DESC-ECS) as a prerequisite for qualification. All qualified manufacturers' schematics shall be maintained by the agent activity and will be available upon request."

Bottom of page, delete footnote "2/" and substitute footnote "4/".

PAGE 4

TABLE II, Interim electrical parameters, delete "(pre burn-in)".

3.6, Marking, delete second second.

PAGE 5

4.2.c, delete and substitute "c. The percent defective allowable (PDA) shall be as specified in MIL-M-38510."

4.4.3.c. (3) delete "appendix B of MIL-M-38510." and substitute "method 1005 of MIL-STD-883."

Source: https://assist.dla.mil--Downloaded: 20261021T14:14Z
Check the source to verify that this is the current version before use.
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

PAGE 7

FIGURE 1, delete "Case X, Y" and substitute "Case 2". Make this same change on pages 8, 9, and 10.

PAGE 12

FIGURE 3, line 2, delete "X, and Y" and substitute "and 2". Make this same change on pages 13, 14, and 15.

FIGURE 3, line 3, delete "for cases X and Y" and substitute "for case 2". Make this same change on pages 13, 14, and 15.

PAGE 17

TABLE III, column four, delete "Cases X, Y" and substitute "Case 2". Make this same change on pages 18, 19, 20, 21, 22, 23, and 24.

PAGE 18

TABLE III, Subgroup 9, t_{PHL}, (device type 01, test nos. 55-62), (device type 02, test nos. 51-56), (device type 03, test nos. 57-65), (device type 04, test nos. 49-56), min limits column, delete "2.0" and substitute "1.5". Make this same change on pages 20, 22, and 24.

PAGE 25

6.1, delete in its entirety.

6.4, delete "Electrical ground (common terminal)" and substitute "Ground, zero voltage potential".

PAGE 26

TABLE IV, device types 01, 02, 03, and 04, Circuit C column, add "X" for each device type.

Custodians:
Air Force - 17
Army - EC
Navy - ER

Review activities:
Army - AR, MI
Navy - OS, SH, TD
Air Force - 11, 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-0922)

Source: https://assist.dla.mil -- Downloaded: 202610-21T14:14Z
Check the source to verify that this is the current version before use.