MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, BIPOLAR, ADVANCED
SCHOTTKY TTL, OCTAL BUFFERS, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/332B, dated 30 October 1987, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

TABLE I, I_{IL1}, device type 01, minimum limits column: Delete "-.03" and substitute "0.0".

TABLE I, I_{IL1}, device types 02 and 03, minimum limits column: Delete "-.03" and substitute "0.0".

TABLE I, I_{IL2}, device types 02 and 03, minimum limits column: Delete "-.03" and substitute "0.0".

PAGE 4

TABLE I, I_{OZL}, unit column: Delete "mA" and substitute "μA".

PAGE 5

TABLE I, propagation delay time, off state to high level, $\overline{OE}$ to $\overline{Y}$, t_{PZH1} and t_{PZH2}: Delete and substitute as follows:

"

Propagation delay time, off state to high level, $\overline{OE}$ to Y	t_{PZH1}	01	2.0	6.5	ns
	t_{PZH4}	04	2.5	9.0	ns

"

3.6, delete in its entirety and substitute:

"3.6 Marking. Marking shall be in accordance with MIL-M-38510."

Add paragraph 3.7 as follows:

"3.7 Microcircuit group assignment. The devices covered by this specification shall be in microcircuit group number 9 (see MIL-M-38510, appendix E)."

PAGE 11

FIGURE 2, device type 01, second truth table, last line, $\overline{Y2}$ outputs column: Delete "X" and substitute "Z".

PAGE 22

TABLE III, device type 01, t_{PLH1}, test numbers 95 through 97, $\overline{OE1}$ column: Add "„", respectively.

TABLE III, device type 01, t_{PLH1}, test number 94, minimum limits column: Delete "1.5" and substitute "1.0".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:15Z
Check the source to verify that this is the current version before use.

PAGE 23

TABLE III, device type 01, t_{PHL1}, test number 102, minimum limits column: Delete "1.5" and substitute "1.0".

TABLE III, device type 01, t_{PHL1}, test numbers 107 through 109, $\overline{OE2}$ column: Add "„", respectively.

TABLE III, device type 01, t_{PHZ1}, test number 110, maximum limits column: Delete "5.3" and substitute "6.0".

TABLE III, device type 01, t_{PZH1}, test number 126, maximum limits column: Delete "5.5" and substitute "6.0".

TABLE III, device type 01, footnote 1/: Delete in its entirety and substitute as follows:

"1/ I_{IL} limits shall be as follows:

Test	Min/Max limits (mA) for circuit			
	A	B	C	D
I_{IL1}	-.42/-1.0	-.03/-1.0	-.03/-1.0	0.0/-0.3

"

TABLE III, device type 01, footnote 3/: Delete and substitute: "3/ A ≥ 2.4 V, B ≤ 0.50 V, H ≥ 1.5 V, L ≤ 1.5 V".

PAGE 25

TABLE III, device type 02, I_{OD}, test number 85, OE2 column: Delete "5.5 V" and substitute "4.5 V".

TABLE III, device type 02, t_{PLH2}, test number 94, minimum limits column: Delete "1.5" and substitute "1.0".

PAGE 26

TABLE III, device type 02, t_{PHL2}, test number 102, minimum limits column: Delete "1.5" and substitute "1.0".

PAGE 27

TABLE III, device type 02, footnote 1/: Delete in its entirety and substitute as follows:

"1/ I_{IL} limits shall be as follows:

Test	Min/Max limits (mA) for circuit			
	A	B	C	D
I_{IL1}	-.03/-1.6	-.03/-1.6	-.03/-1.6	0.0/-0.3
I_{IL2}	-.03/-1.0	-.03/-1.0	-.06/-1.0	0.0/-0.3

"

TABLE III, device type 02, footnote 3/: Delete and substitute: "3/ A ≥ 2.4 V, B ≤ 0.50 V, H ≥ 1.5 V, L ≤ 1.5 V".

PAGE 29

TABLE III, device type 03, t_{PLH2}, test number 94, minimum limits column: Delete "1.5" and substitute "1.0".

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:15Z
Check the source to verify that this is the current version before use.

PAGE 30

TABLE III, device type 03, t_{PHL2}, test number 102, minimum limits column: Delete "1.5" and substitute "1.0".

TABLE III, device type 03, t_{PZL2}, test numbers 139 through 141, $\overline{OE2}$ column: Add "„", respectively.

TABLE III, device type 03, footnote 1/: Delete in its entirety and substitute as follows:

"1/ I_{IL} limits shall be as follows:

Test	Min/Max limits (mA) for circuit			
	A	B	C	D
I_{IL1}	-.03/-1.6	-.03/-1.6	-.03/-1.6	0.0/-0.3
I_{IL2}	-.03/-1.0	-.03/-1.0	-.06/-1.0	0.0/-0.3

"

TABLE III, device type 03, footnote 3/: Delete and substitute: "3/ A ≥ 2.4 V, B ≤ 0.50 V, H ≥ 1.5 V, L ≤ 1.5 V".

PAGE 31

TABLE III, device type 04, I_{IH2}, test number 46, $\overline{OE2}$ column: Delete "2.7 V" and substitute "7.0 V".

PAGE 32

TABLE III, device type 04, functional tests, test number 101, $\overline{OE1}$ column: Delete "A" and substitute "B".

TABLE III, device type 04, functional tests, test number 102, $8\bar{Y}$, $7\bar{Y}$, $6\bar{Y}$, $5\bar{Y}$, $4\bar{Y}$, $3\bar{Y}$, $2\bar{Y}$, and $1\bar{Y}$ columns: Delete "L", "H", "L", "H", "L", "H", "L", and "H" and substitute "H", "L", "H", "L", "H", "L", "H", and "L", respectively.

TABLE III, device type 04, functional tests, test number 103, $8\bar{Y}$, $7\bar{Y}$, $6\bar{Y}$, $5\bar{Y}$, $4\bar{Y}$, $3\bar{Y}$, $2\bar{Y}$, and $1\bar{Y}$ columns: Delete "H", "L", "H", "L", "H", "L", "H", and "L" and substitute "L", "H", "L", "H", "L", "H", "L", and "H", respectively.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - OS, SH, TD
Air Force - 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1290)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:15Z
Check the source to verify that this is the current version before use.