MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, ADVANCED SCHOTTKY TTL, AND-OR-INVERT GATES, MONOLITHIC SILICON

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for monolithic silicon, Advanced Schottky TTL, positive AND-OR-INVERT logic gate microcircuits. Two product assurance classes and a choice of case outlines and lead finishes are provided and are reflected in the complete part number.

1.2 Part number. The part number shall be in accordance with MIL-M-38510, and as specified herein.

1.2.1 Device type. The device type shall be as follows:

Device type	Circuit
01	4-2-3-2 input positive AND-OR-INVERT gate

1.2.2 Device class. The device class shall be the product assurance level as defined in MIL-M-38510.

1.2.3 Case outline. The case outline shall be designated as follows:

Letter	Case outline (see MIL-M-38510, appendix C)
A	F-1 (14-lead, 1/4" x 1/4"), flat package
B	F-3 (14-lead, 3/16" x 1/4"), flat package
C	D-1 (14-lead, 1/4" x 3/4"), dual-in-line package
D	F-2 (14-lead, 1/4" x 3/8"), flat package
2	C-2 (20-terminal, .350" x .350"), square chip carrier package

1.3 Absolute maximum ratings.

Supply voltage range	-0.5 V to +7.0 V
Input voltage range	-1.2 V at -18 mA to +7.0 V
Storage temperature range	-65°C to +150°C
Maximum power dissipation per device (P_D) 1/	25 mW
Lead temperature (soldering, 10 seconds)	300°C
Thermal resistance, junction-to-case, (θ_{JC}):	
Cases (any case in MIL-M-38510)	(see MIL-M-38510, appendix C)
Cases (all LCC's)	0.08°C/W 3/
Junction temperature (T_J), 2/	175°C

1/ Must withstand the added P_D due to short-circuit test (e.g., I_{OS}).

2/ Maximum junction temperature shall not be exceeded except for allowable short duration burn-in screening conditions per method 5004 of MIL-STD-883.

3/ When a thermal resistance value is included in MIL-M-38510, appendix C, it shall supersede the value stated herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Rome Air Development Center (RBE-2), Griffiss AFB, NY 13441, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:16Z
Check the source to verify that this is the current version before use.

1.4 Recommended operating conditions.

Supply voltage (V_{CC})	4.5 V minimum to 5.5 V maximum
Minimum high level input voltage (V_{IH})	2.0 V
Maximum low level input voltage (V_{IL})	0.8 V
Normalized fanout (each output) 2/	
Low logic level	33 maximum
High logic level	50 maximum
Case operating temperature range (T_C)	-55°C to +125°C

2. APPLICABLE DOCUMENTS

2.1 Government specifications and standards. Unless otherwise specified, the following specifications and standards, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-38510 - Microcircuits, General Specification for.

STANDARD

MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Detail specification. The individual item requirements shall be in accordance with MIL-M-38510, and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 herein.

3.2.1 Truth table and logic equation. The truth table and logic equation shall be as specified on figure 1.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 2.

3.2.3 Schematic circuits. The schematic circuits shall be submitted to the preparing activity prior to inclusion of a manufacturer's device in this specification and shall be submitted to the qualifying activity as a prerequisite for qualification. All qualified manufacturers' schematics shall be maintained and available upon request.

3.2.4 Case outlines. The case outlines shall be as specified in 1.2.3.

3.3 Lead material and finish. The lead material and finish shall be in accordance with MIL-M-38510 (see 6.5).

2/ The device shall fanout in both high and low levels to the specified number of data inputs for the same device type as that being tested.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:16Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions $-55°C \le T_C \le +125°C$	Device type	Limits Min	Limits Max	Unit
High-level output voltage	V_{OH}	V_{CC} = 4.5 V, I_{OH} = -1.0 mA, V_{IL} = 0.8 V, V_{IH} = 2.0 V	01	2.5		V
Low-level output voltage	V_{OL}	V_{CC} = 4.5 V, I_{OL} = 20 mA, V_{IH} = 2.0 V	01		0.5	V
Input clamp voltage	V_{IC}	V_{CC} = 4.5 V, I_{IN} = -18 mA, T_C = 25°C	01		-1.2	V
High-level input current	I_{IH1}	V_{CC} = 5.5 V, V_{IN} = 2.7 V	01		20	µA
	I_{IH2}	V_{CC} = 5.5 V, V_{IN} = 7.0 V	01		100	µA
Low-level input current	I_{IL1}	V_{CC} = 5.5 V, V_{IN} = 0.5 V	01	-.03	-.60	µA
Short-circuit output current 1/	I_{OS}	V_{CC} = 5.5 V	01	-60	-150	mA
Output drive	I_{OD}	V_{CC} = 4.5 V, V_{IN} = 5.5 V, V_{OUT} = 2.5 V	01	60		mA
High-level supply current	I_{CCH}	V_{CC} = 5.5 V	01		2.8	mA
Low-level supply current	I_{CCL}	V_{CC} = 5.5 V	01		4.7	mA
Propagation delay time, high-to-low level	t_{PHL}	V_{CC} = 5.0 V, C_L = 50 pF ±10%, R_L = 500Ω ±5%	01	1.0	6.5	ns
Propagation delay time, low-to-high level	t_{PLH}	V_{CC} = 5.0 V, C_L = 50 pF ±10%, R_L = 500Ω ±5%	01	1.0	8.0	ns

1/ Not more than one output should be shorted at a time.

DEVICE TYPE 01											
Input											Output
A	B	C	D	E	F	G	H	I	J	K	Y
H	H	H	H	*	*	*	*	*	*	*	L
*	*	*	*	H	H	*	*	*	*	*	L
*	*	*	*	*	*	H	H	H	*	*	L
*	*	*	*	*	*	*	*	*	H	H	L

* Either H or L - Any combinations of H and L at inputs other than shown will give an H output.

Positive logic : $Y = \overline{ABCD + EF + GHI + JK}$

FIGURE 1. Truth table and logic equation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:16Z
Check the source to verify that this is the current version before use.

3.4 Electrical performance characteristics. The electrical performance characteristics are specified in table I, and apply over the full recommended case operating temperature range, unless otherwise specified.

3.5 Electrical test requirements. The electrical test requirements for each device class shall be the subgroups specified in table II. The electrical tests for each subgroup are described in table III.

3.6 Marking. Marking shall be in accordance with MIL-M-38510.

3.7 Microcircuit group assignment. The devices covered by this specification shall be in microcircuit group number 8 (see MIL-M-38510, appendix E).

TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (see table III)	
	Class S devices	Class B devices
Interim electrical parameters (pre burn-in) (method 5004)	1	1
Final electrical test parameters (method 5004)	1*,2,3,9, 10,11	1*,2,3,9
Group A test requirements (method 5005)	1,2,3, 9,10,11	1,2,3,9
Group B test requirements (method 5005) subgroup 5	1,2,3, 9,10,11	N/A
Group C end-point electrical parameters (method 5005)	N/A	1,2,3
Additional electrical subgroups for group C periodic inspections	N/A	10,11
Group D end-point electrical parameters (method 5005)	1,2,3	1,2,3

*Indicates PDA applies to subgroup 1 (see 4.2c).

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with MIL-M-38510 and methods 5005 and 5007, as applicable, of MIL-STD-883, except as modified herein.

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to qualification and quality conformance inspection. The following additional criteria shall apply:

a. Burn-in test (method 1015 of MIL-STD-883).

(1) Test condition D, using the circuit shown on figure 3, or equivalent.

(2) T_A = +125°C minimum.

b. Interim and final electrical test parameters shall be as specified in table II, except interim electrical parameters test prior to burn-in is optional at the discretion of the manufacturer.

c. The percent defective allowable (PDA) shall be as specified in MIL-M-38510.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:16Z
Check the source to verify that this is the current version before use.

4.3 Qualification inspection. Qualification inspection shall be in accordance with MIL-M-38510. Inspections to be performed shall be those specified in method 5005 of MIL-STD-883 and herein for groups A, B, C, and D inspections (see 4.4.1 through 4.4.4).

4.4 Quality conformance inspection. Quality conformance inspection shall be in accordance with MIL-M-38510. Inspections to be performed shall be those specified in method 5005 of MIL-STD-883 and herein for groups A, B, C, and D inspections (see 4.4.1 through 4.4.4).

4.4.1 Group A inspection. Group A inspection shall be in accordance with table I of method 5005 of MIL-STD-883 and as follows:

a. Tests shall be as specified in table II herein.

b. Subgroups 4, 5, 6, 7, and 8 shall be omitted.

4.4.2 Group B inspection. Group B inspection shall be in accordance with table II of method 5005 of MIL-STD-883. Electrical parameters shall be as specified in table II herein.

4.4.3 Group C inspection. Group C inspection shall be in accordance with table III of method 5005 of MIL-STD-883 and as follows:

a. End-point electrical parameters shall be as specified in table II herein.

b. Subgroups 3 and 4 shall be added to the group C inspection requirements for class B devices and shall consist of the tests, conditions, and limits specified for subgroups 10 and 11 of group A.

c. Steady state life test (method 1005 of MIL-STD-883) conditions, or equivalent.

(1) Test condition D, using the circuit shown on figure 3, or equivalent.

(2) T_A = +125°C minimum.

(3) Test duration: 1,000 hours, except as permitted by appendix B of MIL-M-38510 and method 1005 of MIL-STD-883.

4.4.4 Group D inspection. Group D inspection shall be in accordance with table IV of method 5005 of MIL-STD-883. End-point electrical parameters shall be as specified in table II herein.

4.5 Methods of inspection. Methods of inspection shall be as follows:

4.5.1 Voltage and current. All voltages given are referenced to the microcircuit ground terminal. Currents given are conventional and positive when flowing into the referenced terminal.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510.


6. NOTES

6.1 Intended use. Microcircuits conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:16Z
Check the source to verify that this is the current version before use.

Device type 01

(Cases A, B, C, D)



Device type 01

Case 2





FIGURE 2. Terminal connections (top view).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:16Z
Check the source to verify that this is the current version before use.


Device type 01
Cases A, B, C, D, and 2
(Pins not referenced for case 2 are N/C)



NOTES:
1. CP or $\overline{CP}$ = 100 kHz ±50% square wave; duty cycle = 50 ±15%; V_{IL} = -0.5 V minimum to 0.8 V maximum; V_{IH} = 2.0 V minimum to 5.5 V maximum.
2. R1 = 1 kΩ ±5%; R2 = 160Ω ±5%; R3 = 270Ω.
3. V_{CC} and R4 shall be chosen to insure 5.5 V minimum is present at device V_{CC} terminal.

FIGURE 3. Burn-in and life test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:16Z
Check the source to verify that this is the current version before use.



NOTES:
1. Pulse generator has following characteristics: $t_r = t_f \leq 2.5$ ns; PRR = 1 MHz and $Z_{OUT} \cong 50\Omega$.
2. Inputs not under test are at 2.7 V or GND as specified in table III.
3. C_L = 50 pF ±10% including scope, probe, wiring, and stray capacitance, without package in test fixture.
4. Voltage measurements are to be made with respect to network ground terminal.
5. R_L = 500Ω ±5%.

FIGURE 4. Switching time test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:16Z
Check the source to verify that this is the current version before use.

TABLE III. Group A inspection for device type 01.
Terminal conditions (pins not designated may be high ≥ 2.0 V, low ≤ 0.8 V, or open).

Subgroup	Symbol	MIL-STD-883 method	Cases A,B,C,D Case 2 1/ Test no.	1 2 A	2 3 E	3 4 F	4 6 G	5 8 H	6 9 I	7 10 GND	8 12 Y	9 13 J	10 14 K	11 16 B	12 18 C	13 19 D	14 20 V_{CC}	Measured terminal	Limits Min	Limits Max	Unit
1 T_C = 25°C	V_{OL}	3007	1	2.0 V	GND	GND	GND	GND	GND	GND	20 mA	GND	GND	2.0 V	2.0 V	2.0 V	4.5 V	Y		0.5	V
	"	"	2	GND	2.0 V	2.0 V	GND	GND	GND	"	"	GND	GND	GND	GND	GND	"	"		"	"
	"	"	3	GND	GND	GND	2.0 V	2.0 V	2.0 V	"	"	GND	GND	GND	GND	GND	"	"		"	"
	"	"	4	GND	"	"	GND	GND	GND	"	"	2.0 V	2.0 V	GND	GND	GND	"	"		"	"
	V_{OH}	3006	5	0.8 V	"	"	"	"	"	"	-1 mA	GND	GND	2.0 V	2.0 V	2.0 V	"	"	2.5		"
	"	"	6	2.0 V	"	"	"	"	"	"	"	"	"	0.8 V	2.0 V	2.0 V	"	"	"		"
	"	"	7	2.0 V	"	"	"	"	"	"	"	"	"	2.0 V	0.8 V	2.0 V	"	"	"		"
	"	"	8	2.0 V	"	"	"	"	"	"	"	"	"	2.0 V	2.0 V	0.8 V	"	"	"		"
	"	"	9	GND	0.8 V	2.0 V	"	"	"	"	"	"	"	GND	GND	GND	"	"	"		"
	"	"	10	"	2.0 V	0.8 V	"	"	"	"	"	"	"	"	"	"	"	"	"		"
	"	"	11	"	GND	GND	0.8 V	2.0 V	2.0 V	"	"	"	"	"	"	"	"	"	"		"
	"	"	12	"	"	"	2.0 V	0.8 V	2.0 V	"	"	"	"	"	"	"	"	"	"		"
	"	"	13	"	"	"	2.0 V	2.0 V	0.8 V	"	"	"	"	"	"	"	"	"	"		"
	"	"	14	"	"	"	GND	GND	GND	"	"	0.8 V	2.0 V	"	"	"	"	"	"		"
	"	"	15	"	"	"	GND	GND	GND	"	"	2.0 V	0.8 V	"	"	"	"	"	"		"
	V_{IC}		16	-18 mA						"							"	A		-1.2	"
			17		-18 mA					"							"	E		"	"
			18			-18 mA				"							"	F		"	"
			19				-18 mA			"							"	G		"	"
			20					-18 mA		"							"	H		"	"
			21						-18 mA	"							"	I		"	"
			22							"		-18 mA					"	J		"	"
			23							"			-18 mA				"	K		"	"
			24							"				-18 mA			"	B		"	"
			25							"					-18 mA		"	C		"	"
			26							"						-18 mA	"	D		"	"
	I_{IH1}	3010	27	2.7 V						"				GND	GND	GND	5.5 V	A		20	mA
	"	"	28	GND						"				2.7 V	GND	GND	"	B		"	"
	"	"	29							"				GND	2.7 V	GND	"	C		"	"
	"	"	30							"				GND	GND	2.7 V	"	D		"	"
	"	"	31		2.7 V	GND				"							"	E		"	"
	"	"	32		GND	2.7 V				"							"	F		"	"
	"	"	33				2.7 V	GND	GND	"							"	G		"	"
	"	"	34				GND	2.7 V	GND	"							"	H		"	"
	"	"	35				GND	GND	2.7 V	"							"	I		"	"
	"	"	36							"		2.7 V	GND				"	J		"	"
	"	"	37							"		GND	2.7 V				"	K		"	"
	I_{IH2}	"	38	7.0 V						"				GND	GND	GND	"	A		100	"
	"	"	39	GND						"				7.0 V	GND	GND	"	B		"	"
	"	"	40	GND						"				GND	7.0 V	GND	"	C		"	"
	"	"	41	GND						"				GND	GND	7.0 V	"	D		"	"
	"	"	42		7.0 V	GND				"							"	E		"	"
	"	"	43		GND	7.0 V				"							"	F		"	"
	"	"	44				7.0 V	GND	GND	"							"	G		"	"
	"	"	45				GND	7.0 V	GND	"							"	H		"	"
	"	"	46				GND	GND	7.0 V	"							"	I		"	"
	"	"	47							"		7.0 V	GND				"	J		"	"
	"	"	48							"		GND	7.0 V				"	K		"	"

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:16Z
Check the source to verify that this is the current version before use.

TABLE III. Group A inspection for device type 01 - Continued.
Terminal conditions (pins not designated may be high ≥ 2.0 V, low ≤ 0.8 V, or open).

Subgroup	Symbol	MIL-STD-883 method	Cases A,B,C,D Case 2 1/ Test no.	1 A	2 E	3 F	4 G	5 H	6 I	7 GND	8 Y	9 J	10 K	11 B	12 C	13 D	14 V_{CC}	Measured terminal	Limits Min	Limits Max	Unit
1 T_C = 25°C	I_{IL}	3009	49	0.5 V						GND				5.5 V	5.5 V	5.5 V	5.5 V	A	2/	2/	mA
		"	50	5.5 V						"				0.5 V	5.5 V	5.5 V	"	B	"	"	"
		"	51	5.5 V						"				5.5 V	5.5 V	0.5 V	"	C	"	"	"
		"	52	5.5 V						"				5.5 V			"	D	"	"	"
		"	53		0.5 V	5.5 V				"							"	E	"	"	"
		"	54		5.5 V	0.5 V				"							"	F	"	"	"
		"	55				0.5 V	5.5 V	5.5 V	"							"	G	"	"	"
		"	56				5.5 V	0.5 V	5.5 V	"							"	H	"	"	"
		"	57				5.5 V	5.5 V	0.5 V	"							"	I	"	"	"
		"	58							"		0.5 V	5.5 V				"	J	"	"	"
		"	59							"		5.5 V	0.5 V				"	K	"	"	"
	I_{OS}	3011	60	GND	GND	GND	GND	GND	GND	"	0.0 V	GND	GND	GND	GND	GND	"	Y	-60	-150	"
	I_{OD}		61							"	2.5 V	5.5 V	5.5 V				4.5 V	"	"		"
	I_{CCH}	3005	62	GND	GND	GND	GND	GND	GND	"		GND	GND	GND	GND	GND	5.5 V	V_{CC}		2.8	"
	I_{CCL}	3005	63	5.5 V	5.5 V	5.5 V	5.5 V	5.5 V	5.5 V	"		5.5 V	5.5 V	5.5 V	5.5 V	5.5 V	5.5 V	V_{CC}		4.7	"
2	Same tests, terminal conditions, and limits as for subgroup 1, except T_C = 125°C and V_C tests are omitted.																				
3	Same tests, terminal conditions, and limits as for subgroup 1, except T_C = -55°C and V_C tests are omittted.																				
9 T_C = 25°C	t_{PHL}	3003 Fig. 4	64	IN	GND	GND	GND	GND	GND	GND	OUT	GND	GND	2.7 V	2.7 V	2.7 V	5.0 V	A to Y	1.5	4.5	ns
		"	65	2.7 V	"	"	"	"	"	"	"	"	"	IN	2.7 V	2.7 V	"	B to Y	"	"	"
		"	66	2.7 V	"	"	"	"	"	"	"	"	"	2.7 V	IN	2.7 V	"	C to Y	"	"	"
		"	67	2.7 V	"	"	"	"	"	"	"	"	"	GND	GND	IN	"	D to Y	"	"	"
		"	68	GND	IN	2.7 V	"	"	"	"	"	"	"	"	"	GND	"	E to Y	"	"	"
		"	69	"	2.7 V	IN	"	"	"	"	"	"	"	"	"	"	"	F to Y	"	"	"
		"	70	"	GND	GND	IN	2.7 V	2.7 V	"	"	"	"	"	"	"	"	G to Y	"	"	"
		"	71	"	"	"	2.7 V	IN	2.7 V	"	"	"	"	"	"	"	"	H to Y	"	"	"
		"	72	"	"	"	2.7 V	2.7 V	IN	"	"	"	"	"	"	"	"	I to Y	"	"	"
		"	73	"	"	"	GND	GND	GND	"	"	IN	2.7 V	"	"	"	"	J to Y	"	"	"
		"	74	"	"	"	"	"	"	"	"	2.7 V	IN	"	"	"	"	K to Y	"	"	"
	t_{PLH}	"	75	IN	"	"	"	"	"	"	"	"	"	2.7 V	2.7 V	2.7 V	"	A to Y	1.5	6.0	"
		"	76	2.7 V	"	"	"	"	"	"	"	"	"	IN	2.7 V	2.7 V	"	B to Y	1.5	6.0	"
		"	77	2.7 V	"	"	"	"	"	"	"	"	"	2.7 V	IN	2.7 V	"	C to Y	1.5	6.0	"
10	t_{PHL}	"		Same tests and terminal conditions as for subgroup 9, except T_C = +125°C.															1.0	6.5	"
	t_{PLH}	"																	1.0	6.5	"
11	Same tests, terminal conditions, and limits as for subgroup 10, except T_C = -55°C.																				

1/ Pins not referenced (i.e., 1, 5, 7, 11, 15, and 17) are N/C.
2/ I_{IL} limits shall be as follows:

Test	Min/Max limits in mA Circuits A	B	C
I_{IL}	-.25/-.60	-.03/-.60	-.03/-.60

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:16Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. The contract or purchase order should specify the following:

a. Complete part number (see 1.2).

b. Requirements for delivery of one copy of the quality conformance inspection data pertinent to the device inspection lot to be supplied with each shipment by the device manufacturer, if applicable.

c. Requirements for certificate of compliance, if applicable.

d. Requirements for notification of change of product or process to the contracting activity in addition to notification to the qualifying activity, if applicable.

e. Requirements for failure analysis (including required test condition of method 5003 of MIL-STD-883), corrective action, and reporting of results, if applicable.

f. Requirements for product assurance options.

g. Requirements for special carriers, lead lengths, or lead forming, if applicable. These requirements shall not affect the part number. Unless otherwise specified, these requirements will not apply to direct purchase by or direct shipment to the Government.

h. Requirements for "JAN" marking.

6.3 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein are defined in MIL-M-38510, MIL-STD-1331, and as follows:

GND - - - - - - - - - - - - - Ground zero voltage potential
V_{IN} - - - - - - - - - - - - - Voltage level at an input terminal
I_{IN} - - - - - - - - - - - - - Current flowing into an input terminal

6.4 Logistic support. Lead materials and finishes (see 3.3) are interchangeable. Unless otherwise specified, microcircuits acquired for Government logistic support will be acquired to device class B (see 1.2.2) and lead finish C (see 3.3). Longer length leads and lead forming shall not affect the part number.

6.5 Substitutability. The cross-reference information below is presented for the convenience of users. Microcircuits covered by this specification will functionally replace the listed generic-industry type. Generic-industry microcircuit types may not have equivalent operational performance characteristics across military temperature ranges or reliability factors equivalent to MIL-M-35810 device types and may have slight physical variations in relation to case size. The presence of this information shall not be deemed as permitting substitution of generic-industry types for MIL-M-35810 types or as a waiver of any of the provisions of MIL-M-38510.

Military device type	Generic-industry type
01	54F64

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:16Z
Check the source to verify that this is the current version before use.

6.6 Manufacturers' designation. Manufacturers' circuits which form a part of this specification are designated with an 'X' as shown in table IV herein.

TABLE IV. Manufacturers' designation.

Device type	Manufacturer		
	Circuit A	Circuit B	Circuit C
	Fairchild Semiconductor	Motorola Inc.	Signetics Corp.
01	X	X	

6.7 Changes from previous issue. Asterisks are not used in this revision to verify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - SH, OS, TD
Air Force - 11, 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Agent:
DLA - ES

Preparing activity:
Air Force - 17

(Project 5962-0739)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:16Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE AIR FORCE

Rome Air Development Center
Griffiss AFB, NY 13441

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 73236 WASHINGTON D. C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE AIR FORCE

Commander
Rome Air Development Center
Attn: RBE-2
Griffiss AFB, NY 13441

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:16Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-M-38510/334B	Microcircuits, Digital, Advanced Schottky TTL, And-Or-Invert Gates

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
Monolithic Silicon	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:16Z
Check the source to verify that this is the current version before use.