MILITARY SPECIFICATION

CRANE, ELECTRO-MECHANICAL, SHIPBOARD

This amendment forms a part of Military Specification MIL-C-17949B(SH), dated 7 April 1980, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

At bottom of page, Beneficial comments statement, line 4: Delete "3112" and substitute "55Z3".

PAGE 4

2.2, under "AMERICAN INSTITUTE OF STEEL CONSTRUCTION (AISC)": Delete "Seventh Edition".

PAGE 7

3.1.9 Add: "Visual inspection shall be done on all welds regardless of other testing performed. Radiographic testing shall be done on at least 10 percent of all full-penetration welds in the primary load path and on 100 percent of critical full-penetration welds. Ultrasonic testing may be substituted for radiographic testing where radiographic testing is not feasible. Liquid penetrant or magnetic particle testing shall be done on at least 10 percent of all fillet welds in the primary load path and on 100 percent of critical fillet welds and totally enclosed or inaccessible welds (which cannot be checked later). Welds in 'primary load path' and 'critical welds' shall be identified on preliminary and final drawings. If there is more than one area which requires weld repair as a result of the inspection, the sample size shall be increased by another 10 percent. This procedure shall be continued until this condition is not exceeded. Minor defects, which can be mechanically removed without infringing on the design thickness, are not considered defects requiring weld repair."

PAGE 12

3.3.7, lines 5 and 6: Delete "Seventh Edition,".

PAGE 16

3.5.2.1: Delete and substitute:

"3.5.2.1 Load capability. Load capability of the gearing shall be computed and rated in accordance with AGMA standard practice, quality 6 or better gear tolerance, and service factor of 1.0 for hoisting and topping drives, 1.25 for rotation drive, and 1.5 for travel drive (type C and D cranes)."

FSC 3950

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:47Z
Check the source to verify that this is the current version before use.

3.5.2.2, line 5: Delete "10" and substitute "100".

PAGE 19

3.5.4.2.2(b): Add "Handsets (in lieu of headsets) may be used on bases of type C and D cranes."

PAGE 24

3.5.5(b), line 1: After "switch" add "(green)".

3.5.5(c), line 5: After "switch", add "(green switch with red placard)".

PAGE 28

3.5.8.6, line 8: After "rollers", add "or hooks".

PAGE 29

3.5.8.9, line 6: After "chocks", add "or stowage pins".

3.5.8.9, line 7: Add "If stowage pins are used, the mating sockets shall be provided."

LAST PAGE

DD 1426, Standardization Document Improvement Proposal: Delete "(SEA 3112)" and substitute "(SEA 55Z3)".

Preparing activity:
Navy - SH
(Project 3950-N247)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:47Z
Check the source to verify that this is the current version before use.