INCH-POUND
MIL-DTL-3786G
SUPPLEMENT 1
21 October 2001

DETAIL SPECIFICATION

SWITCHES, ROTARY (CIRCUIT SELECTOR, LOW-CURRENT CAPACITY),
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-DTL-3786G, dated 21 October 2001.

SPECIFICATION SHEETS

MIL-S-3786/1	-	Switch, Rotary, Open Construction, ½ Ampere, Style SR01. INACTIVE FOR NEW DESIGN
MIL-S-3786/2	-	Switch, Rotary, Open Construction, ½ Ampere, Style SR02. INACTIVE FOR NEW DESIGN
MIL-S-3786/3	-	Switch, Rotary, Open Construction, ½ Ampere, Style SR03. INACTIVE FOR NEW DESIGN
MIL-DTL-3786/4	-	Switch, Rotary. Closed Construction, 2 Amperes, Low Level, Positive Shaft Grounding, Style SR04.
MIL-S-3786/5	-	Switch, Rotary, Open Construction, .200 Ampere, Style SR05. INACTIVE FOR NEW DESIGN
MIL-S-3786/9	-	Switch, Rotary, Open Construction, ½ Ampere, Style SR09. INACTIVE FOR NEW DESIGN
MIL-S-3786/10	-	Switch, Rotary, Open Construction, ½ Ampere, Style SR10. INACTIVE FOR NEW DESIGN
MIL-DTL-3786/13	-	Switch, Rotary, Closed Construction, .500 Ampere, Style SR13.
MIL-S-3786/20	-	Switch, Rotary, Closed Construction, Explosion Proof, .500 Inch Diameter, .200 Ampere, Style SR20
MIL-S-3786/28	-	Switch, Rotary, Closed Construction, 1 Ampere and Low Level, Style SR28. INACTIVE FOR NEW DESIGN
MIL-S-3786/32	-	Switch, Rotary, Open Construction, 1/5 Ampere, Style SR32. INACTIVE FOR NEW DESIGN
MIL-S-3786/35	-	Switch, Rotary, Closed Construction, Explosion Proof, .200 Ampere, Style SR35.
MIL-DTL-3786/36	-	Switch, Rotary, Closed Construction, ¼ Ampere, Style SR36.
MIL-DTL-3786/39	-	Switch, Rotary, Closed Construction, Explosion Proof, .400 Milliamperes, Style SR39.
MIL-S-3786/40	-	Switch, Rotary, Open Construction, .5 Ampere and Low Level, Style SR40. INACTIVE FOR NEW DESIGN
MIL-DTL-3786/41	-	Switch, Rotary, Closed Construction, 0.5 Ampere, Style SR41.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:30Z
Check the source to verify that this is the current version before use.

Application cross-reference

MIL-S-3786/	Approximate diameter in inches	Construction type B D E F N S	Angle of throw in degrees	EMI/RFI shielding	Shaft grounding	28 V dc rating Ampere	Low level capability	Contact type	
								S	NS
1	2.094	N S	18 to 72	No	No	.500	No	Yes	Yes
2	1.594	N S	18 to 90	No	No	.500	No	Yes	Yes
3	1.375	N S	30 to 90	No	No	.500	No	Yes	Yes
4	1.180	E F	30 to 90	No	Yes	2.000	Yes	Yes	Yes
5	1.047	N S	30 to 90	No	No	.200	No	Yes	Yes
9	2.344	N S	15 to 30	No	No	.500	No	Yes	Yes
10	2.328	N S	20 to 40	No	No	.500	No	Yes	Yes
13	.765	E F	30 to 60	No	No	.500	No	Yes	Yes
20	.500	E F	30 to 60	No	No	.200	No	Yes	Yes
28	1.360	E F	30 to 30	Yes	Yes	.250	Yes	Yes	Yes
32	1.828	N S	15 to 45	No	No	.200	No	Yes	Yes
35	.562	F	30	No	No	.200	No	Yes	Yes
36	1.281	F	15 to 22	No	No	.250	No	Yes	Yes
39	.687	E F	36	No	No	.400	No	No	Yes
40	1.750	N S	11 to 30	Yes	Yes	.500	Yes	Yes	Yes
41	.765	E F	30 to 60	No	No	.500	No	Yes	Yes

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:30Z
Check the source to verify that this is the current version before use.

Application cross-reference - Continued.

MIL-S-3786/	Temperature life characteristic					Vibration grade			Shock type		Insulation material			Altitude (maximum) (ft)	Type of termination		Additional features
	B	C	D	E	F	1	2	3	High	Med	C	G	P		SL	PC	
1	B	C	D			1				Med				70,000	SL		Concentric shaft
2	B	C	D					3		Med				70,000	SL		Concentric shaft
3	B	C	D					3		Med				70,000	SL		Concentric shaft
4	B	C						3	High	Med			P	70,000	SL		Concentric shaft
5	B	C	D					3	High	Med	C	G	P	70,000	SL		Concentric shaft
9	B					1			High	Med			P	70,000	SL		Concentric shaft
10	B					1			High	Med			P	70,000	SL		Concentric shaft
13	B	C						3	High	Med			P	70,000	SL		
20	B							3	High	Med			P	70,000	SL		
28		C						3	High	Med			P	70,000	SL		Concentric shaft
32	B							3	High				P	70,000	SL		Concentric shaft
35	B							3	High	Med			P	70,000	SL	PC	Slotted shaft
36		C						3	High	Med			P	70,000	SL		
39		C						3	High	Med			P	70,000	SL	PC	In-line PC mount
40				E				3	High	Med			P	10,000	SL	PC	
41	B	C						3	High	Med			P	70,000	SL		

CONCLUDING MATERIAL

Preparing activity:
DLA - CC

(Project 5930-1729-99)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:30Z
Check the source to verify that this is the current version before use.