INCH-POUND
MIL-DTL-3786H
SUPPLEMENT 1
6 January 2006

DETAIL SPECIFICATION

SWITCHES, ROTARY (CIRCUIT SELECTOR, LOW-CURRENT CAPACITY),
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-DTL-3786H, dated 6 January 2006.

SPECIFICATION SHEETS

MIL-DTL-3786/1 - Switch, Rotary, Open Construction, ½ Ampere, Style SR01.
INACTIVE FOR NEW DESIGN
MIL-DTL-3786/2 - Switch, Rotary, Open Construction, ½ Ampere, Style SR02.
INACTIVE FOR NEW DESIGN
MIL-DTL-3786/3 - Switch, Rotary, Open Construction, ½ Ampere, Style SR03.
INACTIVE FOR NEW DESIGN
MIL-DTL-3786/4 - Switch, Rotary. Closed Construction, 2 Amperes, Low Level, Positive Shaft Grounding, Style SR04.
MIL-DTL-3786/5 - Switch, Rotary, Open Construction, .200 Ampere, Style SR05.
INACTIVE FOR NEW DESIGN
MIL-DTL-3786/9 - Switch, Rotary, Open Construction, ½ Ampere, Style SR09.
INACTIVE FOR NEW DESIGN
MIL-DTL-3786/10 - Switch, Rotary, Open Construction, ½ Ampere, Style SR10.
INACTIVE FOR NEW DESIGN
MIL-DTL-3786/13 - Switch, Rotary, Closed Construction, .500 Ampere, Style SR13.
MIL-DTL-3786/20 - Switch, Rotary, Closed Construction, Explosion Proof, .500 Inch Diameter, .200 Ampere, Style SR20
MIL-DTL -3786/28 - Switch, Rotary, Closed Construction, 1 Ampere and Low Level, Style SR28.
INACTIVE FOR NEW DESIGN
MIL-DTL -3786/32 - Switch, Rotary, Open Construction, 1/5 Ampere, Style SR32.
INACTIVE FOR NEW DESIGN
MIL-DTL -3786/35 - Switch, Rotary, Closed Construction, Explosion Proof, .200 Ampere, Style SR35.
MIL-DTL-3786/36 - Switch, Rotary, Closed Construction, ¼ Ampere, Style SR36.
MIL-DTL-3786/39 - Switch, Rotary, Closed Construction, Explosion Proof, .400 Milliamperes, Style SR39.
MIL-DTL-3786/40 - Switch, Rotary, Open Construction, .5 Ampere and Low Level, Style SR40.
INACTIVE FOR NEW DESIGN
MIL-DTL-3786/41 - Switch, Rotary, Closed Construction, 0.5 Ampere, Style SR41.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:30Z
Check the source to verify that this is the current version before use.

Application cross-reference

MIL-S-3786/	Approximate diameter in inches	Construction type B D E F N S	Angle of throw in degrees	EMI/RFI shielding	Shaft grounding	28 V dc rating Ampere	Low level capability	Contact type	
								S	NS
1	2.094	N S	18 to 72	No	No	.500	No	Yes	Yes
2	1.594	N S	18 to 90	No	No	.500	No	Yes	Yes
3	1.375	N S	30 to 90	No	No	.500	No	Yes	Yes
4	1.180	E F	30 to 90	No	Yes	2.000	Yes	Yes	Yes
5	1.047	N S	30 to 90	No	No	.200	No	Yes	Yes
9	2.344	N S	15 to 30	No	No	.500	No	Yes	Yes
10	2.328	N S	20 to 40	No	No	.500	No	Yes	Yes
13	.765	E F	30 to 60	No	No	.500	No	Yes	Yes
20	.500	E F	30 to 60	No	No	.200	No	Yes	Yes
28	1.360	E F	30 to 30	Yes	Yes	.250	Yes	Yes	Yes
32	1.828	N S	15 to 45	No	No	.200	No	Yes	Yes
35	.562	F	30	No	No	.200	No	Yes	Yes
36	1.281	F	15 to 22	No	No	.250	No	Yes	Yes
39	.687	E F	36	No	No	.400	No	No	Yes
40	1.750	N S	11 to 30	Yes	Yes	.500	Yes	Yes	Yes
41	.765	E F	30 to 60	No	No	.500	No	Yes	Yes

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:30Z
Check the source to verify that this is the current version before use.

Application cross-reference - Continued.

MIL-S-3786/	Temperature life characteristic	Vibration grade	Shock type		Insulation material	Altitude (maximum)	Type of termination		Additional features
	B C D E F	1 2 3	High	Med	C G P	(ft)	SL	PC	
1	B C D	1		Med		70,000	SL		Concentric shaft
2	B C D	3		Med		70,000	SL		Concentric shaft
3	B C D	3		Med		70,000	SL		Concentric shaft
4	B C	3	High	Med	P	70,000	SL		Concentric shaft
5	B C D	3	High	Med	C G P	70,000	SL		Concentric shaft
9	B	1	High	Med	P	70,000	SL		Concentric shaft
10	B	1	High	Med	P	70,000	SL		Concentric shaft
13	B C	3	High	Med	P	70,000	SL		
20	B	3	High	Med	P	70,000	SL		
28	C	3	High	Med	P	70,000	SL		Concentric shaft
32	B	3	High		P	70,000	SL		Concentric shaft
35	B	3	High	Med	P	70,000	SL	PC	Slotted shaft
36	C	3	High	Med	P	70,000	SL		
39	C	3	High	Med	P	70,000	SL	PC	In-line PC mount
40	E	3	High	Med	P	10,000	SL	PC	
41	B C	3	High	Med	P	70,000	SL		

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA – CC

Preparing activity:
DLA - CC

(Project 5930-2006-024)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:30Z
Check the source to verify that this is the current version before use.