INCH-POUND
MIL-DTL-3786K
SUPPLEMENT 1
20 May 2022

DETAIL SPECIFICATION

SWITCHES, ROTARY (CIRCUIT SELECTOR, LOW-CURRENT CAPACITY),
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-DTL-3786K, dated 20 May 2022.

SPECIFICATION SHEETS

MIL-DTL-3786/4 - Switch, Rotary, Closed Construction, 2 Amperes, Low Level, Positive Shaft Grounding, Style SR04.
MIL-DTL-3786/13 - Switch, Rotary, Closed Construction, .500 Ampere, Style SR13.
MIL-DTL-3786/20 - Switch, Rotary, Closed Construction, Explosion Proof, .500 Inch Diameter, .200 Ampere, Style SR20
MIL-DTL-3786/35 - Switch, Rotary, Closed Construction, Explosion Proof, .200 Ampere, Style SR35.
MIL-DTL-3786/36 - Switch, Rotary, Closed Construction, ¼ Ampere, Style SR36.
MIL-DTL-3786/39 - Switch, Rotary, Closed Construction, Explosion Proof, .400 Milliamperes, Style SR39.
MIL-DTL-3786/41 - Switch, Rotary, Closed Construction, 0.5 Ampere, Style SR41.

Application cross-reference

MIL-DTL-3786/	Approximate diameter in inches	Construction type B D E F N S	Angle of throw in degrees	EMI/RFI shielding	Shaft grounding	28 V dc rating Ampere	Low level capability	Contact type	
								S	NS
4	1.180	E F	30 to 90	No	Yes	2.000	Yes	Yes	Yes
13	.765	E F	30 to 60	No	No	.500	No	Yes	Yes
20	.500	E F	30 to 60	No	No	.200	No	Yes	Yes
35	.562	F	30	No	No	.200	No	Yes	Yes
36	1.281	F	15 to 22	No	No	.250	No	Yes	Yes
39	.687	E F	36	No	No	.400	No	No	Yes
41	.765	E F	30 to 60	No	No	.500	No	Yes	Yes

AMSC N/A
FSC 5930
DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:29Z
Check the source to verify that this is the current version before use.

Application cross-reference - continued

MIL-DTL-3786/	Temperature life characteristic					Vibration grade			Shock type		Insulation material			Altitude (maximum) (ft)	Type of termination		Additional features
	B	C	D	E	F	1	2	3	High	Med	C	G	P		SL	PC	
4	B	C						3	High	Med			P	70,000	SL		Concentric shaft
13	B	C						3	High	Med			P	70,000	SL		
20	B							3	High	Med			P	70,000	SL		
35	B							3	High	Med			P	70,000	SL	PC	Slotted shaft
36		C						3	High	Med			P	70,000	SL		
39		C						3	High	Med			P	70,000	SL	PC	In-line PC mount
41	B	C						3	High	Med			P	70,000	SL		

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA – CC

Preparing activity:
DLA - CC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:29Z
Check the source to verify that this is the current version before use.