MILITARY SPECIFICATION SHEET

SWITCH, ROTARY, OPEN CONSTRUCTION,
1/2 AMPERE, STYLE SR10

This amendment forms a part of MIL-S-3786/10D, dated 14 August 1984, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 4

Table II: Delete and substitute:

TABLE II. Electrical loads

Environmental condition	Inductive Load Per MIL-I-81023		Resistive Load	
	Milliamperes	Volts, dc	Milliamperes	Volts
At atmospheric pressure	50	28	500 250 50	28 dc 115 V rms 300 V rms
At reduced barometric pressure	--	--	350 100	28 dc 115 V rms

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - AS, OS
Air Force - 11, 99
DLA - ES

User activities:
Army - AT, AV, ME, SM
Navy - CG, MC
Air Force - 19

Preparing activity:
Air Force - 85

(Project 5930-1430-03)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:34Z
Check the source to verify that this is the current version before use.