MILITARY SPECIFICATION SHEET

SWITCH, ROTARY, CLOSED CONSTRUCTION,
.500 AMPERE, STYLE SR13

This amendment forms a part of MIL-S-3786/13D, dated 27 August 1987, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 5

Table II: Delete and substitute:

TABLE II. Circuit values for life (rotational) test.

Environmental condition	Inductive Loads Per MIL-I-81023		Resistive Loads	
	Milliamperes	Volts, dc	Milliamperes	Volts
At atmospheric pressure and elevated temperature (85°C or 125°C) (25,000 cycles)	50	28	125	28 dc
			75	115 V rms 60 Hz
At reduced barometric pressure (approx. 25°C) (25,000 cycles)	10	28	50	28 dc
			20	115 V rms 60 Hz
At atmospheric pressure and room temperature (approx. 25°C)(10,000 cycles) 1/, 2/	250	28	500	28 dc
			500	115 V rms 60 Hz

1/ Three additional samples shall be run for qualification. Switch to be tested shall be part number M3786/13-0321, -3321, or -5321.

2/ The contact resistance (applicable to ac and dc), after life tests, shall not exceed 50 milliohms.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-16T21:36Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - AS, OS
Air Force - 11, 99
DLA - ES

User activities:
Army - AT, AV, ME, SM
Nvy - CG, MC,
Air Force - 19

Preparing activity:
Air Force - 85

(Project 5930-1430-04)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:36Z
Check the source to verify that this is the current version before use.