INCH-POUND
MIL-DTL-3786/5G
19 November 2004
SUPERSEDING
MIL-S-3786/5F
2 June 1992

DETAIL SPECIFICATION SHEET

SWITCH, ROTARY, OPEN CONSTRUCTION, .200 AMPERE, STYLE SR05

Inactive for new design after 8 March 1999

This specification is approved for use by all Departmentsand Agencies of the Department of Defense.

The complete requirements for acquiring the switch described herein shall consist of this specification and MIL-DTL-3786.





FIGURE 1. Style SR05 switch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:33Z
Check the source to verify that this is the current version before use.



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.015 (0.38 mm).
4. The number of sections is as selected from table III.
5. Nonturn device as shown is not applicable to S construction switches.
6. Inner shaft stop strength 4 inch-pounds. Outer shaft stop strength 15 inch pounds.
7. Shaft-flat angle A° is the angle between a line through the center of the shaft and center of the nonturn device, and another line through the center of the shaft and perpendicular to the shaft flat. For construction S switches, the bushing flat is the nonturn device. Angle A is 270°.
8. Shaft shown in maximum counterclockwise position for switches with stops, and with switch in position number 1 for switches without stops.
9. Front plate design optional provided it falls within the maximum outside diameter of the section dimension referenced.
10. Terminal tabs may be bent to the rear at an angle up to 75° from the plane of the section.
11. Marking plate is included with all switches.

FIGURE 1. Style SR05 switch - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:33Z
Check the source to verify that this is the current version before use.





FIGURE 2. Circuit diagrams - viewed from front or knob end with switch in extreme counterclockwise position.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:33Z
Check the source to verify that this is the current version before use.



NOTE: For switches with fewer than maximum number of positions, short clips will be omitted from clockwise end of rotation.

FIGURE 2. Circuit diagrams - viewed from front or knob end with switch in extreme counterclockwise position - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:33Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figures 1 and 2.

Construction type: See table I.

Angle of throw: See table II.

Mounting hardware: Each switch shall be supplied with two hexagon nuts in accordance with MS25082, and one internal-tooth lockwasher in accordance with NASM35333.

Insulation material: See table II.

Number of poles per deck: See table III.

Number of decks: See table IV.

Number of positions: See table III.

Switching characteristics: See table IV.

Temperature-life characteristics: See table I.

Altitude: Symbol C (70,000 feet).

Rotational-torque: 0.75 inch-pound minimum, 4 inch-pound maximum at room temperature.
0.75 inch-pound minimum, 6 inch-pound maximum at minimum temperature.

Terminal strength (pull): A force of 2 ½ pounds shall be applied to the terminals.

Contact resistance:

At room temperature:

Initial and after vibration and shock: 20 milliohms, maximum.

After moisture-resistance and salt spray: 30 milliohms, maximum.

After initial soak and completion of life test: 40 milliohms, maximum.

Vibration grade: Symbol 3 (10 to 2000 Hz).

Shock type: See table I.

Dielectric withstanding voltage:


At atmospheric pressure: 750 volts, rms.

At reduced barometric pressure: 375 volts, rms.

Life (rotational): The test loads for the applicable circuit conditions shall be as specified in table V. Each of the loads specified for the applicable environmental condition shall be switched by at least one rotor contact of the switch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:33Z
Check the source to verify that this is the current version before use.

Part or Identifying Number (PIN): The military pin shall consists of M3786/5- (four letters selected from tables I through IV) as shown in the following example:



Pin's shall be generated only to identify switches shown on figure 2. Acquiring switches not identified by military pin's shall be in accordance with the ordering data of MIL-DTL-3786.

Application. To conserve material, space, and weight, the following is suggested:

Two-position and three-position switches with 30° angle of throw should be four poles per deck.

Four-position switches with 30° angle of throw should be three poles per deck.

Five- and six-position switches with 30° angle of throw should be two poles per deck.

Two-, three-, four-, and five-position switches with 36° angle of throw should be two poles per deck.

Two-, three-, and four-position switches with 45° angle of throw should be two poles per deck.

Two- and three-position switches with 60° angle of throw should be two poles per deck.

M3786/5-ADEC identifies a rotary switch of construction type N, temperature-life characteristic B, shock types H and M, ceramic or glass bonded mica insulation material, 36 degree angle of throw, 1 pole per deck, 5 positions, 2 decks, and nonshorting switching characteristic.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:33Z
Check the source to verify that this is the current version before use.

TABLE I. Code letter for combination of construction type, temperature-life characteristic, and shock type.

Code letter	Construction type 1/ 2/	Temperature-life characteristic	Shock type
A	N	B	H and M
B	S	B	H and M
C	N	C	H and M
D	S	C	H and M
E	N	D	H and M
F	S	D	H and M
G	N	B	M
H	S	B	M
J	N	C	M
K	S	C	M
L	N	D	M
M	S	D	M

1/ Construction type N identifies an open construction switch, without a sealed shaft and panel seal.

2/ Construction type S is an open construction switch, with a sealed shaft and panel seal.

TABLE II. Code letter for combinations of insulation material and angle of throw.

Code letter	Insulation material	Angle of throw	Code letter	Insulation material	Angle of throw
A	C	30°	J	P	45°
B	G	30°	K	C	60°
C	P	30°	L	G	60°
D	C	36°	M	P	60°
E	G	36°	N	C	90°
F	P	36°	P	G	90°
G	C	45°	Q	P	90°
H	G	45°			

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:33Z
Check the source to verify that this is the current version before use.

TABLE III. Code letters for combination of poles per deck and number of positions.

Code letter	Poles per deck	Number of positions	Code letter	Poles per deck	Number of positions
A	1	C 1/	M	1	12
B	1	2	N	2	2
C	1	3	P	2	3
D	1	4	Q	2	4
E	1	5	R	2	5
F	1	6	S	2	6
G	1	7	T	3	2
H	1	8	U	3	3
J	1	9	V	3	4
K	1	10	W	4	2
L	1	11	X	4	3

1/ Switch is continuous rotation type (no stops), and number of positions is dependent of angle of throw as follows:

Angle of throw	Positions
30°	12
36°	10
45°	8
60°	6
90°	4

TABLE IV. Code letter for combinations of number of decks and switching characteristics.

Code letter	Number of decks	Switching characteristics					
		First deck	Second deck	Third deck	Fourth deck	Fifth deck	Sixth deck
A	1	NS					
B	1	S					
C	2	NS	NS				
D	2	S	S				
E	2	NS	S				
F	3	NS	NS	NS			
G	3	S	S	S			
H	3	NS	NS	S			
J	3	NS	S	S			
K	4	NS	NS	NS	NS		
L	4	S	S	S	S		
M	4	NS	NS	NS	S		
N	4	NS	S	S	S		
P	5	NS	NS	NS	NS	NS	
Q	5	S	S	S	S	S	
R	5	NS	NS	NS	NS	S	
S	5	NS	S	S	S	S	
T	4	NS	NS	S	S		
U	5	NS	NS	NS	S	S	

TABLE IV. Code letter for combinations of number of decks and switching characteristics - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:33Z
Check the source to verify that this is the current version before use.

Code letter	Number of decks	Switching characteristics					
		First deck	Second deck	Third deck	Fourth deck	Fifth deck	Sixth deck
V	5	NS	NS	S	S	S	
W	6	NS	NS	NS	NS	NS	NS
X	6	S	S	S	S	S	S
Y	6	NS	NS	NS	NS	NS	S
Z	6	NS	NS	NS	NS	S	S
1	6	NS	NS	NS	S	S	S
2	6	NS	NS	S	S	S	S
3	6	NS	S	S	S	S	S

TABLE V. Electrical loads.

Environmental condition	Inductive load		Resistive loads	
	Milliamperes	Volts, dc	Milliamperes	Volts, dc
At atmospheric pressure	20	28	200	28 dc
			100	115 rms
At reduced barometric pressure	---	---	100	28 dc
			50	115 rms

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Reference Documents:
MIL-DTL-3786
MS25082
NASM35333

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA – CC

Preparing activity:
DLA - CC

(Project 5930-1873)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:33Z
Check the source to verify that this is the current version before use.