MILITARY SPECIFICATION
CIRCUIT CARD ASSEMBLY: 11741043
COMPUTER-6

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the detail requirement for one type of circuit card assembly. The requirements of this specification together with the general requirements of specification MIL-C-48411 comprise the complete requirements for Computer-6.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on the date of invitation for bids or request, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-C-48411	Circuit Card Assemblies, General Specification for

DRAWINGS

11741043	Circuit Card Assembly, Computer-6

(Copies of specifications, standards, drawings, and publications required by supplier in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Item definition.- This assembly is the sixth of six (6) single ended printed circuit boards consisting of operational amplifiers and vector modules necessary to provide mathematical manipulation of various parameter for the generation of computer flight patterns.

3.1.1 Major component list.- The components of this assembly shall be as specified on the Engineering Parts List (EPL) 11741043.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

3.2 Characteristics.

3.2.1 Performance.- The performance requirements specified herein shall be met on every assembly at standard ambient conditions prior to Government acceptance.

3.2.1.1 Power Supply.- The requirements of 3.2 shall be met with the following power supply voltages.

a. +15 VDC
b. -15 VDC
c. 0 to 10 VDC Variable
d. 0 to 15 VDC Variable

3.2.1.2 Operational Amplifier.- The amplifier shall be capable of algebraically combining three inputs into one output.

3.2.1.3 Vector Modules.- The module shall be capable of computing the absolute value of the sum of the squares of two input vectors.

3.2.2 Environmental.- The assembly shall meet the environmental requirements of specification MIL-C-48411.

3.2.3 Physical Characteristics.- The physical characteristics shall be as specified on drawing 11741043 and the engineering parts list.

3.3 Design and Construction.

3.3.1 Production Drawings.- This assembly shall be fabricated in accordance with the requirements of specification MIL-C-48411, Drawing 11741043 and associated lists.

3.3.2 Standard of Manufacture.- The standard of manufacture shall be those specified in specification MIL-C-48411.

3.3.3 Workmanship.- The workmanship shall be as specified in specification MIL-C-48411.

3.3.4 Preproduction sample.- Preproduction sampling shall be as specified in specification MIL-C-48411.

4. QUALITY ASSURANCE PROVISIONS

4.1 General.

4.1.1 Responsibility for inspection.- The responsibility for inspection shall be as specified in specification MIL-C-48411.

4.1.2 Special test and examination.- The assembly shall undergo first article and control testing in accordance with 4.1.2 of specification MIL-C-48411.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

4.2 Quality conformance inspection.- The assembly shall be inspected and tested in accordance with 4.2 of specification MIL-C-48411.

4.2.1 Test equipment.- (See Figure 1)

4.2.1.1 Power Supply (PS 1).- The power supply shall be 15 ± 0.5 VDC, 100 mA or greater and a ripple of less than 10 m V RMS.

4.2.1.2 Digital Voltmeter.- The digital voltmeter shall have a voltage accuracy and resolution of 0.1 percent or better from zero to 100 VDC. Input inpedance of 10 megohms or greater on all voltage scales.

4.2.1.2 Dummy Loads.- The dummy load shall be 10K ± 0.1%, 1/2 watt resistors.

4.2.2 Performance.- Unless otherwise specified, the performance tests specified herein shall be satisfactorily met at standard ambient conditions. Standard ambient conditions for the purpose of these tests shall be defined as:

a. Temperature between 60°F and 90°F.
b. Barometric pressure between 28 and 32 inches of mercury.
c. Relative Humidity (RH) up to 90%.

4.2.2.1 Power supply.- All the requirements shall be met with the following power supply voltages.

a. +15 ± 0.05 VDC
b. -15 ± 0.05 VDC
c. 0 to 10 ± 0.1 VDC
d. 0 to 15 ± 0.1 VDC

4.2.2.3 Test Set-Up.- The test of the circuit card assembly shall be performed with the inputs and outputs as diagrammed in Figure 1 unless otherwise specified.

4.2.2.4 Operational Amplifier.- When DC voltage are applied to the input pins the corresponding output shall be as shown in Table I.

TABLE I

	INPUT ± 1mVDC			OUTPUT (± 0.10 VDC)
PINS	32	29	26	39
	1	0	0	-1.00
	0	-1	0	+1.00
	0	0	5	0.19
	10	0	0	-10.00

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.




Figure 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

4.2.2.5 Vector Module.- When DC voltages are applied to the input pins of the modules the corresponding output shall be as shown in Table II. If the outputs on Pin 14 and 28 are not zero for zero inputs, obtain same by adjusting R1 and R8 respectively.

TABLE II

	INPUT (± 1mVDC)			OUTPUT (±0.10 VDC)					
PINS	6	12	3	14	8	13	28	34	30
	0	0	0	0.00	0.20	---	0.00	0.20	---
	1	5	5	5.10	5.30	---	7.14	7.34	---
	-5	-5	-5	7.07	7.27	2.83	8.66	8.86	3.37

5. PREPARATION FOR DELIVERY

5.1 Packaging.- Packaging and marking shall be in accordance with the requirements Packaging Data Sheet (PDS), AMC Form 1029, 11741043.

6. NOTES

6.1 The notes specified in the general specification MIL-C-48411 are applied to this specification.

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1240-A621

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.