MILITARY SPECIFICATION

PRIMER, STAB, M45
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-P-60345 (MU), dated 25 May 1965 and is approved by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Add the following preamble underneath the title:

"This specification is approved by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense."

PAGE 1

3.5.1: Delete in its entirety and substitute the following:

"3.5.1 Sensitivity. The primers shall function on the first attempt under an applied energy of 11.85 inch ounces maximum (max.) and shall cause a high order report when fired against a steel disc. The test shall be performed as specified in 4.3.3.1."

PAGE 8

4.3.3.1: Delete last sentence and substitute the following:

"A primer that fails to fire with a high order report shall be classed defective."

4.3.3.2: Delete the last sentence and substitute the following:

"A primer that fails to fire with a high order report shall be classed defective."

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No. 1375-A214

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:30Z
Check the source to verify that this is the current version before use.