MILITARY SPECIFICATION

PARACHUTE PROTECTOR AND OGIVE ASSEMBLY, WHITE STAR

1. SCOPE

1.1 This specification covers the assembling and packing for one type of parachute designated as Parachute Protector and Ogive Assembly, White Star.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-A-2550 — Ammunition and Special Weapons, General Specification for.

MIL-I-45607 — Inspection Equipment, Supply and Maintenance of.

STANDARDS

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes (A BC,-STD-105)

MIL-STD-109 — Quality Assurance Terms and Definitions.

MIL-STD–1168 — Lot Numbering of Ammunition.

MIL-STD-1169 — Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

MIL-STD-1235 — Single and Multi-level Continuous Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS

U. S. ARMY MUNITIONS COMMAND

9206923 — Parachute Protector and Ogive Assembly, White Star.

PUBLICATIONS

ARMY

ET-9206923 — Equipment Tabulation.

FSC 1370

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:36Z
Check the source to verify that this is the current version before use.

(Copies of specifications standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Assembly. The assembly shall comply with all requirements specified on Drawings (dwg.) 9202623 and with all requirements specified in applicable specifications.

3.3 Functioning at cold temperature (– 65 degress F. plus or minus 5 degrees F.). The parachute shall not separate from the assembly, delay opening from time of ejection for more than five (5) seconds, or remain partially open when tested as specified in 4.4.1.

3.4 Workmanship. All assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii. surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents.

3.5 Submission of results of contractor-conducted examinations and tests. The Contractor shall forward copies of the results of any of his examinations or tests to the designated address as required by the contract, the specification, or as requested by the Contracting Officer (see 6.4).

3.6 First article testing. This specification makes provisions for first article testing Submission of first article quantity by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 in order to define terms used herein The provisions of MIL-A-2550 shall apply.

4.1.1 *Submission of product.* At the time the completed lot of product is submitted to the Government for acceptance. the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

(a) A statement that the lot complies with all of the quality assurance provisions specified within this specification

(b) Number of units of product inspected.

(c) Results obtained, by defect code, for all inspections performed.

(d) Drawings. specification number and date, together with an identification and date of changes.

(e) Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.

(f) Number of items in the lot.

(g) Date submitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:36Z
Check the source to verify that this is the current version before use.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.2 *Government verification.* Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings, and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 First article inspection.

4.2.1 *Submission.* The contractor shall submit a first article quantity as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.2.2 (see 6.1). The first article sample shall consist of the following:

(a) Thirty-two (32) parachute protector and ogive assemblies.

All completed assemblies submitted shall have been produced by the contractor (or furnished by a supplier) using the same production processes, procedures and equipment as will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same sources of supply as will be used in regular production. The sample shall be accompanied by certificates of conformance. A first article quantity, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process, material used, drawing, specification or source of supply as to significantly affect product uniformity as determined by the Government. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer.

4.2.2 *Inspections to be performed.* Assemblies will be subjected by the Government to any or all the examinations or tests specified in this specification and any or all requirements of the applicable drawings.

4.2.3 *Rejection.* If any assembly fails to comply with any of the applicable requirements, the first article quantity shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article quantity or portion thereof. Until a first article quantity is accepted, the contractor is in no way authorized by the Government to resume regular production unless otherwise directed by the Contracting Officer.

4.3 Inspection provisions.

4.3.1 *Lot formation.* The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable require-

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:36Z
Check the source to verify that this is the current version before use.

ments. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Changes to the process, specification or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of the lot. The inspetion lot shall comply with MIL-STD-105 and shall be numbered in accordance with MIL-STD-1168. Unless otherwise approved by the Contracting Officer, the inspection lot size of end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period, nor more than the largest monthly quantity contractually scheduled for delivery during the contract period. Inspection lots for components or sub-assemblies, other than the items of delivery, shall be homogeneous and of a size mutually convenient to both the contractor and the Government inspector.

4.3.2 Examination. Sampling plans and procedures for the following classifications of defects shall be in accordance with MIL-STD-105 (ABC-STD-105), except that, inspection for critical defects shall be 100 percent. Contractor's sampling plans, if used, shall be approved by the Government, and shall provide, as a minimum, the protection afforded the Government by the sampling plans in MIL-STD-105. Continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQLs and sampling plans may be applied to the individual characteristics listed using an AQL of 0.40 percent for each Major defect and an AQL of 0.65 percent for each Minor defect except where 100 percent inspection is specified, Equipment necessary for the performance of the inspections listed shall be in acordance with 4.3.4.

4.3.2.1 *Parachute assembly prior to assembling parachute protector and ogive (see* dwg. 9206923).

Categories	Defects	Method of inspection	Defect code (see 6.2)
Critical: None defined			
Major	AQL 100 Percent		
101.	Tears or holes in parachute	Visual	(01001)
102.	Shroud lines not secure to parachute	Visual	(01002)
103.	Shroud lines improperly tied to coupling	Visual	(01003)
104.	Coupling not secure to chain	Visual	(01004)
105.	Shrouds twisted	Visual	(01005)
Minor	AQL 0.65 Percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	(01006)

4.3.2.2 *Parachute protector and ogive assembly (See Dwg. 9206923)* .

Categories	Defects	Method of inspection	Defect Code
Critical: None defined			
Major	AQL 0.40 Percent		
101	Outside diameter	Gage	(02001)
Minor	AQL 1.00 Percent		
201.	Tape missing	Visual	(02002)
202.	Evidence of poor workmanship (see 3 4)	Visual	(02003)

4.3.3 *Testing.*

4.3.3.1 *Functioning at cold temperature (—65 degrees F. plus or minus 5 degrees F.). (see paragraph 3.3). major defect, code No. (03001).* Fifty (50) parachute protector and ogive assemblies shall be selected from each lot and subjected to this test. If two (2) or more assemblies fail to comply with the applicable requirement, the lot shall be rejected The test shall be performed as specified in

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:36Z
Check the source to verify that this is the current version before use.

4.4.1 using equipment in accordance with 4.3.4.

4.3.4 *Inspection equipment.* Equipment tabulation (ET) number 9206923 and equipment lists (ELs) referenced thereon identify the Inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3.

4.3.4.1 *Government rights to documentation.* Inspect Ion equipment drawings and lists provided and revised in accordance with the requirements of this specification may be used by DOD activities for design, procurement, manufacture, testing, evacuation, production and receiving Inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey, and whenever inspection equipment drawings are needed.

4.3.4.2 *Supply and maintenance.* Supply and maintenance of the equipment listed on the ELs shall be in accordance with MIL-I-45607.

4.3.4.3 *Government use of contractor's inspection and test equipment.* The contractor shall, when required by the Government, make available all inspection and test equipment necessary for determining conformance with the contract requirements. Personnel for operating the equipment, and verification of its accuracy shall be supplied by the contractor for the performance of examination or test by the Government.

4.4 Test methods and procedures.

4.4.1 Functioning at cold temperature (—65 *degrees F plus or minus 5 degrees F.).* The parachute protector and ogive assemblies with tape removed shall be assembled to complete white star cartridges packed in thier regular shipping containers and conditioned for a minimum of 16 hours at – 65 degrees F. plus or minus 5 degrees F. The cartridges shall be taken from the conditioning chamber, removed from the packing containers and fired from an approved mount at 90 degrees quantrant elevation before the temperature of the cartridge changes. Observation shall be made for the requirements of Paragraph 3.3.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging.

5.1.1 *Level C* — Minimum military pack-(age. See 5.2.1.

5.2 Packing.

5.2.1 *Level C* — Minimum military pack. The parachute protector and ogive assembly shall be packed for shipment in accordance with MIL-STD-1169.

5.3 Marking. Marking of the carton shall be in accordance with MIL-STD-1169.

5.4 Shipping. When shipments from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Ordering data. Procurement documents shall specify the following:

(a) Title, number and date of this specification.

(b) Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

(c) Provisions for submission of first article samples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:36Z
Check the source to verify that this is the current version before use.

6.2 Inspection code numbers. The five-digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment. The contractor shall design inspection equipment as required by the referenced equipment lists (EL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 *Equipment lists.* Equipment lists indicate the availability of inspection equipment designs by showing in the "part number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings of Federal stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the "Part number" column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 *Equipment list codes.* The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD — Contractor design on controlled contractor format and / or commercial equipment.

MU — Army design, mandatory for use.

6.3.3 *Army designs.* Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of Inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and nonmandatory (indicated by drawing or Federal stock number). When an equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with nonmandatory designs, and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor-prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 *Contractor designs.* Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions. materials, finishes, notes, and operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, category E, form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high-contrast reproductions. Contractors shall submit one copy of final designs as a rolled set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 *Submission of contractor designs.* All submitted designs shall reference the applicable five-digit code number contained in section 4 of this specification. Unless otherwise specified on the EL, all designs of equipment

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:36Z
Check the source to verify that this is the current version before use.

for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND3. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract. Submission shall be as directed by the Contracting Officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished, normally, within one month after receipt.

6.4 Submission of results of contractor-conducted examinations and tests. Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND3.

Custodian:

Army—MU

Preparing activity:

Army-MU

Project No. FSC 1370-A-233

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:36Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:36Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
Picatinny Arsenal
Dover, New Jersey 07801

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

COMMANDING OFFICER
United States Army
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:36Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION | CITY AND STATE

CONTRACT NO | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT

$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:36Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:36Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:36Z
Check the source to verify that this is the current version before use.