MIL-T-507670(MU)
13 August 1971

MILITARY SPECIFICATION

TELESCOPE, ELBOW: 11737695

1. SCOPE

1.1 This specification covers one type of non-maintainable four power fixed focus elbow telescope.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this Specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-O-13830	Optical Components for Fire Control Instruments; General Specification Governing the Manufacture, Assembly, and Inspection of
MIL-F-13926	Fire Control Materiel, General Specification Governing the Manufacture and Inspection of
MIL-P-14232	Parts, Equipment and Tools for Army Materiel, Packaging and Packing of
MIL-I-45607	Inspection Equipment, Acquisition, Maintenance and Disposition of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	Quality Assurance Terms and Definitions

DRAWINGS

U.S. Army, Frankford Arsenal

F8565556	Pressure Tester, Two-Station
11737695	Telescope, Elbow

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

PACKAGING DATA SHEETS

11737695 Packaging of Telescope, Elbow 11737695

(Copies of specifications, standards, drawings and packaging data sheets required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Fabrication. - The telescope shall be manufactured in accordance with the applicable drawing listed in 2.1.

3.2 General specification. - The contractor shall be responsible for compliance with the following requirements of MIL-F-13926.

a. Order of precedence
b. Dimensions and tolerances
c. Inorganic protective surface finishes
d. Part identification and marking

3.3 Temperature conditions. - The requirements of this specification shall be met with the telescope thermally stabilized at an ambient temperature of between 60 and 90° Fahrenheit (F) unless otherwise specified in the requirement paragraphs.

3.4 Workmanship. - The workmanship requirements of MIL-F-13926 shall be met. The exterior protective surface finishes shall be free of any defects which effect their protective qualities or appearances. Optical surfaces shall be clean and free of any scratches or blemishes which may effect their optical qualities and shall meet the requirements of 3.5.4.

3.5 Environmental. - Any telescope subjected to any or all of the requirements of 3.5.1 to 3.5.3.1 inclusive shall subsequently meet the requirements of 3.5.4 to 3.6.7 inclusive, unless otherwise specified.

3.5.1 Storage temperature. - The telescope shall show no evidence of physical failure such as cement separation, glass breakage or casting failure after having been exposed and thermally stabilized at ambient temperatures of -80° and +l60°F (see 3.5.3.1).

3.5.2 Vibration. - The telescope shall be positioned with the line of sight through the eyepiece and objective tube in a horizontal plane and the telescope supported at the 0.8435 inch diameter of the objective tube. The telescope shall be vibrated at a constant frequency of 30 cycles per second with an amplitude of 1/16 inch (1/8 inch total excursion) for a period of 5 minutes ± 15 seconds.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T20:36Z
Check the source to verify that this is the current version before use.

3.5.3 Sealing. - The telescope shall show no evidence of leakage in excess of 0.2 psig when subjected to an internal pressure of 5 ± 0.10 psig for a period of 2 hours using dry nitrogen having a dew point at least as low as -25°F.

3.5.3.1 Condensation (low temperature). - When view through the eyepiece and objective ends of the telescope, there shall be no evidence of condensation at room temperature (60° to 90°F) immediately upon tehermal stabilization, subsequent to being subjected to the -80°F and prior to the +16°F requirement of 3.5.1.

3.5.4 Cleanliness. - The telescope shall meet the cleanliness requirements of MIL-O-13830. When viewed through the eyepiece, dirt shall not exceed the following limitations of dirt, quantity, and size (see 6.33-size equivalent).

a. Inner zone (100 mils diameter). - The maximum size of any one particle of dirt or foreign material shall not exceed the area equivalent to a size 5 dig. There shall be no more than 6 particles of dirt. Three particles may be as large as a size 5 dig. Three particles shall not exceed a size 1 dig. Any particles smaller than a size 1/4 dig shall not be counted.

b. Outer zone (limited to clear aperture of reticle). - The maximum size of any one particle of dirt or foreign material shall not exceed the area equivalent to a size 10 dig. Three paricles may be as large as a size 10 dig. Smaller sizes may be more in number, but their combined area shall not exceed that of 3 size 10 digs, which is maximum dirt permitted. Any particles smaller than a size 1/4 dig shall not be counted.

c. Dirt separation. - The separation between each dirt particle or foreign matter shall be at least 10 mils for both zones.

d. Glass surfaces. - All glass surfaces shall be free of condensation, or stains resulting from condensation, when viewed through the objective and eyepiece ends of the telescope.

3.6 Accuracy.

3.6.1 Collimation. - The optical axis of the telescope shall be in coincidence with the geometric axis within 0.50 mil when the telescope is rotated 3200 mils (90° to the left and 90° to the right from a vertical position of the eyepiece) about the geometric axis as defined by the exterior mounting surface of the objective tube of the telescope.

3.6.2 Parallax. - With the parallax shield removed, parallax at the optical axis shall not exceed 0.2 mils when viewing targets between 300 meters and 1000 meters.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

3.6.3 Resolution. - The resolution on the optical axis shall be 15 seconds of arc or less.

3.6.4 Parallelism of reticle and image. - The vertical reticle line shall be parallel to the image of a plumb line within 30 minutes of arc, when each of the 3 indices (90° apart) are in position for coincidence with a vertical plane index through the geometric axis of the telescope's objective tube.

3.6.5 Reticle accuracy. - The angular separation for the O to 50 mil span in each of the 4 quadrants of the reticle shall each be 50 mils ± 1.5 mils

3.6.6 Eyepiece focus. - The eyepiece focus of the reticle shall be set between minus 0.75 and minus 1.0 diopter.

3.6.7 Illumination. - The telescope shall meet the "Illuminated Re-titles" requirement of MIL-0-13830. With the reticle illuminated by Instrument Light M53El or equivalent, the reticle markings shall appear clearly defined when observed in a darkened area.

4. QUALIty ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise Except as otherwise specified, the supplier may utilize his own facilities or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisions. - The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions of this specification. of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 First article (initial production) approval. - The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of 3 telescopes plus 3 each of all items covered by SQAP. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.2.1 Government testing. - When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, includingt certificates of conformance for materials.

4.2.2 Contractor testing. - When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection.

4.3 Inspection provisions.

4.3.1 Submission of product. - Unless otherwise specified by the contracting officer, inspection lot size, lot formation and presentation of lots shall be in accordance with "Submission of Product" provisions of MIL-STD-105.

4.3.2 Examination and tests.

4.3.2.1 Components and subassemblies. - All components and subassemblies shall be inspected in accordance with the inspection provisions contained in Supplementary Quality Assurance Provisions (SQAP) listed in the technical data package (TDP0. In the absence of SQAP'S, the applicable Quality Assurance Provisions of MIL-F-13926 shall apply. Examination and tests related to Section 3 herein, shall be performed on asingle defect (individual characteristic) basis in accordance with MIL-STD-105 and the sampling plans specified in Tables I, II and III herein. Examination and tests for packaging, packing, and marking shall be in accordance with MIL-P-14232 and Section 5 herein. The tabulated classification of de3fects in Tables I, II and III shall constitute the minimum inspection to be performed by the supplier after first article approval and prior to Government acceptance or rejection by item or lot.

TABLE I - CLASSIFICATION OF DEFECTS

CLASS		REQUIREMENT	TEST PROCEDURE
CRITICAL:	NONE		
MAJOR:	AQL 0.657. Defective		
101.	Vibration	3.5.2	4.6.2
102.	Sealing	3.5.3	4.6.3
103.	Cleanliness	3.5.4	4.6.4
104.	Resolution	3.6.3	4.6.5
105.	Collimation	3.6.1	4.6.6.1
106.	Parallax	3.6.2	4.6.6.2
107.	Parallelism of reticle and image	3.6.4	4.6.6.3

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T20:36Z
Check the source to verify that this is the currentversion before use.

108.	Reticle accuracy	3.6.5	4.6.6.4
109.	Eyepiece focus	3.6.6	4.6.6.5
110.	Illumination	3.6.7	4.6.7
111.	Workmanship	3.4	4.6.8

MINOR: NONE

NOTE: The tests in Table I shall be conducted at a temperature between 60° and 90°F.

4.3.3 Acceptance and rejection. - Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-sTD-105.

Special sampling.

4.4.1 General. - One telescope shall be selected at random as a special sampling from each 100 produced. The sample shall meet the requirements and tests in Table II.

TABLE II

NO.	CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
301.	Fabrication	3.1	Applicable Drawing ing - Visual
302.	General specification	3.2	MIL-F-13926, Visual

NOTE: The tests in Table II shall be conducted at a temperature between 60° and 90°F.

4.4.2 Environmental. - Three telescopes shall be selected at random as samples from each 50 produced, or from each month's production, whichever occure first. Each sample shall meet the requirements and tests in Table III and shall then meet the requirements and tests in Table I.

TABLE III

No.	CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
303.	Storage temperature (-80°F)	3.5.l	4.6.1
304.	Condensation (low temperature -80°F)	3.5.1, 3.5.3.1	4.6.1, 4.6.1.1
305.	Storage temperature (+160°F)	3.5.1	4.6.1.2

4.4.3 Failure of sample. - Should any one item of a special sampling fail to meet the specified test requirements, acceptance of the represented inspection lot shall be suspended by the Government until necessary corrections have been made by the Contractor and the resubmitted items have been approved (see 4.3.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.5 Inspectin equipment. - Except as otherwise provided for by the contract, the contractor shall supply and maintain inspection equipment in accordance with the applicable requirements of MIL-1-45607.

4.5.1 Government furnished inspection equipment. - Where the contract provides for Government furnished test equipment, supply and maintenance of test equipment shall be in accordance with applicable requirements specified in MIL-I-45607.

4.5.2 Contractor furnished inspection equipment.

4.5.2.1 Government design. - All inspection equipment specified by drawing number in specifications or SQAP'S forming a part of the contract shall be supplied by the contractor in accordance with technical data included in the technical data package list.

4.5.2.2 Contractor design. - The contrator shall design and supply inspection equipment compatible with the "Test Methods and Procedures" specified in 4.6 of this specification and with the component inspection procedures specified in "Examination" and "Test Facilities" requirements of MIL-F-13926. Since tolerance of Lest equipment is normally considered to be within 10% of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. thus, concept, construction, materials, dimensions and tolerances used in the design of test equipment shall he so selected and controlled as to insure that the test equipment will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit, permit positive rejection when non-conforming. Construction shall be such as to facilitate routine calibration of test equipment.

4.5.2.3 Inspection equipment design requirements.

4.5.2.3.1 Accuracy. - Special testing equipment to test the telescope shall conform to the following requirements:

a. Leveling of special testing equipment. - The qualified surface of the testing equipment utilized for securing a precision "V" block with a calibrated vertical index, a clamping devuce and a target projector collimator shall be crossleveled within 10 seconds. provisions shall be made on the testing equipment for locating and securing the "V" block utilized to assure accurate and repeatable positioning of the telescope. A precision level shall be used to align the "V" block within 10 seconds.

b. "V" block with vertical index and clamping device. - The "V" block and clamping device shall be capable of securing the exterior mounting surface of the objective tube of the telescope. the clamping device shall provide shall provide sufficient tension to permit the telescope to be rotated

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

through the excursion specified in 3.6.1 without slippage or rotation under its own weight, and for establishing coincidence of the 3 indices of the telescope with respect to the calibrated vertical index and geometric axis of the telescope's tube as specified in 3.6.4.

c. Targer Projector collimator. - The target projector collimator shall have a clear aperture of at least 2 inches. The target reticle of the projector collimator shall contain a 0.50 mil diameter circle at the intersecting point of the horizontal and vertical reticle lines to determine conformance with collimation, as specified in 3.6.1. Tolerance marks shall also be incorporated on both sides of the vertical reticle line to determine conformance to parallelism of reticle and image, as specified in 3.6.4 Unless otherwise specified, the target projector collimator shall be set at infinity focus. The zero line of sight of the target collimator shall be set with the line of sight in the same horizontal (level) plane of the geometric optical axis (the nominal line of sight of the telescope) within 10 seconds. The vertical reticle line of the collimator shall be adjusted plumb.

d. Collimating telescope. - A calibrated collimating telescope of at least 3 power (3X) containing a horizontal and vertical reticle line shall be utilized for alignment of the "V" block with respect to the geometric optical axis of the target collimator. Position the telescope in the "V" block with the vertical reticle line of the telescope adjusted plumb when in the test position. While observing through the telescope, establish coincidence of the intersecting point (horizontal and vertical reticle lines) of the telescope with respect to the intersecting point (horizontal and vertical reticle lines) of the target image. The telescope shall then be rotated 3200 mils (90° to the left and 90° to the right) from the established position ahove to determine repeatability of the testing equipment prior to performing any accuracy tests of the telescope assembly.

4.5.2.3.2 Sealing. - Special testing equipment to test sealing of the telescope shall conform to the internal pressure test requirements of Drawing F8454445, Pressure Tester - Two Station.

4.6 Test methods and procedures.

4.6.1 Storage temperature (-80°F). - The testing equipment utilized in this test shall be in accordance with the "Test Facilities" requirements of MIL-F-13926 and the conditions of 3.5.l. The telescope shall be placed in the test chamber and the temperature of the chamber reduced gradually (see NOTE) tpo -80°F. The telescope shall remain at this temperature for a minimum of 2 hours. At the completion of this 2 hour period, the temperature of the test chamber shall be gradually raised to room temperature (+60° to +90°F). At the end of a 1 hour period the telescope shall be removed from the test chamber and subjected to test in 4.6.1.1. Upon completion of the test in 4.6.1.1 the telescope shall be subjected to a visual and tactile examination for evidence of physical failure. The telescope shall meet the requirements of 3.5.1. The telescope shall then be subjected to the test in 4.6.1.2.

NOTE: The rate of temperature change in the test chamber shall not exceed 20 degrees per hour throughout the temperature cycling tests in 4.6.1 and 4.6.1.2.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:36Z
Check the source to verify that this is the current version before use.

4.6.1.1 Condensation (low temperature). - Subsequent ot low temperature and upon stabilization at room temperature (60° to 90°F), the telescope shall be thoroughly examined as specified in 3.5.3.1. The requirements of 3.5.3.1 shall be met.

4.6.1.2 Storage temperature (+160°F). - The testing equipmetn utilized in this test shall conform to the requirements of 4.6.1. The telescope shall be placed in the test chamber and the temperature of the chamber raised gradually to +160°F. The telescope shall remain at this temperature for a minimum of 2 hours. At the completion of this 2 hour period, the temperature of the test chamber shall be gradually reduced to room temperature. The telescope shall be removed from the test chamber and subjected to a visual and tactile examination for physical damage. The telescope shall meet the requirements of 3.5.1.

4.6.2 Vibration. - Standard vibrating equipment capable of providing the amplitude and frequency as specified in 3.5.2 shall be utilized for the vibration test. Unless otherwise specified, the test equipment shall be in accordance with MIL-F-13926. The telescope shall be vibrated in the direction and conditions specified in 3.5.2. Upon completion of the vibration test, the telescope shall be subjected to the visual examination specified in 4.6.2.1.

4.6.2.1 Examination. - Subsequent to vibration, the telescope shall be thoroughly examined for physical defects prior to being subjected to the remaining tests specified herein. A visual examination shall be conducted externally and internally for missing or damaged parts, with particular attention to lenses, prism and reticle. Any one of the possible defects defined above shall be cause to consider the telescope defective. Telescopes which have passed the above examinations shall be subjected to the tests specified in 4.6.3 through 4.6.8 inclusive.

4.6.3 Sealing. - Internal pressurizing of the telescope to test sealing shall be performed using dry nitrogen gas having a dew point at least as low as -25°F and special testing equipment conforming to 4.5.2.3.2. The telescope shall be pressurized to the requirements of 3.5.3 in accordance with the procedure for internal pressure testing of Drawing F8565556. Maintain the applied pressure for the time period specified. Any evidence of leakage in the telescope at the enc of the 2 hour time period shall not exceed the tolerance specified in 3.5.3, as measured on the pressure gauge of the testing equipment. Upon satisfactory completion of this test, disconnect the pressure tester adapter from the telescope. The body sealing screw shall be assembled to the telescope immediately so as to maintain a nitrogenized atmosphere within the telescope.

Source: https://assist.dla.mil -- Downloaded: 2026t0-22T20:36Z
Check the source to verify that this is the currentversion before use.

4.6.4 Cleanliness. - The optical surfaces of the telescope shall be inspected for cleanliness in accordance with MIL-O-13830. Inspection for dirt particles shall be made through the eyepiece by viewing a uniformly illuminated field having a brightness of approximately 300 foot candles. All dirt size evaluations shall take into account the viewing magnification. Inspection far condensates shall be made with the unaided eye viewing through the objective and eyepiece ends of the telescope by the shadowing technique. Cleanliness shall conform to the requirements of 3.5.4.

4.6.5 Resolution. - Position the telescope on a holding device capable of accepting the exterior mounting surface of the objective tube of the telescope. Perform this test utilizing an observation telescope with a magnification of at least 3 power (3X) and a resolving power chart on a wall target. The test methods and procedures shall be in compliance with the "Resolution Test" specified in MIL-O-13830 and the resolving power chart shall contain 4 line sets as shown in Figure 1 therein. The focus of the observation telescope shall be established at one best focus setting for viewing of the detectable line structure and proper line count of the resolution target. Resolution of the telescope optical system shall meet the requirements specified in 3.6.3.

4.6.6 Accuracy. - Perform the following tests with the telescope positioned on special testing equipment conforming to 4.5.2.3.l.

4.6.6.1 Collimation. - Position the telescope with the eyepiece in a vertical position. Observe through the eyepiece of the telescope. The intersectingpoint of the telescope reticle centerlines shall be in coincidence with respect to the intersecting point of the target reticle lines within the tolerance specified in 3.6.1 as measured on the 0.50 mil diameter circle of the target reticle. Repeat the collimation test procedure above shen the telescope is rotated 90° to the left and 90° to the right of the original test position. The intersecting point of the telescope reticle shall be within the 0.50 mil diameter circle of the target reticle at both positions to insure overall compliance with 3.6.1.

4.6.6.2 Parallax. - Parallax requirements shall be met when the target image is adjusted as specified in 3,6.2. Parallax will be recognized by any apparent displacement of the telescope reticle lines with respect to the center target image lines when the observer’s head is moved from side to side or up and down. Patallax shall be measured at the optical axis (center of the reticle pattern). Displacement between the telescope reticle and target image shall not exceed the tolerance specified in 3.6.2.

4.6.6.3 Parallelism of reticle and image. - Perform this test in conjunction with the test in 4.6.6.1 when each of the indices as specified in 3.6.4 are in position and coincident with respect to the index of the "V" block. One extremity of the telescope vertical reticle shall be coincident to the vertical target image line. The reticle line shall be parallel to the target image line within the tolerance specified in 3.6.4, as measured at the other extremity of the telescope reticle line with respect to the target image tolerance marks.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.6.6.4 Reticle accuracy. - This test shall be conducted in accordance with test for reticle scale spacings of MIL-O-13830. The total angular subtense of the reticle graduations shall meet the requirements specified in 3.6.5 as measured on the target image.

4.6.6.5 Eyepiece focus. - A calibrated dioptometer with a magnification of at least 3 power (3X) and a diopter measuring range of zero to minus one diopter shall be utilized for measuring the accuracy of the eyepieCe focus of the telescope reticle. Set the dioptometer objective diopter scale to zero and adjust the dioptometer eyepiece for best focus of the dioptometer reticle. Position the dioptometer at the eyepiece of the telescope. Observe through the dioptometer, obtain best focus of the telescope reticle by adjustment of the dioptometer objective diopter scale. The telescope reticle shall be in best focus within the tolerance specified in 3.6.6, as measured on the dioptometer objective diopter scale.

4.6.7 Illumination. - A device consisting of a .19 ampere lamP energized by 3.0 volts shall be used to illuminate the telescope reticle. The illuminated etchings of the reticle pattern shall be clearly defined when visually examined against a darkened background. Should the brightness of a reticle defect be greater than the brightness of a reticle line, the defect shall be cause for rejection.

4.6.8 Workmanship. - The telescope shall be subjected to a visual examination and shall meet the requirements specified in 3.4.

5. PREPARATION FOR DELIVERY

5.1 Packaging packing and marking. - Packaging, packing and marking of the Telescope. Elbow: 11737695 shall be in accordance with Packaging Data Sheet 11737695. The level of prelection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use. - The Telescope, Elbow: 11737695 is used with the AN/TPS-58 Radar System for azimuth alignment of radar.

6.2 Ordering data. - Procurement documents should specify the following:

Title, number and date of this specification
b. Selection of applicable levels of preservation, packaging and packing
Applicable stock numbers
d. Applicable packaging data sheet (see 5.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

6.3 Dirt size equivalent. - For comparison purposes, the maximum width of a reticle line is equal to a 1.5 dig size.

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1240-A320

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22 R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
   ☐ YES ☐ NO (If "yes", in what way?)

4. REMARKS (*Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.*)

NAME AND ACTIVITY (*Typed name and activity - Optional*) | DATE

DD FORM 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
Department of the Army

OFFICIAL BUSINESS

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-T1000
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.