MIL-W-60197(MU)
AMENDMENT 2
18 August 1967
SUPERSEDING
AMENDMENT 1
21 April 1967

MILITARY SPECIFICATION

WRITE AMPLIFIER: 10526585

This amendment forms a part of Military Specification MIL-W-60197(MU), dated 24 February 1965.

Paragraph 3.1: Change Drawing Number "F10526858" to F10526585".

Paragraph 3.4.1: Delete Pin "32B".

Paragraph 3.4.1.1(g): Change "2 Milliamperes" to "4 Milliamperes".

Paragraph 3.4.4: Change "CR62" to "CR63".

Paragraph 4.4.1.1: Delete Item 9 and change Items 1 through 8 from "dc to 500." to "dc to 500 Kc." Items 10 to 11 from "dc to 20". to "dc to 20 Kc." Item 13, last line: Change "less than 0.4 milli microseconds" to "less than 0.4 microseconds".

Paragraph 4.5.1.1, Line 5 after "vibration": Delete the letter "c".

Paragraph 4.5.1.3.2: Delete in its entirety and substitute:

"4.5.1.3.2 Operating.- This test shall be conducted in accordance with the humidity test defined in Procedure III of MIL-F-13926, except that the humidity shall be maintained at 92 to 97 percent for the 24-hour period, and the test shall cease at the end of that period (Method 106 of MIL-STD-202 shall be excluded). Throughout the test period, the board shall be capable of performing the test of 4.5.3.3. In order to demonstrate this capability, the tests of 4.5.3.3 shall be performed a minimum of once each 6 hours of the 24-hour period. The final test shall be conducted during the final portion of the 24-hour period. Between tests, the board shall be electrically energized as described in 4.5.2.1".

Paragraph 4.5.1.4: Delete in its entirety and substitute:

"4.5.1.4 Salt spray.- This test shall be conducted in accordance with the salt spray test defined in Method 101, Condition B of MIL-STD-202 using a 5 percent salt solution. At the end of the exposure period, salt deposits shall be removed from the board by a gentle wash, not exceeding 30 minutes, in running water not warmer than 100°F, using a soft-hair brush or plastic-bristle brush. The board shall then be air dried in a controlled environment at 72°F ± 5°F and a relative humidity of 30 to 50

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:17Z
Check the source to verify that this is the current version before use.

percent for a period of 24 hours. The board shall be inspected visually for any physical damage, then tested in accordance with 4.5.3.3. The board shall subsequently be inspected as specified in 4.5.1.5, prior to determining compliance with 3.4 as required by 3.3.6."

Paragraph 4.5.2.1: Change Pin "32B" to "23A".

Paragraph 4.5.2.1.1: Delete Pin "32B".

Paragraph 4.5.3.1: Change Pin "13B" to "15A".

Item (a): Shall read, "The voltage from Pin 17A to Pin 52B shall be more positive than minus 0.3 volts."

Item (c): Change to read _ _ _ _ Pin 11B to Pin 33A shall _ _ _ _.

Item (d): Shall read, "The voltage at Pin 1B to Pin 33A shall be equal to or less than plus 12 volts."

Item (e): Change to read _ _ _ _ Pin 25A to Pin 33A shall _ _ _ _.

Item (f): Change to read _ _ _ _ Pin 22A to Pin 33A shall _ _ _ _.

Item (g): Change "64 ± 2" to "64 ± 4".

Add Item (i) "Remove the reset voltage from Pin 15A."

Paragraph 4.5.3.2:

Item (a) shall read, "_ _ _ _ shall be more positive than minus 0.3 volts."

Item (c) shall read "_ _ _ _ Pin 22B to 33A shall be _ _ _ _."

Item (d) shall read "_ _ _ _ Pin 18B to Pin 33A shall be equal to or less than plus 12 volts."

Item (e) shall read "_ _ _ _ Pin 4B to Pin 33A shall be _ _ _ _."

Item (f) shall read "_ _ _ _ Pin 11B to Pin 33A shall be _ _ _ _."

Item (g): Change "64 ± 2" to "64 ± 4".

Add Item (i): "Remove the reset voltage from Pin 13B."

Paragraph 4.5.3.3.1.1: Change "0.5 ± 0.75 volt' to "Minus 0.5 ± 0.75 volts."

Paragraph 4.5.3.3.2.1: Delete: Third sentence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:17Z
Check the source to verify that this is the current version before use.

Paragraph 4.5.4: Change Pin "28B"to "29A" and add "36A" after Pin "34B".

Table V: Delete Pins "29A and 36A".

Change "32B" to "23A".

Add pins "5A and 24A" to Write Amplifier 1 column and Pins "40B and 62B: to Write Amplifier 2 column.

Paragraph 4.5.5.1: Change Pin "36B" to "63B".

Paragraph 4.5.6.1.1: Delete in its entirety and substitute:

"4.5.6.1.1 Forward voltage drop.- The forward voltage drop shall be tested by the following procedure to determine compliance with 3.4.4.1.

(a) Connect the minus 18 volt power supply to Pin 50B. The voltage at the pin in Column A with respect to the pin in Column B shall be more positive than minus 0.6 volt. Connect the power supply ground return in turn to the pin in Column B.

Column A	Column B
10B	5A
10B	14A
19B	24A
19B	14A

After the last measurement is complete, remove the power supply ground return from Pin 14A. Remove the minus 18 volt power supply from Pin 50B.

(b) Connect the minus 18 volt power supply to Pin 49B. The voltage at the pin in Column A with respect to the pin in Column B shall be as shown in Column C. Connect the power supply ground return in turn to the pin in Column B.

Column A	Column B	Column C
8B	2B	$\geq$ Minus 0.6
8B	33B	$\geq$ Minus 0.8
8B	14B	$\geq$ Minus 0.6
20B	23B	$\geq$ Minus 0.6
20B	26B	$\geq$ Minus 0.8
20B	14A	$\geq$ Minus 0.6

After the last measurement is complete, remove the ground return from 14A. Remove the minus 18 volt power supply from Pin 49B.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:17Z
Check the source to verify that this is the current version before use.

(c) Connect the minus 18 volt power supply thru a 68 K ohm 1/4 W 5% resistor to Pin 14A. Measure the voltage at Pin 14A with respect to the grounded pin. The voltage shall be more positive than minus 0.6 volts. Connect the power supply ground return in turn to Pin 20A and Pin 22A. Upon completion of the forward voltage drop tests remove the minus 18 volt power supply from Pin 14A and all leads from the module."

Paragraph 4.5.6.1.2: Delete in its entirety and substitute:

"4.5.6.1.2 Leakage current.- Leakage current shall be tested by the following procedures to determine compliance with 3.4.4.2.

(a) Connect the plus 15 volt power supply to Pin 49B. Connect the power supply ground return to pins 33B and 26B. The voltage from Pin 49B to Pins 8B and 20B shall be less than 0.05 volt. Remove the power supply ground return from Pins 33B and 26B.

(b) Connect the plus 15 volt power supply ground return to Pins 2B and 23B. The voltage from Pin 49B to Pins 8B and 20B shall be less than 1.7 volts. Remove the power supply ground return from Pins 2B and 23B.

(c) Connect the plus 15 volt power supply ground return to Pin 14A. The voltage from Pin 49B to Pins 8B and 20B shall be less than 1.7 volts. Remove the plus 15 volt power supply from Pin 49B and the ground return from Pin 14A.

(d) Connect the plus 15 volt power supply to Pin 50B. Connect the power supply ground return to Pin 5A and 24A. The voltage from Pin 50B to Pins 10B and 19B shall be less than 1.18 volts. Remove the power supply ground return from Pins 5A and 24A.

(e) Connect the plus 15 volt power supply ground return to Pin 14A. The voltage from Pin 50B to Pins 10B and 19B shall be less than 1.18 volts. Remove the plus 15 volt power supply from Pin 50B and the ground return from Pin 14A.

(f) Connect the plus 15 volt power supply thru a 68 K ohm 1/4 W ± 5 percent resistor to Pin 14A. Connect the power supply ground return to Pin 20A. The voltage from the plus 15 volt power supply to Pin 14A shall be less than 1.7 volts. Move the plus 15 volt power supply ground return from Pin 20A to Pin 22A. The voltage from the plus 15 volt power supply to Pin 14A shall be less than 1.7 volts. Remove the power supply ground return from Pin 22A and the connection from Pin 14A.

Figure 3: Delete and substitute new Figure 3.



Figure 3

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A048

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:17Z
Check the source to verify that this is the current version before use.