INCH-POUND

A-A-55469C
18 August 2025
SUPERSEDING
A-A-55469B
15 November 2015

COMMERCIAL ITEM DESCRIPTION

CONNECTORS, ELECTRICAL, PLUGS, TIP (TEST POINT PLUG, BANANA PLUG) GENERAL REQUIREMENTS FOR

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies.

1. SCOPE. This CID covers the general requirements for test point plugs and banana plugs for use in electrical and electronic equipment. The test point connectors covered by this CID are primarily for use in airborne, ground support, and shipboard electrical and electronic equipment, for test purposes only. They are not intended for use as an integral part of the equipment for which the overall system operation is dependent. Connectors covered by this CID are intended for commercial/industrial applications and shall not be used in military systems needing stringent environmental and electrical requirements.

2. CLASSIFICATION/PART OR IDENTIFICATION NUMBER. This CID uses a classification system which is included in the Part Identification Number (PIN) as shown in the following example (see 7.1).

A-A-55469	/01	-	001
CID number	Applicable CID Sheet (two digits)		Dash number (see applicable CID sheet)

3. SALIENT CHARACTERISTICS.

3.1 Interface and physical dimensions. The connectors supplied to this CID shall be as specified on the applicable CID sheet.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: Defense Supply Center, Columbus, ATTN: DLA Land & Maritime-VAI, Post Office Box 3990, Columbus OH 43216-5000 or by email: RFConnector@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:47Z
Check the source to verify that this is the current version before use.

3.2 Materials. Material shall be as specified herein; however, when a definite material is not specified, a material shall be used which will enable the connectors to meet the performance requirements of this CID. Acceptance or approval of any constituent material shall not be construed as a guaranty of the acceptance of the finished product.

3.3 Metal parts.

3.3.1 Nonmagnetic materials. All parts shall be made from materials which are classified as nonmagnetic.

3.3.2 Dissimilar metals. Where dissimilar metals are used in intimate contact with each other, protection against electrolysis and corrosion shall be provided. Dissimilar metals shall be defined as when metallic areas (finished or unfinished) to be placed in intimate contact by assembly presents a special problem, since intermetallic contact of the dissimilar metals results in electrolytic couples which promote corrosion through galvanic action. Dissimilar metals such as brass, copper, or passivated steel (except corrosion-resisting steel) shall not be used in intimate contact with aluminum or aluminum alloy.

3.3.3 Metals and finishes. All exposed metal parts, except electric contacts, terminals, and corrosion-resisting steel parts shall be nickel-plated in accordance with class I, type 2 of SAE-AMS-QQ-N-290. Steel parts shall be passivated in accordance with SAE-AMS-2700 to prevent corrosion.

3.3.4 Contacts. Contacts and contact tabs shall be made of copper-beryllium in accordance with ASTM B194 or ASTM B196/196M, ASTM B197/B197M or (when specified in applicable CID sheet) phosphor bronze in accordance with ASTM B139/B139M or nickel silver in accordance with ASTM B122/B122M. Contacts shall be gold plated (99.0 percent in purity, knoop hardness 130 through 200 inclusive) .00005 inch thick minimum. Silver underplate shall not be used. Spring contacts are nickel silver and are nickel plated .0001 inch minimum, in accordance with SAE-AMS-QQ-N-290.

3.3.4.1 Terminals. Soldering terminals shall be made of a copper alloy material, and shall be gold plated (99.0 percent in purity, knoop hardness 130 through 200 inclusive) with an .0002-inch minimum thickness underplate of either copper or nickel, or shall be tin plated (The tin purity shall not exceed 97 percent.), .0004-inch (0.010 mm) thick minimum with a .0002-inch minimum thickness underplate of copper. Silver underplate shall not be used. Solder studs are tin plated .0001 inch minimum with no underplate.

3.3.5 Plastic parts. Plastic parts shall be made of glass fiber-filled diallyl phthalate resin, polypropylene, acrylonirtile butadiene styrene (ABS) in accordance with ASTM D4673 or ASTM D4894 and ASTM D4895, or nylon 6/6, in accordance with ASTM D4066. The color of the insulated portions shall be black number 17038 or red number 11136 in accordance with SAE-AMS-STD-595.

3.3.6 Flammability. Plastic material shall be limited to those certified by their manufacturers as self-extinguishing in accordance with method ASTM D635 or ASTM D2863.

3.3.7 Threaded parts. Screw threads for threaded parts shall conform to FED-STD-H28 and shall be as specified in the applicable CID sheet.

3.3.8 Operating temperature. Unless otherwise specified in the applicable CID sheet, connectors shall have an operating temperature range of -65°C to +50°C.

3.3.9 Contact identification. Contact positions or multiple-contact connectors shall be permanently identified by legible letters or numerals, as specified in the applicable CID sheet, molded or stamped on the front and rear face of the connector body. Marking shall be arranged to avoid confusion between contacts.

3.3.10 Contact arrangement. The center-to-center distance between contacts shall be as specified in the applicable CID sheet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:47Z
Check the source to verify that this is the current version before use.

3.3.11 Contact finish. Contact finish shall be smooth, free of shear lines, tear our or scratches, and shall show no signs of porosity or surface cracks.

3.3.12 Contact current rating. The current rating of contacts shall be as shown in table I, or as specified in the applicable CID sheet.

TABLE I. Contact current rating.

Contact diameter	Current rating (maximum)
Inch	Amperes
.040	3
.080	5
.150 through 170	8

3.4 Cable mounting hardware. Screws, clamps, brackets, or similar means for mounting the cable shall be furnished.

3.5 Marking. Connectors supplied to this CID shall be marked with the manufacturers (MFR's) standard commercial PIN.

3.6 Workmanship. Connectors shall be processed in such a manner as to be uniform in quality and shall be free from pits, cracks, rough edges, and other defects that will affect life, serviceability, or appearance.

4. REGULATORY REQUIREMENTS. The offerer/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. PRODUCT CONFORMANCE PROVISIONS.

5.1 Product conformance. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

5.2 Certificate of compliance. At time of order, a certificate of compliance shall accompany all connectors supplied to this CID upon request.

6. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES.

7.1 PIN. The PIN should be used for Government purposes to buy commercial products to this CID. See section 2 for PIN format example.

7.2 Recycled, recovered, environmentally preferable, or biobased materials. Recycled, recovered, environmentally preferable, or biobased materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

7.3 Commercial and Government Entity (CAGE) code. For ordering purposes, inventory control, and submission of these connectors to DSCC under the Military Parts Control Advisory Group (MPCAG) evaluation program, CAGE code 58536 should be used.

7.4 Source of documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:47Z
Check the source to verify that this is the current version before use.

FEDERAL REGULATIONS

FAR – Federal Acquisition Regulations (FAR).

(Copies of this document are available online at http://www.acquisition.gov/comp/far/index.html from the U.S. Government Printing Office, 732 North Capital Street, NW, Washington D.C. 20401-0001.)

FEDERAL STANDARDS

FED-STD-H28 - Screw Thread Standards for Federal Services

(Copies of these documents are available online at http://quicksearch.dla.mil.)

Other Publications

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE-AMS-QQ-N-290 - Nickel Plating (Electrodeposited)
SAE-AMS-2700 - Passivation Treatments for Corrosion-Resistant Steel
SAE-AMS-STD-595 - Colors Used in Government Procurement

(Applications for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, Pennsylvania, 15096-0001. https://www.sae.org.)

ASTM INTERNATIONAL

ASTM B122/B122M - Standard Specification for Copper-Nickel-Tin Alloy, Copper-Nickel-Zinc Alloy (Nickel Silver), and Copper-Nickel Alloy Plate, Sheet, Strip, and Rolled Bar
ASTM B139/B139M- Rod, Phosphor Bronze, Bar and Shapes
ASTM B194 - Copper Beryllium Alloy Plate, Sheet, Strip and Rolled Bar
ASTM B196/196M - Rod and Bar, Copper-Beryllium Alloy
ASTM B197/197M - Wire, Alloy Copper-Beryllium
ASTM D635 - Plastics in a Horizontal Position, Rate of Burning and/or Extent and Time of Burning Of
ASTM D2863 - Plastics, Measuring the Minimum Oxygen Concentration to Support Candle-Like Combustion Of (Oxygen Index)
ASTM D4066 - Standard Classification System for Nylon Injection and Extrusion Materials (PA)
ASTM D4673 - Molding and Extrusion Materials, Acrylonitrile-Butadiene-Styrene (ABS), Plastics and Alloys
ASTM D4894 - Standard Specification for Polytetrafluoroethylene (PTFE) Granular Molding and Ram Extrusion Materials
ASTM D4895 - Standard Specification for Polytetrafluoroethylene (PTFE) Resin Produced from Dispersion

(Applications for copies should be addressed to the ASTM International, PO Box C700, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959, https://www.astm.org.)

7.5 Ordering data. The contract or order should specify the following:

a. CID document number, revision, and CID PIN.
b. Product conformance provisions.
c. Packaging requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:47Z
Check the source to verify that this is the current version before use.

7.6 Government users. To acquire information on obtaining these connectors from the Government inventory system, contact DLA Land & Maritime ATTN: DSCC-VAI, Post Office Box 3990, Columbus, OH 43216-5000.

7.7 Suggested sources of supply. Refer to the associated CID as specified herein.

7.8 Subject term (key word) listing.

Acrylonirtile butadiene styrene
Glass fiber-filled diallyl phthalate resin
Nonmagnetic
Polypropylene

7.9 Revision notations. The margins of this specification are marked with vertical lines to indicate where modifications from this revision were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

MILITARY INTERESTS:

Custodians:
Army – CR
DLA – CC

Review activities:
Army - PT

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FAS

Preparing activity:

DLA - CC

(Project 5935-2025-083)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:47Z
Check the source to verify that this is the current version before use.