INCH-POUND

A-A-55469/4A
1 August 2003
SUPERSEDING
A-A-55469/4
7 April 1995

COMMERCIAL ITEM DESCRIPTION
SPECIFICATION SHEET

# CONNECTORS, ELECTRICAL, PLUGS, TIP, SINGLE RIGHT ANGLE (BANANA PLUG)

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies.

The complete requirements for acquiring the connectors described herein shall consist of this document and the issue in effect of CID A-A-55469

CLASSIFICATION/PART OR IDENTIFICATION NUMBER (PIN). This CID uses a classification system which is included in the PIN as shown in the following example.




TABLE I. Design and identification data.

| Dash number AA55469/04 | Color | Current rating (amperes, maximum) | Contact resistance (milliohms, maximum) |
|---|---|---|---|
| 01 | Black | 15 | 10 |
| 02 | Red | 15 | 10 |

SALIENT CHARACTERISTICS.

Design, construction, and dimensions. Design, construction, and dimensions shall be as specified on figure 1 and table I.

Contact current rating. Contact current rating shall be as specified in table I.

Contact resistance. Contact resistance shall be as specified in table I.

AMSC N/A FSC 5935
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:47Z
Check the source to verify that this is the current version before use.




| Inches | mm |
|---|---|
| .125 | 3.18 |
| .150 | 3.81 |
| .160 | 4.06 |
| .40 | 10.16 |
| .58 | 14.73 |
| .75 | 19.05 |
| .94 | 23.88 |
| 1.50 | 38.1 |

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ± .010 (0.25 mm) for three-place decimals and ± .03 (0.08 mm) for two-place decimals.
4. When set screw is used, the head shall be below the surface of the insulating material.

FIGURE 1. Configuration and dimensions.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:47Z
Check the source to verify that this is the current version before use.

Dielectric withstanding voltage (at sea level). Dielectric withstanding voltage (at sea level) shall be 3,000 V rms at 60 Hz or 5,000 V dc.

Operating voltage. Operating voltage is 300 volts rms, 60 hertz at sea level.

Marking. Connectors supplied to this CID shall be marked with the manufacturer's standard commercial part number.

NOTES.

PIN. The PIN should be used for Government purposes to buy commercial products to this CID. See classification information for PIN format example.

Supersession data. This CID supersedes MIL-C-28901/4.

Suggested sources of supply. Suggested sources of supply are listed below. Additional sources will be added as they become available. The vendors listed have submitted a certificate of compliance to DSCC-VAI and meet the requirements of this CID.

| Dash number (see table I) AA55469/04- | Vendor commercial PIN CAGE 91967 | Applicable NSN |
|---|---|---|
| 01 | 255-103 | 5935-00-491-9456 |
| 02 | 255-102 | 5935-00-416-6356 |

Commercial products. As part of the market analysis and research effort, this CID was coordinated with the following manufacturers of commercial products. At the time of CID preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID. (NOTE: This information should not be used to restrict procurement to only the manufacturers shown.)

| Vendor CAGE number | Vendor name and address |
|---|---|
| 91967 | Abbatron<br>632 Arch Street<br>Meadville, PA 16335 |

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - 7FXE

PREPARING ACTIVITY:

DLA - CC

(Project 5935-4519-002)



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:47Z
Check the source to verify that this is the current version before use.