[INCH-POUND]
A-A-859A
July 29, 1993
SUPERSEDING
A-A-859
July 1, 1980

COMMERCIAL ITEM DESCRIPTION

BREADBOX, PANTRY

The General Services Administration has authorized the use of this commercial item description as a replacement for Federal Specification RR-B-623 which has been canceled.

1. SCOPE

1.1 Scope. This commercial item description covers a metal breadbox used in kitchens and dining facilities.

2. APPLICABLE DOCUMENTS

2.1 The documents referenced in this commercial item description shall be the issues in effect on the date of issuance of the invitation for bids or request for proposal unless otherwise specified. These documents form a part of this commercial item description to the extent specified. In the event of a conflict between this commercial item description and a document referenced herein, this commercial item description shall take precedence.

Federal Standard:

FED-STD-376 - Preferred Metric Units For General Use By The Federal Government.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Engineering Group (7FXEE), 819 Taylor St., Fort Worth, TX 76102

DISTRIBUTION STATEMENT A : Approved for public release; distribution is unlimited.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.

Copies of Federal standards are available from the General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA, and the GSA Specifications Unit (3FBP-W), Suite 8100, L'Enfant Plaza, S.W., Washington, DC 20407.

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

Copies of military standards may be obtained from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

ASTM Standard:

E 29 - Standard Practice For Using Significant Digits In Test Data To Determine Conformance With Specifications.

Application for copies of ASTM standards should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103.

NSF International:

Standard Number 2 - Food Service Equipment.
Annual Listing - Food Service Equipment and Related Products, Components and Materials.

Application for NSF International documents should be addressed to the NSF International, 3475 Plymouth Road, P.O. Box 130140, Ann Arbor, MI 48113-0140.

3. SALIENT CHARACTERISTICS

3.1 Design and construction. The pantry breadbox may be fabricated from either aluminum or corrosion-resisting steel. The breadbox shall be 11 inches (279.4 mm) high by 17-1/2 inches (444.5 mm) wide by 12-1/2 inches (317.5 mm) deep. A tolerance of ± 1/4 inch (6.4 mm) shall be allowed in all directions. The minimum thickness of the material shall be 0.036 inch (0.9 mm) if aluminum is used and 0.020 inch (0.5 mm) if corrosion-resisting steel is used.

3.1.1 Body. The body shall be fabricated from a single piece of metal. A metal staple sized to fit the cover hasp shall be securely fastened on the front of the body. The upper edge of the body shall be reinforced by folding inside to form a hem and flattened tightly. The vertical seam joining the ends of the body shall be flat and shall be centrally located in the back of the body. Small ventilation holes shall be provided at the ends.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.

3.1.2 Cover. The cover shall be fabricated from a single piece of metal. The cover shall be made from the same material as the body and may be up to 20 percent less in thickness. The cover shall be hinged at the back with two hinges or one piano hinge and shall have a metal hinged hasp at the front. The cover shall be reinforced by folding the edges to form a hem and flattened tightly. The cover shall close over the rim of the body with a hinged hasp fitting over the hasp staple on the body.

3.2 Finish. Aluminum breadboxes shall have a white anodized finish and corrosion-resisting steel breadboxes shall have a polished finish.

3.3 NSF International compliance. Prior to approval of first shipment, the contractor shall submit to the contracting officer or his authorized representative satisfactory evidence that the items offered meet the applicable requirements of NSF International Standard No. 2. Satisfactory evidence of this compliance may be any of the following:

(1) A listing in the current edition of the NSF International "Listing of Food Service Equipment" and display of the NSF International mark on the finished item, or

(2) A certification issued by NSF International under this special one-time contract evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the contracting officer or authorized representative of the service for which the items are being procured, indicating that the item has been tested and conforms to NSF International Standard No. 2.

3.4 Marking for identification. The manufacturer's name, trade name, or trademark shall be applied to the breadbox. The breadbox shall be legibly marked with the word "Bread".

3.5 Workmanship. The finished breadbox shall be clean and smooth and shall not contain any burrs, rough die, tool, gouge, or grind marks. The finished item shall not be fractured, dented, bent, punctured, or malformed. There shall be no defects which may impair serviceability, durability or appearance.

3.6 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580, as amended, to the maximum extent practicable.

3.7 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within tolerances specified using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this document are met.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:10Z
Check the source to verify that this is the current version before use.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the specification preparing activity for changes to this document.

3.8 Measurement system. The values stated in inch-pound units are to be regarded as the standard. The values stated in parentheses are for information purposes only.

3.9 Commercial item. The use of the term "commercial item description" in this document does not imply that any item or items offered are not required to conform with all requirements specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor certification. The contractor shall certify that the item meets the salient characteristics and the requirements of this commercial item description, and, except for any government unique requirements specified, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product offered for sale in the commercial marketplace, or is the same product that has been successfully been delivered to the government on a previous contract or purchase order. The government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.2 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.3 Sampling. The levels of inspection and acceptable quality levels (AQL's) shall be in accordance with MIL-STD-105.

4.4 Lot formation. All breadboxes from the same manufacturer offered for delivery at one time shall be considered a lot for purposes of inspection.

4.5 Sampling for visual and dimensional examination. A random sample of breadboxes shall be selected from each lot in accordance with inspection level S-4, AQL 4.0 expressed in terms of defects per hundred units. The sample unit shall be one finished breadbox.

of this commercial item description.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.

The sample breadbox shall be visually and dimensionally examined to verify compliance with table I and the remainder of this commercial item description. All dimensions are absolute as defined in ASTM E 29.

4.6 Examination for preparation for delivery. A random sample of shipping containers shall be selected from each lot for examination of the unit, intermediate and shipping containers (as applicable) for conformance with the packaging, packing, and marking required in the contract or order. Samples shall be selected in accordance with inspection level S-2, AQL 6.5, expressed in terms of defects per hundred units. The sample unit shall be one shipping container.

TABLE I - Classification of defects

Examine	Defect
Finish	Area of corrosion Stained or discolored
Construction and Workmanship	Any burrs, slivers, sharp edges, rough die marks, or tool gouge. Any part missing, or not specified size Any component fractured, split, bent, buckled, punctured or otherwise impaired
Marking	Missing, incomplete, or illegible.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, and marking. The packaging, packing, and marking shall be as specified in the contract or order.

6. NOTES

6.1 Ordering data. Purchasers should include the following information in procurement documents (if applicable):

a. Title, number and date of this commercial item description.
b. The packaging, packing, and marking required.

6.2 National Stock Number (NSN). The following NSN corresponds to this CID: 7330-00-151-9821.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:10Z
Check the source to verify that this is the current version before use.

Military Coordinating Activity:

Army - GL

Custodians:
Army - GL
Navy - SA
Air Force - 99

Review Activities:
Army - MD, QM
Air Force - 84, 50

User Activity:
Navy - MC

Civil Agency Coordinating Activity:

VA - OSS

PREPARING ACTIVITY:

GSA - FSS

(DoD Project 7330-0666)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.