MIL-A-516J
INT. AMENDMENT 1(ME)
2 May 1983

MILITARY SPECIFICATION

AUGER, EARTH, SKIDMOUNTED: AND

AUGER, EARTH,

TURNTABLE BASE MOUNTED, POWER DRIVEN

This interim amendment is approved for use by the US Army Mobility Equipment Research and Development Command, Department of the Army, with Military Specification MIL-A-516J, dated 1 September 1981.

PAGE 2

2.1.1, under SPECIFICATIONS, MILITARY, DELETE:

"MIL-T-740 - Trucks; 5-Ton, 6 X 6, Military Design, M39 Series."

2.1.1, under STANDARDS, MILITARY, add:

"MIL-STD-1474 - Noise Limits for Army Materiel."

PAGE 3

2.2, delete entirely: "AMERICAN IRON AND STEEL INSTITUTE (AISI)" and add:

"AMERICAN SOCIETY OF TESTING AND MATERIALS (ASTM)

A304 - Alloy Steel Bars Subject to End-Quench Hardenability Requirements.
A322 - Steel Bars, Alloy, Standard Grades.
A331 - Steel Bars, Alloy, Cold-Finish.

(Application for copies should be addressed to the American Society of Testing and Materials, 1916 Race Street, Philadelphia, PA 19103)."

PAGE 11

3.17.1, line 5, delete "under the rear corners of the truck", and substitute "to the rear end of the frame of the truck".

3.17.3, delete last sentence in its entirety and substitute:

"The auger bar shall be hot-roller or cold drawn alloy steel conforming to ASTM A322 or A331, UNS designation G4140-G4145, or A304, UNS designation J4140-H4145. The steel shall have fine grain (austenitic grain size 5 to 8) and shall be quenched and tempered to 277-321 Brinell hardness to obtain 138,000 psi minimum tensile strength."

FSC 3820

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:40Z
Check the source to verify that this is the current version before use.

PAGE 13

after 3.19.1, add the following:

"3.19.2 Engine oil sampling valve. An oil sampling valve shall be provided on the engine and transmission. The valve shall be manually operated and shall automatically close after release. It shall be made of material resistant to corrosion such that it will not contaminate the sample. The discharge port of the valve shall be covered with a captive chained cap conforming to SAE J514. The valve shall be located in such a way as to insure that personnel will not be exposed to danger when taking oil samples with the engine running. The location of the oil tap shall be such that when samples are taken, it shall be a true representation of oil that is flowing while the engine is running."

3.20.1 line 2, delete "5 ton, military design truck conforming to MIL-T-740 or equal," and substitute "military truck, cargo, 14 foot body, model M54A2C/ with winch or M813CW/winch or M925.

PAGE 18

4.6.2.8.1, line 3, delete "Nonconformance to 3.7.2.1 shall constitute failure of this test."

4.6.2.8.2, line 2, delete "Nonconformance to 3.7.2.2 shall constitute failure of this test."

Add:

4.6.2.8.3 Failure Criteria. When the sound level of the equipment exceeds 85 dB(A) at the operator's station, a noise hazard caution sign per MIL-STD-1474 shall be permanently affixed to the euipment in the operator's compartment. The noise hazard zone shall be clearly stenciled on the equipment in a conspicuous location with 3/4 inch letters stating: "Hearing protection required with _____feet from this equipment".

PAGE 26

6.4, lines 1, 2, delete "table I of SAE J106" and substitute "The Unified Soil Classification Table."

6.6, and 6.7, line 2, delete 5-ton, military design truck conforming to MIL-T-740", and substitute "Military truck, cargo, 14 feet body, model M54A2C/with winch or M813CW/winch or M925.

Custodian:
Army - ME

Preparing activity
Army - ME

Project 3820-A015

☆ U.S. GOVERNMENT PRINTING OFFICE: 1982—605-034/2692 2-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:40Z
Check the source to verify that this is the current version before use.