MIL-A-516J
INT. AMENDMENT 2(ME)
8 January 1988
SUPERSEDING
INT. AMENDMENT 1 (ME)
2 May 1983

MILITARY SPECIFICATION

AUGER, EARTH, SKIDMOUNTED: AND

AUGER, EARTH,

TURNTABLE BASE MOUNTED, POWER DRIVEN

This interim amendment is approved for use by the US Army Belvoir Equipment Research, Development and Engineering Center, Department of the Army, with Military Specification MIL-A-516J, dated 1 September 1981.

PAGE 2

* 2.1.1, under SPECIFICATIONS, FEDERAL, delete "PPP-T-60" in its entirety.

Under SPECIFICATIONS, MILITARY, delete MIL-T-740 in its entirety and add:

MIL-T-22085	- Tape, Packaging, Waterproof
MIL-C-46168	- Coating, Aliphatic Polyurethane, Chemical Agent Resistant.
MIL-C-53039	- Coating, Aliphatic Polyurethane, Chemical Agent Resistant."

Under STANDARDS, FEDERAL, delete "FED-STD-595 in its entirety.

Under STANDARDS, MILITARY, add:

"MIL-STD-1474	Noise Limits for Army Materiel."
MS52181	Connector, Plug, Electrical Intervehicle Power Cable."

PAGE 3

2.2, delete entirely: "AMERICAN IRON AND STEEL INSTITUTE (AISI), Steel Products Manual" and add:

"AMERICAN SOCIETY OF TESTING AND MATERIALS (ASTM)

A304 " Alloy Steel Bars Subject to End-Quench Hardenability Requirements.
A322 - Steel Bars, Alloy, Standard Grades.
A331 - Steel Bars, Alloy, Cold-Finish.

AMSC N/A FSC 3820
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-16T07:40Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Society of Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).”

PAGE 4

* 3.1, add the following at end of paragraph:

“Boom length for pole setting shall be not less than 15 feed from auger mounting surface ot top of boom when in elevated working position. The working height with the auger mounted on the Military cargo trucks listed in 3.20.1 shall not exceed 24 feet.”

PAGE 7

* 3.6.9, line 5, after “accessible for cleaning.” add:

“The system fluid shall conform to MIL-L-2104, grade 10. All hydraulic system component materials shall be compatible with the oil. A straight thread ‘[o” ring boss diagnostic port conforming to SAE J514 shall be provided at the pump(s) outlet or pressure inlets to the valves."

PAGE 9

* 3.10.1, line 2, delete "SAE J754 and, when practical" and substitute "SAE J754 when lubricants are compatible with Military standard and.”

* 3.10.3, line 3, delete “manual fluid level” and substitute “dipsticks, check plugs, or sight gage.” Line 9, after “enclosure” add “and without draining onto or over other components of the auger.”

* 3.13, delete the first sentence and substitute: “The auger shall be furnished with an identification plate showing the contractor’s model number, NW?, serial number, weight, date of manufacture, and date of delivery in accordance with MIL-STD-130.”

PAGE 10

* 3.14 delete in its entirety and substitute:

“3.14 Treatment and painting. The portions of the auger normally painted shall be cleaned, treated and painted in accordance with MIL-T-704, type F or G. Unless otherwise specified (see 6.2), the finish coat shall be camouflage green 383 conforming to MIL-C-46168 or MIL-C-53039. When specified (see 6.2) the finish coat shall be camouflage pattern painted in accordance with Government furnished patterns.”

* 3.15, “line l,” after "provided with a“ add “waterproof”. Line 8, delete “The toolbox shall shed water and have provision for draining.”

PAGE 11

3.17.1, line 5, delete “under the rear comers of the truck”, and substitute "to the rear end of the frame of the truck”.

Source: https://assist.dla.mil -- Downloaded: 202610-16T07:40Z
Check the source to verify that this is the current version before use.

3.17.3, delete last sentence in its entirety and substitute:

"The auger bar shall be hot-roller or cold drawn alloy steel conforming to ASTM A322 or A331, UNS designation G4140-G4145, or A304, UNS designation J4140-H4145. The steel shall have fine grain (austenitic grain size 5 to 8) and shall be quenched and tempered to 277-321 Brinell hardness to obtain 138,000 psi minimum tensile strength."

PAGE 13

after 3.19.1, add the following:

*"3.19.2 Engine oil and transmission sampling valve. An oil sampling valve shall be provided on the engine and transmission. The valve shall be manually operated and shall automatically close after release- They shall be made of material resistant to corrosion such that it will not contaminate the sample. The discharge port of the valve shall be covered with a captive chained cap conforming to SAE J514. The valves shall be located in such a way as to insure that personnel will not be exposed to danger when taking oil samples with the engine or transmission running. The location of the oil tap shall be such that when samples are taken, it shall be a true representation of oil that is flowing while the engine or transmission is running. The valves shall be labeled "Engine Oil" and "Transmission Oil" respectively."

3.19.3 Slaving components. The auger shall be equipped with a 24 volt slave receptacle conforming to MS52131. The slave receptacle shall permit charging of the batteries and starting of the engine from external power source for charging and slaving other equipment. The slave receptacle shall be installed on the exterior of the auger near the battery compartment. The voltage potential of' the salve receptacle shall be identified on a plate mounted adjacent to the receptacle."

3.20.1 line 2, delete "5 ton, military design truck conforming to MIL-T-740 or equal," and substitute "military truck, cargo, 14 foot body, model M54A2C with winch or M813CW winch or M925.

PAGE 18

4.6.2.8.1, line 3, delete "Nonconformance to 3.7.2.1 shall constitute failure of this test."

4.6.2.8.2, line 2, delete "Nonconformance to 3.7.2.2 shall constitute failure of this test."

Add:

4.6.2.8.3 Failure criteria. When the sound level of the equipment exceeds 85 dB(A) at the operator's station, a noise hazard caution sign per MIL-STD-1474 shall be permanently affixed to the equipment in the operator's compartment. The noise hazard zone shall be clearly stenciled on the equipment in a conspicuous location with 3/4 inch letters stating: "Hearing protection required with feet from this equipment".

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:40Z
Check the source to verify that this is the current version before use.

PAGE 22

* 5.2. 1.8,. line 8, delete “PPPOT-60, type IV” and substitute MIL-T-22085, type II.”

PAGE 35

* 6.2, add: “(w) When finish coat shall be camouflage pattern painted (see “ 3.14).”

PAGE 26

6.4, lines 1, 2, delete “table I of SAE J106" and substitute “The Unified Soil Classification Table."

6.6, and 6.7, line 2, delete 5-ton, military design truck conforming to MIL-T-740”, and substitute “Military truck, cargo, 14 feet body, model M54A2C with winch or M813CW with winch or M925.

Custodian:
Army-ME

Preparing activity
Army-ME

Project 3820-A029

Source: https://assist.dla.mil -- Downloaded: 202610-16T07:40Z
Check the source to verify that this is the current version before use.