MILITARY SPECIFICATION

TANK, STORAGE DISTILLING

1. SCOPE

1.1 This specification covers one type of tank, suitable for the storage of distilled water.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-B-585	Boxes, Wood, Wirebound.
PPP-B-601	Boxes, Wood, Cleated-Plywood.
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	Box, Fiberboard.

Military

MIL-L-10547	Liners, Case, and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible.

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:34Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material. Material shall be suitable for the purpose intended and as hereinafter specified.

3.2 Construction. Unit shall consist of a storage tank and a supporting stand. Total height of the tank plus the stand shall be 41 ± 1 inches.

3.2.1 Storage tank. Storage tank shall be fabricated of cold-rolled copper, and the inside surfaces shall be lined with block tin. Seams shall be double locked and soldered with block tin. Side of storage tank shall have an outlet faucet and a glass tube. Outlet faucet shall have a brass seat with a fiber washer, and inside surfaces of faucet shall be lined with block tin. Glass tube shall be of such design as to indicate the level of the water in the tank and shall be protected by metal rods. Top of storage tank shall have a handhole and a protrusion for connection to the source of distilled water. Handhole shall have a removable cover, the inside surface of which shall be lined with block tin and which shall make a dustproof seal with the tank. Protrusion shall be circular and shall be of sufficient length to accept rubber tubing. Tank shall have a capacity of 25 gallons (minimum), a height of 26 ± 1/2 inches, and a diameter of 18 + 1/2 meters. Bottom of the internal circumference of the faucet shall be 1/4 inch (maximum) from the bottom of the tank. Tank shall not leak, when tested as specified in 4.4.1.

3.2.2 Support stand. Support stand shall be fabricated from iron and shall consist of a minimum of four legs with cross bars connecting opposite legs. Intersection of cross bars shall be so secured, that the stand will stand by itself. The tops of the legs shall be so designed that the tank can rest on them without slipping. Stand shall not break, buckle, or deform in any way, when tested as specified in 4.4.1. Legs and bracing shall be finished with silicone paint.

3.3 Workmanship. Workmanship shall be first class throughout. The tank shall be free from defects which detract from its appearance or may impair its serviceability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:34Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual, auditory, etc., investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.2 Certificates of quality. When available, certificates of quality, supplied by the manufacturer of the component or material, listing the specified test method and test results obtained, may be furnished in lieu of actual performance of such testing by the contractor.

4.2 Sampling.

4.2.1 For examination. Sampling for examination shall be conducted in accordance with MIL-STD-105.

	Inspection level	AQL (percent defective)
For visual examination		
Major defects	II	2.5
Minor defects	II	4.0
For dimensional examination	S-1	2.5

4.2.2 For tests. Sampling for tests shall be conducted in accordance with MIL-STD-105.

Component (unit of product)	Characteristic	Requirement	Test procedure	Inspection level	AQL
Tank	Leakage	3.2.1	4.4.1	S-2	*
Stand	Support	3.2.2	4.4.1	S-2	*

*. Acceptance number shall be zero.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:34Z
Check the source to verify that this is the current version before use.

4.3 Examination. The tanks shall be examined to determine compliance with all requirements contained in this specification.

4.3.1 Classification of defects. Examination shall be conducted in accordance with the following classification of defects:

Categories and defects*

Major
101 Component part missing.
102 Unit not free of deformity.
103 Unit not free of sharp edges.
104 Lining on tank not continuous.
105 Lining on cover not continuous.
106 Stand not capable of standing upright (without tank on top).
107 Intersection of cross bars not secured.
108 Glass tubes not free of cracks and chips.

Minor
201 Stand not free of rocking when placed on a flat surface.
202 Finish on stand not continuous.
203 Finish on stand not free of blisters.

*Examination shall not be restricted to the classified possible defects listed above.

4.3.2 Dimensional examination. The unit shall be examined for defects in dimensions. Any dimension not within the tolerance specified herein shall be classified as a defect.

4.4 Tests. Tests shall be conducted to determine compliance with specification requirements.

4.4.1 Leakage and support. Tank shall be placed on stand, filled with water, and allowed to stand for 1 hour.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:34Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Unit of issue. One (1) tank, as specified, constitutes one unit of issue.

5.1.2 Level A.

5.1.2.1 Unit package. Each unit shall be packaged in a carton of appropriate size constructed in accordance with PPP-B-636. Carton shall be designed with suitable interior fittings or shall contain sufficient cushioning material to insure against shifting of, or damage to, the contents. Closure shall be in accordance with method I of PPP-B-636.

5.2 Packing.

5.2.1 Level A.

5.2.1.1 Exterior container. Each unit, packaged as specified in 5.1.2.1, shall be overpacked in an exterior container designed for type 2 load, and constructed in accordance with PPP-B-585, style 3, for class 3 use; PPP-B-601, table II, using type III, class 1 plywood; PPP-B-621, table III; or PPP-B-636, type CF, class weather-resistant.

5.2.1.2 Case liner. Each level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall conform to applicable paragraphs of appendix thereto. Case liner shall not be required for fiberboard boxes.

5.2.1.3 Closure. Closure of wood boxes shall be in accordance with appendix of applicable box specification. Closure of each fiberboard box shall be as specified in the appendix, and waterproofing shall conform to 30.4, of PPP-B-636.

5.2.1.4 Strapping. Strapping, when required, shall be in accordance with appendix of applicable box specification.

NOTE: Strapping shall not be required for shipments forwarded to a receiving activity within the continental limits of the United States for storage and redistribution.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:34Z
Check the source to verify that this is the current version before use.

5.2.2 Level B.

5.2.2.1 Exterior container. No overpacking shall be required.

5.3 Marking.

5.3.1 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Number and date of this specification.
(b) Selection of applicable level of packing (see 5.2).

6.2 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured to meet Military requirements.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Review activities:
Army - MD
Navy - MS
Air Force - 03

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:34Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEFENSE LOGISTICS AGENCY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Commander
Defense Personnel Support Center
ATTN: DPSC-ATTS
Philadelphia, PA 19101

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:34Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:34Z
Check the source to verify that this is the current version before use.