MILITARY SPECIFICATION

DETONATOR, FLASH, M21
LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type flash detonator designated as Detonator, M21.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-G-2550 - General Specification for Ammunition Except Small Arms Ammunition.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109 - Inspection Terms and Definitions.

DRAWINGS

ORDNANCE CORPS

7548100 - Box, Packing, Ammunition for Detonators.
7548103 - Box, Set-up, Packing, Ammunition, Outer for Booster, Detonators or Primers. Assembly, Details, Packing, and Marking.
7548104 - Box, Set-up, Packing, Ammunition, Inner for Boosters, Detonators or Primers. Assembly, Details, Packing and Marking.
8797756 - Detonator, Stab, M21, Loading Assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:27Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

ORDNANCE CORPS

ORD-M608-11 - Procedures and Tables for Continuous Sampling by Attributes.
IEL-7153519 - Index of Inspection Equipment Lists.

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications.-The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 71-78 - Interstate Commerce Commission Rules and Regulations for the Transportation of Explosives and Other Dangerous Articles.

(The Interstate Commerce Commission Regulations are now a part of the Code of Federal Regulations (1949 Edition and revisions) available from the Superintendent of Documents, Government Printing Office, Washington 25, D.C. Orders for the above publication should cite "49 CFR 71-78 (latest revision)".)

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with applicable drawings and specifications.

3.2 Detonators.-The detonators shall comply with all requirements specified on Drawing (dwg.) 8797756 and with all requirements specified in applicable specifications.

3.3 Moisture content of lead azide.-The moisture content of the lead azide used in loading the detonators shall not exceed 0.50 percent when tested as specified in 4.3.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:27Z
Check the source to verify that this is the current version before use.

3.4 Sensitivity.-The detonators shall function on the first attempt and shall cause perforation of the lead disc to a diameter of not less than 1/8 inch when tested as specified in 4.3.3.

3.5 Workmanship.-All parts shall be free from chips, dirt, grease, rust and other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.-The supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define the terms used herein. Inspection shall be performed in accordance with this specification and other specifications referenced in any of the contractual documents.

4.1.1 Contractor quality assurance system.-The contractor shall provide and maintain an effective quality assurance system acceptable to the Government covering the supplies procured under this specification and shall perform all inspections required by the system. A current written description of the system shall be submitted to the contracting officer, and meet his approval, prior to initiation of production. It shall include a description covering controls for lot formation and identification, inspections to be performed, inspection stations, sampling procedures, methods of inspection (gages, measuring, and testing equipment), and provisions for control and disposition of non-conforming material. The written description will be considered acceptable when, as a minimum, it provides the quality assurance required by the provisions of 4.2 and 4.3 and the other documents referenced herein. Except in the cases of 4.3.3 the contractor shall not be restricted to the inspection station nor the method of inspection listed in this specification provided that an equivalent control is included in the approved quality assurance procedure. In cases of dispute as to whether certain procedures of the contractor's system provide equal assurance, the comparable procedure of this specification shall apply. The contractor shall notify the Government of, and obtain approval for,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:27Z
Check the source to verify that this is the current version before use.

any change to the written procedure that affects the degree of assurance required by this specification or other documents referenced herein. In the case of the sensitivity test, the weight of the ball and height of drop shall not differ from the values specified in 4.3.3 and on the applicable test equipment drawing.

4.1.2 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.

b. Number of units of product inspected.

c. Results obtained for all inspection performed.

d. Drawing, specification number and date, together with an identification and date of changes.

e. Certificates of analyses on all material procured directly by the contractor.

f. Number of items in the lot.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principl. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.3 Government verification.-Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification shall consist of: (a) surveillance of contractor operations to determine that the methods and procedures of the written procedure are being properly applied and (b) Government product inspection. The Government inspector shall also ascertain prior to acceptance that the product complies with all the contractual documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:27Z
Check the source to verify that this is the current version before use.

4.1.3.1 Surveillance.-Surveillance shall include, but is not limited to:

a. Observation of procedures concerning lot formation and identification.

b. Observation of sampling procedures and application of acceptance criteria.

c. Determination that all required examinations and tests are performed in accordance with the prescribed procedures of this specification, or approved equivalents thereto.

d. Review of procedures for control and disposition of non-conforming material.

4.1.3.2 Product inspection.-Physical inspection by the Government of contractor accepted product will be performed to the extent necessary to assure contractor compliance with the requirements of this specification and to determine the reliability of contractor records. Severity of Government inspection of individual characteristics will be directly related to the seriousness classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records. (See Specification MIL-G-2550.)

4.1.3.3 Deviations and deficiencies.-Deviations from the prescribed or agreed upon procedures, or instances of poor practice which have an effect on the quality of the product, shall be called to the attention of the contractor immediately. To avoid interference with operations, the contractor shall designate a responsible official, or officials, to whom the Government inspector will report such instances. Failure of the contractor to correct deficiencies promptly, shall be cause for suspension of acceptance until correction has been made or until conformance to prescribed criteria has been demonstrated.

4.2 Inspection provisions.

4.2.1 Lot formation.-A lot shall consist of detonators produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification, and same specification revision. Drawing, specification, and process changes not affecting safety, performance, or fit, as determined by the Government, shall not necessitate changing the lot number. Each lot shall contain:

a. Parts bearing the same interfix lot number from one manufacturer.

b. Lead azide from not more than one lot.

c. Tetryl from not more than one lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:27Z
Check the source to verify that this is the current version before use.

4.2.2 Examination.-Sampling plans and procedures for the following classification of defects shall be in accordance with Standard MIL-STD-105 except that inspection for critical defects, when listed, shall be 100 percent. Continuous sampling plans in accordance with Handbook ORD-M608-11 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics listed using an AQL of 0.25 percent for each major defect and an AQL of 0.40 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Assembly (see dwg. 8797756).

Categories	Defects	Method of inspection
Critical:	None defined	
Major:	AQL 0.65 percent	
101.	Length	Gage
102.	Diameter	Gage
103.	Not crimped full 360°	Visual
104.	Disc loose	Manual
105.	Disc punctured or torn	Visual
106.	Cup damaged	Visual
107.	Color of lacquer incorrect (both ends)	Visual
Minor:	AQL 0.40 percent	
201.	Evidence of poor workmanship (see 3.5)	Visual

4.2.2.2 Box, set-up, packing, ammunition, inner (see dwg. 7548104).

Categories	Defects	Method of inspection
Critical:	None defined	
Major:	AQL 0.25 percent	
101.	Box damaged exposing contents	Visual
102.	Label missing or incorrect	Visual
Minor:	None defined	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:27Z
Check the source to verify that this is the current version before use.

4.2.2.3 Box, set-up, packing, ammunition, (see dwg. 7548103).

Categories	Defects	Method of inspection
Critical:	None defined	
Major:	AQL 0.25 Percent	
101.	Barrier bag damaged	Visual
102.	Label missing or incorrect	Visual
Minor:	None defined	

4.2.2.4 Box, packing, ammunition, for detonators (see dwg. 7548100).

Categories	Defects	Method of inspection
Critical:	None defined	
Major:	AQL 0.40 percent	
101.	Box damaged	Visual
102.	Nails missing or improperly driven	Visual
103.	Strapping missing or loose	Visual-Manual
104.	Marking incomplete or misleading	Visual
Minor:	None defined	

4.2.3 Testing.

4.2.3.1 Moisture content of lead azide (see 3.3) - Major defect.- The moisture content of the lead azide shall be determined for each lot at the time of loading. A sample of 2 grams shall be selected and tested as specified in 4.3.2. If the moisture content is in excess of the percentage specified and loading has not begun, the lot of lead azide shall be rejected until proper corrective action has been accomplished as verified by repeating the moisture content test specified in 4.3.2. If loading has begun, action on the unloaded lead azide shall be as specified above and all detonators loaded with the questionable lead azide shall be rejected.

4.2.3.2 Binder-lubricant content of tetryl (see dwg. 8797756) Major defect.-The binder-lubricant content of the tetryl shall be determined for each lot at the time of loading. A sample of 5 grams shall be selected and tested as specified in 4.3.1. If the binder-lubricant is in excess of the percentage specified, and loading has

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:27Z
Check the source to verify that this is the current version before use.

not begun, the lot of tetryl shall be rejected until proper corrective action has been accomplished as verified by repeating the binder-lubricant content test specified in 4.3.1. If loading has begun, action on the unloaded tetryl shall be as specified above and all detonators loaded with the questionable tetryl shall be rejected.

4.2.3.3 Sensitivity (see 3.4) - Major defect.-A sample of complete detonators shall be selected in accordance with Standard MIL-STD-105, using code letter P and an AQL of 0.15 percent. The sample detonators shall be tested as specified in 4.3.3, using test equipment specified in 4.2.4. Rejection shall be in accordance with Standard MIL-STD-105.

4.2.4 Inspection equipment.-For the performance of the examinations and tests specified in 4.2.2 and 4.2.3, when applicable, the contractor shall have available, and utilize correctly, all necessary gages, measuring, and testing equipment identified by Index of Inspection Equipment Lists No. 7153519, or approved equivalents thereto. (see 4.1.1). When inspecting the contractor's inspection equipment, the Government inspector will determine that the contractor has available, and utilizes correctly, gages, measuring and testing equipment of the required accuracy and precision and that the instruments are of the proper type and range to make measurements of the required accuracy. The contractor will have available a set of master gages, standards, and appropriate instruments for regularly scheduled calibration of his inspection equipment. Records of such regularly scheduled calibration will be maintained by the contractor and made available for review by the Government. The calibration of gages, standards, and instruments will be periodically checked by authorized Government personnel.

4.3 Test methods and procedures.

4.3.1 Determination of binder-lubricant content of tetryl.-An accurately weighed portion of 5 grams shall be transferred to a medium porosity sintered glass filtering crucible. The sample shall be extracted with four 10 milliliter (ml.) portions of acetone maintaining each portion in contact with the residue for approximately 5 minutes before applying suction. Any lumps which may persist shall be broken up and the sides of the crucible washed down with each 10 ml. portion of acetone to insure complete removal of the tetryl. The residue shall be asperated until the odor of acetone is no longer detectable. The curcible and contents shall be placed in a drying oven at 100 degrees Centigrade (°C.) - 150°C. for 1/2 hour, cooled in a desiccator and weighed. The above extraction shall be repeated, drying and weighing, with individual 10 ml. portions of acetone until the loss in weight on subsequent extractions totals less than 0.005 gram. The weight of residue in the crucible shall be calculated to the percentage of total binder-lubricant.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:27Z
Check the source to verify that this is the current version before use.

4.3.2 Determination of moisture content of lead azide.-A tared dried aluminum dish 2 inches in diameter shall be covered with a sheet of polytetrafluoroethylene 2 1/2 inches square and sufficiently flat to form a tight cover. An accurately weighed portion of approximately two grams of the sample shall be transferred to the moisture dish and the dish and the contents shall be transferred to an oven and dried at 95°C. ± 2°C. for two hours. The cover shall be placed in the sulfuric acid desiccator during the drying period. After drying, the dish shall be quickly transferred to the desiccator and allowed to cool to room temperature. The polytetrafluoroethylene cover shall be placed on the dish and the assembly weighed. The loss in weight shall be calculated to the percentage of moisture in the lead azide to determine compliance with 3.3 as follows:

$$\text{Percentage of moisture} = \frac{(A-B) \times 100}{A}$$

where:

A = weight of the sample before drying.
B = weight of the sample after drying.

4.3.3 Sensitivity of detonator.-The detonator shall be assembled to the applicable test fixture specified in 4.2.4 so that the firing pin will strike the sensitive end of a M55 Primer. A steel ball 13/16 inch in diameter and weighing 3.95 ounces maximum shall be dropped in the firing pin from a height of 8 inches maximum. The height of drop shall be measured as the height from the top of the firing pin to the bottom of the ball. A detonator that fails to fire or fails to create a hole in the lead disc of the required size shall be classed defective.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Levels B and C (see 6.3).-The detonators shall be preserved, marked and packaged in accordance with drawings 7548103 and 7548104.

5.2 Packing.

5.2.1 Level C.-The detonators shall be packed and marked in accordance with drawing 6548100.

5.3 Data cards.-Data card information shall be as specified in Specification MIL-G-2550.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:27Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data.-Procurement documents should specify the title, number, and date of this specification.

6.2 Check test for possible deterioration.-The following test is designed to prevent the loading of detonators which have deteriorated into a major ammunition item. The test should be performed on detonators from each lot which has been stored under normal conditions for more than two years, or under adverse conditions for any period of time. If the specification for the ammunition item into which the detonators are loaded does not require that the check test be performed, the contracting officer should insert a provision for the performance of the check test in the contract. The contracting officer shall arrange to have the contractor reimbursed for any expenses incurred in the performance of the check test for possible deterioration.

6.2.1 Sensitivity.-A sample of detonators shall be selected in accordance with Standard MIL-STD-105, using code letter P and an AQL of 0.25 percent. The sample detonators shall be tested as specified in 4.3.3, using test equipment specified in 4.2.4. Rejection shall be in accordance with Standard MIL-STD-105.

6.3 Level B packaging.-In the event the expected storage time of the detonators is in excess of 180 days, the barrier bag shall be used as specified on the applicable drawing. Expected storage time shall be determined by the procuring activity.

Notice.-When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodian:
Army-Ordnance Corps

Preparing activity:
Army-Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:27Z
Check the source to verify that this is the current version before use.