MILITARY SPECIFICATION

DETONATOR, STAB, M13
PARTS FOR

1. SCOPE

1.1 This specification covers the parts for one type of detonator designated as Detonator, Stab, M13.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-G-2550 - General Specification for Ammunition Except Small Arms Ammunition
MIL-P-10025 - Packing and Marking for Interplant Shipment of Inert Ammunition Components; General Specification.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109 - Inspection Terms and Definitions.

DRAWINGS

ORDNANCE CORPS

8797744 - Detonator, M13, Loading Assembly

PUBLICATIONS

ORDNANCE CORPS

ORD-M608-11 - Procedures and Tables for Continuous Sampling by Attributes.
GL-7300115 - Gage Lists

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:30Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with applicable drawings and specifications.

3.2 Parts.-The parts shall comply with all requirements specified on Drawing (dwg.) 8797744, , and with all requirements specified in applicable specifications.

3.3 Workmanship.-All parts shall be free of chips, dirt, grease, rust, and other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents used.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.-The supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define the terms used herein. Inspection shall be performed in accordance with this specification and other specifications referenced in any of the contractual documents.

4.1.1 Contractor quality assurance system.- The contractor shall provide and maintain an effective quality assurance system acceptable to the Government covering the supplies procured under this specification and shall perform all inspections required by the system. A current written description of the system shall be submitted to the contracting officer, and meet his approval, prior to initiation of production. It shall include a description covering controls for lot formation and identification, inspections to be performed, inspection stations, sampling procedures, methods of inspection (gages, measuring and testing equipment), and provisions for control and disposition of non-conforming material. The written description will be considered acceptable when, as a minimum, it provides the quality assurance required by the provisions of 4.2 and the other documents referenced herein. The contractor shall not be restricted to the inspection station nor the method of inspection listed in this specification provided that an equivalent control is included in the approved quality assurance procedure. In cases of dispute as to whether certain procedures of the contractor's system provide equal assurance, the comparable procedure of this specification shall apply. The contractor shall notify the Government of, and obtain approval for, any change to the written

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:30Z
Check the source to verify that this is the current version before use.

procedure that affects the degree of assurance required by this specification or other documents referenced herein.

4.1.2 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.

b. Number of units of product inspected.

c. Results obtained for all inspection performed.

d. Drawing, specification number and date, together with an identification and date of changes.

e. Certificates of analyses on all material procured directly by the contractor.

f. Number of items in the lot.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.3 Government verification.-Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification shall consist of: (a) surveillance of contractor operations to determine that the methods and procedures of the written procedure are being properly applied and (b) Government product inspection. The Government inspector shall also ascertain prior to acceptance that the product complies with all the quality assurance provisions of other specifications referenced in any of the contractual documents.

4.1.3.1 Surveillance.-Surveillance shall include, but is not limited to:

a. Observation of procedures concerning lot formation and identification.

b. Observation of sampling procedures and application of acceptance criteria.

c. Determination that all required examinations and tests are performed in accordance with the prescribed procedures of this specification, or approved equivalents thereto.

d. Review of procedures for control and disposition of non-conforming material.

4.1.3.2 Product inspection.-Physical inspection by the Government of contractor accepted product will be performed to the extent necessary to assure contractor compliance with the requirements of this specification and to determine the reliability of contractor records. Severity of Government inspection of individual characteristics will be directly related to the seriousness classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records, Specification MIL-G-2550 will apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:30Z
Check the source to verify that this is the current version before use.

4.1.3.3 Deviations and deficiencies.- Deviations from the prescribed or agreed upon procedures, or instances of poor practice which might have an effect on the quality of the product, shall be called to the attention of the contractor immediately. To avoid interference, with operation, the contractor shall designate a responsible official, or officials, to whom the Government inspector will report such instances. Failure of the contractor to correct deficiencies promptly shall be cause for suspension of acceptance until correction has been made or until conformance to prescribed criteria has been demonstrated.

4.2 Inspection provisions.

4.2.1 Lot formation.-A lot shall consist of parts produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification, and same specification revision. Drawing, specification, and process changes not affecting safety, performance, or fit, as determined by the Government, shall not necessitate changing the lot number.

4.2.2 Examination.-Sampling plans and procedures for the following classifications of defects shall be in accordance with Standard MIL-STD-105 except that inspection for critical defects, when listed, shall be 100 percent. Continuous sampling plans in accordance with Handbook ORD-M608-11 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics listed using an AQL of 0.25 percent for each major defect and an AQL of 0.40 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.3.

4.2.2.1 Disc, detonator (see dwgs. 8795797 and 8797036 covering a detail of dwg. 8797744)

Categories	Defects	Method of inspection
Critical: None defined.		
Major:	AQL 0.25 percent	
101.	Diameter	Gage
102.	Thickness	Gage
Minor:	AQL 0.40 percent	
201.	Evidence of poor workmanship (see 3.3)	Visual

4.2.2.2 Cup, detonator (see dwg. 8797745 covering a detail of dwg. 8797744)

Categories	Defects	Method of inspection
Critical: None defined.		
Major:	AQL 0.65 percent	
101.	Diameter of flash hole, minimum	Gage
102.	Length	Gage
103.	Thickness through bottom, minimum	Gage
104.	Concentricity of flash hole with inside diameter	Gage
105.	Cup damaged	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:30Z
Check the source to verify that this is the current version before use.

Minor: AQL 1.50 percent

201.	Inside diameter, minimum	Gage
202.	Outside diameter, maximum	Gage
203.	Evidence of poor workmanship (see 3.3)	Visual

4.2.3 Inspection equipment.-For the performance of the examinations and tests specified in 4.2.2 the contractor shall have available, and utilize correctly, all necessary gages identified by Gage List No. 7300115, or approved equivalents thereto. When inspecting the contractor's inspection equipment, the Government inspector will determine that the contractor has available and utilizes correctly, gages, of the required accuracy and precision and that the instruments are of the proper type and range to make measurements of the required accuracy. The contractor will have available a set of master gages, standards, and appropriate instruments for regularly scheduled calibration of his gages. Records of such regularly scheduled calibration will be maintained by the contractor and made available for review by the Government. The calibration of gages, standards and instruments will be periodically checked by authorized Government personnel.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.-Packing and marking shall be in accordance with Specification MIL-P-10025.

5.2 Data cards.-Data card information shall be as specified in Specification MIL-G-2550.

6. NOTES

6.1 Ordering data.-Procurement documents should specify the title, number and date of this specification.

Notice.-When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodian:
Army-Ordnance Corps

Preparing Activity:
Army-Ordnance Corps

GPO 902746

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:30Z
Check the source to verify that this is the current version before use.