A-34

MIL-F-46298C (PA)
04 November 1974
SUPERSEDING
MIL-F-46298B (MU)
30 August 1968

MILITARY SPECIFICATION

FIRING DEVICE, PULL RELEASE TYPE, M3 PARTS, LOADING, ASSEMBLING AND PACKING

*This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

*1.1 This specification covers the parts for and loading assembling and packing for one type of firing device designated as Firing Device, Pull Release Type, M3.

2. APPLICABLE DOCUMENTS

*2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-F-320	- Fiberboard, Corregated and Solid Sheet Stock (Container Grade and Cut Shape)
PPP-B-676	- Boxes, Set-up, Paperboard
TT-I-1795	- Ink, Marking, Stencil, Opaque for Porous Surfaces

MILITARY

MIL-P-116	- Preservation, Packaging, Methods of
MIL-B-117	- Bags, Interior Packaging
MIL-B-2427	- Boxes, Ammunition Packing, Wood Nailed

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 202610-22T05:30Z
Check the source to verify that this is the current version before use.

5 5

MIL-P-12951- Primer, Percussion, M39A1, Loading, Assembling and Packing
MIL-F-50449- Filler, Sheet Form (For use in Ammunition Containers)
*MIL-A-48078- Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
*MIL-STD-1168- Lot Numbering of Ammunition

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

8796522 - Marking Diagram and Sealing for Wood Packing Boxes
8837262 - Coupling, Base, Assembly
8837267 - Firing Device, Pull Release Type, M3 Assembly
8837280 - Dial Assembly

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

*(For meaning of asterisk (*) see 6.5).

3. Requirements

3.1 Material. - Materials shall be in accordance with applicable drawings and specifications.

3.2 Firing Device. - The firing device shall comply with all requirements specified on Drawing (dwg.) 8837267 and with all requirements specified in applicable specifications.

3.3 Non-functioning. - The firing device shall not function when a load of 6 pounds, minimum, is applied to the trip wire in a direction parallel to the longitudinal axis of the release pin.

95

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:30Z
Check the source to verify that this is the current version before use.

3.4 Functioning

*3.4.1 Pull of trip wire. - The firing device shall function the primer when a load of 12 pounds, maximum (max.) is applied to the trip wire in a direction parallel to the longitudinal axis of the release pin.

*3.4.2 Cutting of trip wire. - The firing device shall function the primer when adequate tension is applied to the trip wire to permit withdrawal of the safety pin, and subsequent cutting of the trip wire.

3.5 Embrittlement of springs. - Springs shall not break when pulled to the point of minimum permanent distortion.

*3.6 Workmanship. - All parts shall be fabricated and finished (or fabricated and loaded) in a thorough, workmanlike manner, and all manufacturing, processing and assembly operations shall be correctly performed. The parts shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

3.7 First Article Inspection. - The specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

*4.1 Responsibility for inspection and Standard Quality Assurance Provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply, and are hereby made a part of this detail specification.

*4.2 Classification of Inspection. - The following types of inspection shall be conducted on this item.

a. First Article Inspection
b. Quality Conformance Inspection

95

Source: https://assist.dla.mil -- Downloaded: 202610-22T05:30Z
Check the source to verify that this is the current version before use.

*4.3 First Article Inspection

4.3.1 Submission. - The Contractor shall submit a first article sample as designated by the Contracting Officer. The first article sample shall consist of fifty (50) complete assemblies without primers and thirty (30) complete sets of parts and sub-assemblies without primers (i.e., 30 each of every component and sub-assembly). The first article shall be evaluated in accordance with the provisions of 4.3.2 and 4.3.3.

4.3.2 Inspections to be Performed. - See MIL-A-48078 and paragraphs 4.4.2 and 4.4.3 specified herein. The inspections listed in 4.4.2.1 through 4.4.2.13 may be inspected for Critical and Major Defects only.

4.3.3 Rejection. - See MIL-A-48078.

*4.4 Quality Conformance Inspection

*4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078. Lot numbering as required shall be in accordance with MIL-STD-1168. In addition, each inspection lot of firing devices shall contain:

a. Parts from not more than one interfix lot number from one manufacturer.
b. Primers from not more than one interfix lot number from one manufacturer.

*4.4.2 Examination. - See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

95

Source: https://assist.dla.mil -- Downloaded: 202640-22T05:30Z
Check the source to verify that this is the currentversion before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8837278
4.4.2.1	Spring, Dial Winding Key				NEXT HIGHER ASSEMBLY 8837280
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major:	None Defined				
Minor:					
201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:
5

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.2	Pawl, Dial	1	1	8837273
				NEXT HIGHER ASSEMBLY 8837280

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Profile		0.40%	3.2	Gage
132.	Thickness		0.40%	3.2	Gage
Minor:					
201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Dial Bracket and Pawl Assembly		8837279
			NEXT HIGHER ASSEMBLY 8837280

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Protective finish incomplete or inadequate		0.40%	3.2	Visual
132.	Pawl above flush with edge of bracket		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

1

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T05:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Pin, Safety		8837272
			NEXT HIGHER ASSEMBLY 8837267

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Diameter of small portion of shaft		0.40%	3.2	Gage
132.	Diameter of small end, minimum (min)		0.40%	3.2	Gage
133.	Protective finish incomplete or inadequate		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-10T05:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Pin, Dial, Release		8837281
			NEXT HIGHER ASSEMBLY 8837280

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:					
101.	Diameter of tip		0.40%	3.2	Gage
Major B:					
131.	Diameter of thru hole		0.40%	3.2	Gage
132.	Diameter of shaft below tip		0.40%	3.2	Gage
133.	Diameter of large portion of shaft		0.40%	3.2	Gage
134.	Diameter of rear end, min.		0.40%	3.2	Gage
135.	Finish of sliding surface improper		0.40%	3.2	Visual
136.	Protective finish incomplete or inadequate		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

6

Source: https://assist.dla.mil -- Downloaded: 2026-02-27T05:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Spring, Pin, Firing	1 OF 1	8833502
			NEXT HIGHER ASSEMBLY 8837267

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B: 131.	Protective coating incomplete or inadequate		0.40%	3.2	Visual
Minor: 201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Pin, Firing	1 OF 1	8837269
			NEXT HIGHER ASSEMBLY 8837267

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Profile of firing pin point		0.40%	3.2	Gage
132.	Width of slots		0.40%	3.2	Gage
133.	Length of slots		0.40%	3.2	Gage
134.	Diameter of thru hole (prior to slotting)		0.40%	3.2	Gage
135.	True position of firing pin point with outside diameter (prior to slotting)		0.40%	3.2	Gage
136.	Location of thru hole		0.40%	3.2	Gage
137.	Outside diameter at rear end (prior to slotting)		0.40%	3.2	Gage
138.	Outside diameter at forward end		0.40%	3.2	Gage
139.	Diameter of dial release pin hole (prior to slotting)		0.40%	3.2	Gage
140.	Finish improper on sliding surface		0.40%	3.2	Visual
141.	Diameter of dial release pin hole and outside diameter at rear end (functional)		0.40%	3.2	Gage
Minor:					
201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

11

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T05:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Body				8837268
					NEXT HIGHER ASSEMBLY 8887267
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Pitch diameter of thread, maximum (max.)		0.40%	3.2	Gage
132.	Minor diameter of thread, min.		0.40%	3.2	Gage
133.	Diameter of firing pin hole		0.40%	3.2	Gage
134.	Diameter of head counterbore, max.		0.40%	3.2	Gage
135.	True position of firing pin hole with head counterbore		0.40%	3.2	Gage
136.	Diameter of firing pin spring hole, min.		0.40%	3.2	Gage
137.	True position of threads with head counterbore		0.40%	3.2	Gage
138.	Depth from bottom of head counterbore to firing pin hole, min.		0.40%	3.2	Gage
139.	Burr on interior surface		0.40%	3.2	Visual
Minor:					
201.	Total length		0.65%	3.2	Gage
202.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T05:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.9	Base, Coupling		8837263
			NEXT HIGHER ASSEMBLY 8837262

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Pitch diameter of larger thread		0.40%	3.2	Gage
132.	Major diameter of larger thread		0.40%	3.2	Gage
133.	Pitch diameter of smaller thread		0.40%	3.2	Gage
134.	Major diameter of smaller thread		0.40%	3.2	Gage
135.	Inside diameter of primer cavity, max.		0.40%	3.2	Gage
136.	Diameter of flash hole, min.		0.40%	3.2	Gage
137.	Depth of primer cavity		0.40%	3.2	Gage
138.	Length of shipping cup end		0.40%	3.2	Gage
139.	Flash hole obstructed		0.40%	3.2	Gage
Minor:					
201.	Total length		0.65%	3.2	Gage
202.	Length to flange from end		0.65%	3.2	Gage
203.	Diameter of shipping cup end		0.65%	3.2	Gage
204.	Outside diameter below larger thread		0.65%	3.2	Gage
205.	Finish improper		0.65%	3.2	Visual
206.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026/10-22T05:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Base Coupling Assembly				8837262
					NEXT HIGHER ASSEMBLY 8837267
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:					
101.	Primer missing or loose		0.40%	3.2	Visual/Manual
102.	Primer cocked (incorrectly seated)		0.40%	3.2	Visual
103.	Compound or other foreign matter on primer		0.40%	3.2	Visual
104.	Primer cracked or punctured		0.40%	3.2	Visual
Major B:					
131.	Excessive compound		0.40%	3.2	Visual
132.	Thread damaged		0.40%	3.2	Visual
133.	Crack, split or deep cut		0.40%	3.2	Visual
Minor:					
201.	Shipping cup missing or damaged (cracked or punctured)		0.65%	3.2	Visual
202.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-27 05:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Assembly				8837267
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:					
1.	Safety pin missing		100%	3.2	Visual
2.	Cotter safety pin missing		100%	3.2	Visual
3.	Cotter pin missing from safety pin		100%	3.2	Visual
4.	Cotter pin(s) not spread		100%	3.2	Visual
Major A:					
101.	Head loose in body		0.40%	3.2	Manual
102.	Crimp not 360 degrees		0.40%	3.2	Visual
103.	Component missing or loose		0.40%	3.2	Visual/Manual
Minor					
201.	Safety pin cord missing or improperly tied		0.65%	3.2	Visual
202.	Safety cotter pin cord missing or improperly tied		0.65%	3.2	Visual
203.	Marking incorrect, incomplete or illegible		0.65%	3.2	Visual
204.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

15

Source: https://assist.dla.mil/ Downloaded: 2026-02-10T22:05:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.12	Sealed Barrier Bag (Prior to Insertion in Packing Box)				(See 5.1.1)
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Waterproofness of barrier bag destroyed by rupture, puncture, or separation of heat seal	See MIL-P-116		4.5.8	Test
132.	Evidence of crushed carton (see Note 1)		0.40%	3.2	Visual
Minor:					
201.	Heat seal of barrier bag located so that one or more subsequent seals cannot be applied		0.65%	3.2	Visual
202.	Marking of bag misleading or unidentifiable		0.65%	3.2	Visual
203.	Evidence of poor workmanship		0.65%	3.6	Visual
	NOTE 1. - Package should be opened if there is evidence of crushing				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T05:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.13	Box, Packing		(See 5.2.1)
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Contents loose		0.40%	3.2	Manual
132.	Box damaged to the extent that contents are exposed or liable to become exposed		0.40%	3.2	Visual
133.	Strapping broken or missing		0.40%	3.2	Visual
Minor:					
201.	Strapping mislocated		0.65%	3.2	Visual
202.	Marking misleading or unidentifiable		0.65%	3.2	Visual
203.	Metallic seal missing, unsealed or incorrectly positioned		0.65%	3.2	Visual
204.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

17

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T05:30Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

*4.4.3.1 Spring embrittlement. (See 3.5) - Major A defect - A sample of 30 springs shall be selected from each heat treatment lot and tested as specified in 4.5.1. If one or more springs fail to comply with the specified requirement, the heat treatment lot represented by the sample springs shall be rejected. (Destructive Test).

*4.4.3.2 Pull test of cotter pin. (See dwg. 8837267) - Major A defect - The sampling plan for this requirement shall be in accordance with MIL-STD-105, using Code Letter H and an AQL of 1.00 percent. The test shall be performed as specified in 4.5.2. Any assembly which fails to comply with the specified requirement shall be classed defective and removed from the lot. Samples complying with the requirement may be returned to the lot. (Non-destructive test).

*4.4.3.3 Pull test of pin, cotter, safety (see dwg. 8837267) Major A defect. - The sampling plan for this requirement shall be in accordance with MIL-STD-105, using Code Letter H and an AQL of 1.00 percent. The test shall be performed as specified in 4.5.3. Any assembly which fails to comply with the specified requirement shall be classed defective and removed from the lot. Samples complying with the requirement may be returned to the lot. (Non-destructive Test).

*4.4.3.4 Pull test of pawl (see dwg. 8837279). -Major A defect - The sampling plan for this requirement shall be in accordance with MIL-STD-105, using Code Letter H and an AQL of 1.00 percent. The test shall be performed as specified in 4.5.4. Any assembly which fails to comply with the specified requirement shall be classed defective and removed from the lot. Samples complying with the requirement may be returned to the lot. (non-destructive test).

*4.4.3.5 Non-functioning (see 3.3) - Major A defect. - The sampling plan for this requirement shall be in accordance with MIL-STD-105, using Code Letter H and an AQL of 1.00 percent. The test shall be performed as specified in 4.5.5. Any assembly which fails to comply with the specified requirement shall be classed defective and removed from the lot. Samples complying with the requirement may be returned to the lot. (Non-destructive test).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:30Z
Check the source to verify that this is the current version before use.

*4.4.3.6 Functioning

4.3.3.6.1 Pull test (see 3.4.1) - Major A defect. - The sampling plan for this requirement shall be in accordance with MIL-STD-105, using Code Letter H and an AQL of 1.00 percent. The test shall be performed as specified in 4.5.6.1. Any assembly which fails to comply with the specified requirement shall be classed defective. Samples used in this test shall not be returned to the lot. (Destructive test)

4.4.3.6.2 Cutting test (see 3.4.2). - Major A defect. The sampling plan for this requirement shall be in accordance with MIL-STD-105, using Code Letter H an an AQL of 1.00 percent. The test shall be performed as specified in 4.5.6.2. Any assembly which fails to comply with the specified requirement shall be classed defective. Samples used in this test shall not be returned to the lot. (Destructive test)

*4.4.3.7 Check test for possible deterioration of primers - Major A defect. - If the total elapsed time between the original acceptance of any primer lot and the assembly of that lot into the firing devices exceeds two years, or if the primers have been subjected to adverse conditions, however brief, at any time since previous test, the primer lot shall be subjected to and must satisfactorily pass the check test specified in MIL-P-12951 immediately before the primer lot is assembled into the firing device assembly. This test shall be performed by the Contractor on primers selected by the Government inspector at the facility assembling the primer lot into the firing device assembly and shall be conducted at Government expense without cost to the contractor (see 6.4), who loaded the primers or the contractor assembling the primers into the firing device assembly. Furthermore, this test shall not constitute a basis of rejection against either contractor except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor. (Destructive test)

*4.4.3.8 Load test of springs at assembled height (see dwg. 8837278 and dwg. 8833502). - Major A defects. A sample of ten (10) dial winding key springs or firing pin springs as applicable shall be selected from each heat treatment batch. If any spring fails to comply with the applicable drawing requirement, the batch of springs represented by the sample shall be rejected. The test shall be performed as specified in 4.5.7. (Destructive test).

95

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:30Z
Check the source to verify that this is the current version before use.

*4.4.4 Inspection Equipment. - The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1 and the test method paragraphs (see 4.5). The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078.

*4.5 Test methods and procedures

*4.5.1 Spring embrittlement. - The spring shall be pulled until the minimum point of permanent distortion is reached. If the spring breaks when pulled to the point of permanent distortion it shall be classed defective. Springs so tested shall be discarded and not returned to the lot.

*4.5.2 Pull test of cotter pin. - The assembly shall be mounted in a suitable test fixture and a steady increasing force shall be applied, without impact, to the cotter pin so as to tend to remove the pin from the assembly. The force shall act in a direction parallel to the length of the pin and shall be applied at the eye. The assembly shall be classified defective if the force required to remove the pin is not in accordance with the specified drawing requirement.

*4.5.3 Pull test of pin, cotter, safety. - The assembly shall be mounted in a suitable test fixture and a steady increasing force shall be applied, without impact, to the safety cotter pin so as to tend to remove the pin from the assembly. The force shall act in a direction parallel to the length of the pin and shall be applied at the eye. The assembly shall be classified defective if the force required to remove the pin is not in accordance with the specified drawing requirement.

*4.5.4 Pull test of pawl. - The dial bracket and pawl assembly shall be mounted in a suitable test fixture and the minimum specified load applied in the direction of the open end of the slot in the bracket. The assembly shall be classed defective if the pawl shows evidence of separation from the dial bracket.

*4.5.5 Non-functioning. - The firing device assemblies shall be mounted in a suitable test fixture, the pin, safety, cotter removed, the trip wire attached and tension applied to the trip

Source: https://assist.dla.mil -- Downloaded: 202640-22T05:30Z
Check the source to verify that this is the current version before use.

wire by turning the winch on the dial and pawl assembly until it is possible to withdraw the safety pin. The specified load shall be applied to the trip wire in a direction parallel to the release pin and observation made for actuation of the firing pin. The firing device shall be classified defective if the firing pin is released.

4.5.6 Functioning

*4.5.6.1 Pull Test. - The firing device assembly shall be assembled in a suitable test fixture, the trip wire attached, and tension applied to the trip wire by turning the winch on the dial and pawl assembly unitl it is possible to withdraw the safety pin. The specified load shall be applied to the trip wire in a direction parallel to the longitudinal axis of the release pin and primer. The firing device shall be classed defective if the firing pin fails to release or the primer fails to function.

*4.5.6.2 Cutting test. - The firing device shall be assembled in a suitable test fixture, the trip wire attached and tension applied to the trip wire by turning the winch on the dial and pawl assembly until it is possible to withdraw the safety pin. The trip wire shall then be cut and observation made for actuation of the firing pin and primer. The firing device shall be classed defective if the firing pin fails to release or if the primer fails to function.

4.5.7 Load test of springs at assembled height. - The springs shall be maintained at the specified height for 24 hours minimum. The spring shall then be tested for compliance with the load requirement.

4.5.8 Heat seal test of sealed bag (see 5.1.1). - Major B Defect - Sampling, acceptance criteria and test procedures for this test shall be as specified in Specification MIL-P-116.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

*5.1.1 Level A. - The firing devices shall be packaged in paper set-up boxes conforming to the requirements of PPP-B-676, Type I, Class A in quantities of 5 devices each including two (2) spools of trip wire. Place a fiberboard filler on the top and bottom of box and add fillers along the ends, sides and tops as required. Filler material shall conform to PPP-F-320, Type

95

Source: https://assist.dla.mil -- Downloaded: 202610-22T05:30Z
Check the source to verify that this is the current version before use.

CF, Class Domestic, Variety SW, Grade 125. Size of fillers shall be equal to the inside length and width of the box surface it is intended for less approximately 1/2 inch. Blunt all corners of the box and insert in a heat sealed bag conforming to the requirements of MIL-B-117, Type I, Style I, Class E. Exhaust all excess air from the bag and close the opening by means of heat-sealing. Seals shall meet the heat seal requirements of MIL-P-116.

5.2 Packing

*5.2.1 Level A. - Pack forty (40) boxes flatwise, in five (5) layers of eight (8) boxes per layer in a nailed wood box conforming to the requirements of MIL-B-2427 Grade A Type II, Class 2. All interior surfaces of the box shall be lined with composition board, MIL-F-50449. Filler size shall be equal to theinside length and width of the box side, top, bottom or end for which it is intended, less approximately 1/2 inch. Boxes shall be closed and strapped in accordance with instructions contained in the appendix of the box specification.

5.3 Marking

5.3.1 Each box shall be printed, stamped or labeled and each barrier bag printed or stamped with the following information:

5 - FIRING DEVICE, PULL RELEASE TYPE
M3 W/2 SPOOLS TRIP WIRE LOT (MFR.
SYMBOL - NUMBER) LOADED (MO/YR).

Letters shall be capitals. Size of markings minimum 1/4 inch. Ink shall be black stencil ink TT-I-1795 or commercial waterproof ink.

*5.3.2 Shipping container. - The shipping container shall be marked in accordance with Drawing 8796522. The descriptive nomenclature to be applied shall be "200 Firing Device, Pull, Release Type, M3, with eighty (80) Spools, Trip Wire." The DOT marking to be applied shall be "Percussion Fuzes - Handle Carefully".

*6. NOTES

6.1 Ordering Data. - Procurement documents shall specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:30Z
Check the source to verify that this is the current version before use.

a. Title, number and date of this specification.
b. Provisions for submission of first article samples.
c. Provisions of MIL-A-48078.

6.2 Submission of Inspection Equipment Designs for Approval (See MIL-A-48078). Submit equipment designs as required, to Commander: Picatinny Arsenal, ATTN: SARPA-QA-T Dover, New Jersey 07801.

6.3 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M Dover, New Jersey 07801.

6.4 Check test for possible deterioration. - The following test is designed to prevent primers that have deteriorated from being assembled into major ammunition items. The test shall be performed on detonators from each lot which have been stored under normal conditions for more than two years or under adverse conditions for any period of time. If the specification for the ammunition item into which the detonators are assembled does not require that the check test be performed, the Contracting Officer should insert in the contract a provision for the performance of the check test for possible deterioration. Detonator assemblies shall be selected from each lot for this test.

6.5 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1375-A-110

Source: https://assist.dla.mil -- Downloaded: 202640-22T05:30Z
Check the source to verify that this is the current version before use.

100

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil - Downloaded: 2026-10-22T05:30Z
Check the source to verify that this is the current version before use.

515 943

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

85 943

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:30Z
Check the source to verify that this is the current version before use.