26

MIL-F-46298C(PA)
AMENDMENT 1
6 MAY 1976

MILITARY SPECIFICATION

FIRING DEVICE, PULL RELEASE TYPE, M3
PARTS, LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-F-46298C(PA) dated 4 November 1974 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1 To Federal Specifications add:

"TT-E-516 - Enamel, Lusterless, Quick-Drying, Styrenated Alkyd Type"

To Military Specifications add:

'MIL-F-11195 - Lacquer, Lusterless, Hot Spray"

PAGE 17A & 17B

4.4.2.14 & 4.4.2.15 Add new Classification of Defects as follows:

3190

FSC: 1375

S/S

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:29Z
Check the source to verify that this is the current version before use.

3190

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46298C(PA)
AMENDMENT 1

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.14	Spool	1	1	9312585
				NEXT HIGHER ASSEMBLY: 7548176

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Height of spool		0.40%	3.2	Gage
132	Thickness of hub		0.40%	3.2	Gage
133	Diameter of body of spool		0.40%	3.2	Gage
134	Diameter of large hole		0.40%	3.2	Gage
Minor					
201	Location of small hole		0.65%	3.2	Gage
202	Diameter of small hole		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4B10

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46298C(PA)
AMENDMENT 1

PARAGRAPH	TITLE		SHEET OF	DRAWING NUMBER
4.4.2.15	Wire Spool Assembly		1 1	7548186
				NEXT HIGHER ASSEMBLY
				8797446

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Wire not tight		0.40%	3.2	Visual
132	Wire above flush		0.40%	3.2	Visual - Straight edge
133	End of wire not inserted into plastic spool I.D.		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4B10

Source: http://assist.dla.mil -- Downloaded: 2026-10-22T05:29Z
Check the source to verify that this is the current version before use.

PAGE 19

4.4.3.9: Add as follows:

"4.4.3.9 Salt spray test of trip wire - Major A Defect - Sampling plan for this test shall be in accordance with applicable protective finish specified on drawing. Test shall be performed as specified in 4.5.9."

PAGE 21

4.5.9: Add as follows:

"4.5.9 Salt spray test - This test shall be performed in accordance with TT-E-516 or MIL-F-11195 whichever is applicable. The duration of the test shall be six (6) hours.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1375-A-170

3190

S/S

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:29Z
Check the source to verify that this is the current version before use.