INCH-POUND

MIL-M-46310A(MU)
AMENDMENT 1
13 December 1994

MILITARY SPECIFICATION

MOUNT, TELESCOPE: M137

This amendment form a part of MIL-M-46310A(MU), dated 8 September 1969, and is approved for use by the U.S. Army Armaments, Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the department of Defense.

PAGE 1

2.1, DRAWINGS:

Line 1: Delete "U.S. Army, Frankford Arsenal" and substitute "U.S. Army Armament Research, Development and Engineering Center (ARDEC)"

Under list of DRAWINGS: Add new drawings as follows:

"F5549108	Telescope, Collimating
F8565556	Pressure Tester, Two Station
F8658940	Inspection Aid
F11730831	Test Fixture for Mount Telescope M137"

PAGE 2

3.2: Delete in it's entireity and substitute the following:

"3.2 General Specification.-The contractor shall be responsible for the compliance with the requirements of MIL-F-13926."

PAGE 7

TABLE IV, under MAJOR: Add the following:

"119. Packaging 5.1 4.7"

4.4.1: Delete in it's entireity and substitute the following:

"4.4.1 General. Subsequent to meeting the requirements of Table I, three mounts shall be selected at random by a Government representative as a special sample from each 50 produced or each month's production, whichever occurs first. The sample shall meet the requirements and tests in Table I after being subjected to Table II testing."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:30Z
Check the source to verify that this is the current version before use.

PAGE 9

4.6.1.1: Delete in it's entireity and substitute the following:

"4.6.1.1 The temperature test shall be performed at the temperatures outlined in 3.3.1. When thermally stabilized at the specified temperature, the mount shall meet the performance requirements outlined in 3.3.1. The test equipment shall be of the standard type as outlined under "test facilities" in MIL-F-13926.

4.6.1.2, last sentence: Delete "F8665556" and substitute "F8565556".

PAGE 10

4.6.2.6: Delete in it's entirety and substitute the following:

"4.6.2.6 Elevation error and backlash. With the fixture and mount positioned as outlined in 4.6.2.1 and with the auxiliary telescope's sighting device assembled to the mount, insert an elevation into the mount from low to high thus excluding backlash. Rotate the fixture handwheel until the mount elevation level vial bubble is centered. Using a gunners quadrant (inspection aid) on the fixture quadrant seat assembly, measure the actual elevation. The difference between the whole number mount elevation and the actual reading from the gunners quadrant shall not exceed the limit outlined in 3.4.4.2. Place the gunners quadrant on the auxiliary telescope's sighting device and center the quadrant level vial bubble. Record this gunners quadrant reading. Rotate the mount elevation knob approximately one revolution beyond the elevation. Rotate the knob in the reverse direction back to the original whole number elevation, making sure not to overide this position. Center the gunners quadrant level bubble. Record this gunners quadrant reading. The difference between the first gunners quadrant reading and the second is considered backlash and shall not exceed the limit outlined in 3.4.4.3.1."

Add new paragraph 4.7 as follows:

"4.7 Packaging inspection. The preservation, packing, and marking shall be inspected to verify conformance to the requirements of 5.1."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1240-0003)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:30Z
Check the source to verify that this is the current version before use.