FED. SUP CLASS
6640

REVIEW ACTIVITIES: OTHER - NSA
USER ACTIVITIES: ARMY - ME



MS36088-1



MS36088-2 through
MS36088-4

PART NUMBER	CAPACITY ml +15%	DIMENSIONAL DATA				
		FILTER (± 0.02 mm)		Body (± 1 mm)		
		DIA OF PERFORATIONS	DIA OF PERFORATED AREA	HEIGHT OVERALL	TOP OD	BASE OD
MS36088-1	1.5	0.5	7.5	15	15	12
MS36088-2	13.0	0.7	11.0	34	29	18
MS36088-3	25.0	0.7	16.0	41	36	22
MS36088-4	40.0	0.6	19.0	47	40	25

MATERIAL: Vitreous, ceramic, whiteware.

FINSIH: Glazed inside and outside with the exception of the outside bottom surface.

DESIGN: Crucibles, with the exception of MS36088-1, shall have a flat, perforated base to give a firm and stable resting surface. The side wall shall form a sloping and convex surface extending to the brim.

MS36088-1 shall have a perforated base and straight, tapered sides.

NOTES:
1. For design feature purposes this standard takes precedence over procurement document referenced herein.
2. Referenced document shall be of the issue in effect on date of invitations for bid.

APPROVED 28 June 1961 REVISED (A) 4 JUN 69

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

(A) ENTIRE STANDARD REVISED

P.A. MU	TITLE	MILITARY STANDARD
Other Cust MS 82	CRUCIBLE, FILTERING, LABORATORY porcelain, Gooch	MS36088
Procurement Specification NNN-C-680	SUPERSEDES:	SHEET 1 OF 1

DD FORM 1 SEP 63 672 (Coordinated)

EDITION OF 1 SEP 57 MAY BE USED.

☆ U. S. GOVERNMENT PRINTING OFFICE: 1969-341-520/A-7329

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:34Z
Check the source to verify that this is the current version before use.