FED. SUP CLASS
6640



PART NUMBER	NOMINAL DIMENSIONAL DATA (MM)			CAPACITY ML
	TOP ID BOWL	STEM LG	STEM OD	
MS36578-1	35	50	7	9
MS36578-2	55	60	8	36
MS36578-3	65	65	8.5	60
MS36578-6	75	75	9	95
MS36578-7	90	90	10	160
MS36578-4	100	100	11.5	225
MS36578-5	160	125	16	930

MATERIAL: Polypropylene, Natural Color, in accordance with Federal Specification L-P-394, Type I, Autoclavable.

FINISH: Funnels shall be smooth and free of bubbles and blisters.

DESIGN: The bowl shall be 60° angle with internal ribs at 58° to permit rapid filtration when used with standard filter paper. Outside ribbing shall be included to eliminate air lock. The stem shall have an oblique termination.

NOTES:

1. Items differing from this Military Standard by minor variations in design or dimensions are considered standard under this document, provided such variations do not affect performance and are not in conflict with the material requirements specified herein.
2. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
3. Referenced documents shall be of the issue in effect on date of invitations for bid.
4. FSCM: 05178, 22527, and 59728.

APPROVED 4 June 1969 REVISED (A) 3 FEB 1984

(A) ENTIRE STANDARD REVISED

P.A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
EA		FUNNELS, COMMON, LABORATORY, ANALYTICAL	MS36578
Other Cust MS 99			
Procurement Specifications NNN-F-001652	SUPERSEDES:		SHEET 1 OF 1

USER ACTIVITIES: ARMY - MD, DM
NAVY - MS

REVIEWER ACTIVITIES: ARMY - ME
AIR FORCE - 82

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23117:432
Check the source to verify that this is the current version before use.