NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/30E
27 September 1996
SUPERSEDING
MIL-L-11484/30D
14 January 1994

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, EXCEPTIONAL CIVILIAN SERVICE AWARD, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11484 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

DASH NO.
-1, -4: Exceptional Civilian Service
-2, -5: Additional Exceptional Civilian Service
-3, -6: Exceptional/Meritorious Civilian Service
(DESIGNATES RECIPIENT RECEIVED BOTH AWARDS)

MATERIAL:
-1, -4: Red Brass
-2, -5: Red Brass with a Minimum 2 Point Ruby Stone
-3, -6: Red Brass with a Minimum 2 Point, Grade A, Single Stone, White Diamond

FINISH: Gold Plate, Rose Gold Plate, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 20.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:14Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
DIAMETER: 5/8 inch (1.59 cm) (REF)
THICKNESS: 0.050 inch ± 0.005 inch (0.127 cm ± 0.012 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The design for Dash No. -1 and -4 are identical to the figure shown.

3. The design of -2, -3, -5, and -6 are identical to the figure shown except for the stone located on the center of the eagle's breast. The stones shall be set in the eagle's breast with a three or four bead setting. The ruby stone for Dash -2 and -5 may be genuine or synthetic.

4. Lapel buttons shall be lacquered.

5. Dash No. -1 through -3 attaching device shall be prong with pick and flat ball type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

6. Dash No. -4 through -6 attaching device shall have a pin and catch type attaching device fused or soldered to the reverse of the lapel button. The pin shall be located on the horizontal center line of the lapel button with hinge and catch equidistant from the outer edges.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 45

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
DLA - CT

(Project No. 8455-0858)


Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:14Z
Check the source to verify that this is the current version before use.